

NIORA MIRROR

TECHNICAL INFORMATION (For connection types, please refer to the last page)

Height x Width ( H x W )	Tube	Depth (D)	Pipe Centers (A)	Wall To Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type	Prices Ex. Vat
mm	pieces	mm	mm	mm	mm	mm	mm	mm	L		
1800x682	7	60	1745	56-65	86-95	26-35	4	80	1,92	C-E-D	£ 429,00

HEAT OUTPUTS INFORMATION

Height x Width ( H x W )	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
1800x682	1405	4791	1827	6229

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions ( H x W x D )
kg	kg	m³	mm
23,51	22,33	0,14	1920X722X100

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	✓	✓

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request.  
Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel