

TECHNICAL INFORMATION

Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type	Prices Ex. Vat
mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L		
300 x 500	4 (2+2)	61	255	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 72.00
300 x 792	6 (2+2)	61	255	56/65	86/95	26/35	4	140	80	0,45	C-E-D	£ 112.00
300 x 1096	8 (2+2)	61	255	56/65	86/95	26/35	4	140	80	0,63	C-E-D	£ 155.00
300 x 1400	10 (2+2)	61	255	56/65	86/95	26/35	4	140	80	0,80	C-E-D	£ 194.00
300 x 1704	12 (2+2)	61	255	56/65	86/95	26/35	4	140	80	0,97	C-E-D	£ 245.00
400 x 500	4 (2+2)	61	355	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 79.00
400 x 792	6 (2+2)	61	355	56/65	86/95	26/35	4	140	80	0,45	C-E-D	£ 123.00
400 x 1096	8 (2+2)	61	355	56/65	86/95	26/35	4	140	80	0,63	C-E-D	£ 168.00
400 x 1400	10 (2+2)	61	355	56/65	86/95	26/35	4	140	80	0,80	C-E-D	£ 211.00
400 x 1704	12 (2+2)	61	355	56/65	86/95	26/35	4	140	80	0,97	C-E-D	£ 264.00
500 x 500	4 (2+2)	61	455	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 86.00
500 x 792	6 (2+2)	61	455	56/65	86/95	26/35	4	140	80	0,45	C-E-D	£ 132.00
500 x 1096	8 (2+2)	61	455	56/65	86/95	26/35	4	140	80	0,63	C-E-D	£ 182.00
500 x 1400	10 (2+2)	61	455	56/65	86/95	26/35	4	140	80	0,80	C-E-D	£ 227.00
500 x 1704	12 (2+2)	61	455	56/65	86/95	26/35	4	140	80	0,97	C-E-D	£ 285.00
600 x 500	4 (2+2)	61	555	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 93.00
600 x 792	6 (2+2)	61	555	56/65	86/95	26/35	4	140	80	0,45	C-E-D	£ 143.00
600 x 1096	8 (2+2)	61	555	56/65	86/95	26/35	4	140	80	0,63	C-E-D	£ 194.00
600 x 1400	10 (2+2)	61	555	56/65	86/95	26/35	4	140	80	0,80	C-E-D	£ 243.00
600 x 1704	12 (2+2)	61	555	56/65	86/95	26/35	4	140	80	0,97	C-E-D	£ 304.00
800 x 500	4 (2+2)	61	755	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 106.00
1000 x 500	4 (2+2)	61	955	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 119.00
1200 x 500	4 (2+2)	61	1155	56/65	86/95	26/35	4	152	80	0,29	C-E-D	£ 133.00

HEAT OUTPUTS INFORMATION

Width x Height (W x H)	Heat Outputs		Heat Outputs	
		ΔT 50 °C		ΔT 60 °C
mm	Watt	Btu	Watt	Btu
300 x 500	167	570	218	744
300 x 792	256	873	333	1136
300 x 1096	347	1184	452	1542
300 x 1400	438	1494	570	1944
300 x 1704	529	1804	688	2347
400 x 500	217	740	283	966
400 x 792	332	1133	432	1474
400 x 1096	449	1532	584	1992
400 x 1400	565	1927	735	2507
400 x 1704	681	2323	886	3022
500 x 500	270	921	351	1197
500 x 792	412	1405	536	1828
500 x 1096	554	1890	721	2459
500 x 1400	697	2377	907	3093
500 x 1704	840	2865	1092	3724
600 x 500	326	1112	424	1446
600 x 792	494	1685	643	2193
600 x 1096	665	2268	865	2950
600 x 1400	835	2848	1086	3704
600 x 1704	1006	3431	1308	4461
800 x 500	408	1392	531	1811
1000 x 500	483	1648	628	2142
1200 x 500	551	1879	717	2445

LOGISTICS INFORMATION

Width x Height (W x H)	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
300 x 500	3,7	4,1	0,02	600 x 340 x 85
300 x 792	5,4	6,3	0,05	892 x 540 x 85
300 x 1096	7,2	8,3	0,06	1196 x 440 x 110
300 x 1400	9	10,5	0,07	1500 x 540 x 85
300 x 1704	10,9	12,8	0,1	1804 x 640 x 85
400 x 500	4,3	4,7	0,03	600 x 440 x 85
400 x 792	6,3	7,3	0,05	892 x 640 x 85
400 x 1096	8,4	9,6	0,08	1196 x 540 x 110
400 x 1400	10,5	12,2	0,09	1500 x 640 x 85
400 x 1704	12,6	13,8	0,06	1804 x 340 x 85
500 x 500	4,8	5,3	0,03	600 x 540 x 85
500 x 792	7,2	7,9	0,04	892 x 440 x 85
500 x 1096	9,6	11	0,09	1196 x 640 x 110
500 x 1400	12	13,4	0,07	1500 x 540 x 85
500 x 1704	14,4	16,4	0,1	1804 x 640 x 85
600 x 500	5,4	5,9	0,04	600 x 640 x 85
600 x 792	8,1	9,5	0,09	892 x 840 x 110
600 x 1096	10,8	11,6	0,05	1196 x 340 x 110
600 x 1400	13,5	14,5	0,06	1500 x 340 x 110
600 x 1704	16,2	17,4	0,07	1804 x 340 x 110
800 x 500	6,6	7,1	0,03	600 x 440 x 85
1000 x 500	7,8	8,3	0,03	600 x 440 x 85
1200 x 500	9	9,6	0,03	600 x 540 x 85

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3	TR
x	x	x	x	x	x	✓