

BAMBOO

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010100503000239	280 x 240	2	39	245	37-46	63-72	24-33	1	119	0,22	C
5010100503000359	280 x 360	3	39	245	37-46	63-72	24-33	1	119	0,33	C
5010100503000479	280 x 480	4	39	245	37-46	63-72	24-33	1	119	0,43	C-E-D
5010100503000599	280 x 600	5	39	245	37-46	63-72	24-33	1	119	0,54	C-E-D
5010100503000719	280 x 720	6	39	245	37-46	63-72	24-33	1	119	0,65	C-E-D
5010100503000839	280 x 840	7	39	245	37-46	63-72	24-33	1	119	0,76	C-E-D
5010100503000959	280 x 960	8	39	245	37-46	63-72	24-33	1	119	0,86	C-E-D
5010100503001079	280 x 1080	9	39	245	37-46	63-72	24-33	1	119	0,97	C-E-D
5010100503001199	280 x 1200	10	39	245	37-46	63-72	24-33	1	119	1,08	C-E-D
5010100503001319	280 x 1320	11	39	245	37-46	63-72	24-33	1	119	1,18	C-E-D
5010100503001439	280 x 1440	12	39	245	37-46	63-72	24-33	1	119	1,29	C
5010100503001559	280 x 1560	13	39	245	37-46	63-72	24-33	1	119	1,40	C
5010100503001679	280 x 1680	14	39	245	37-46	63-72	24-33	1	119	1,51	C
5010100503001799	280 x 1800	15	39	245	37-46	63-72	24-33	1	119	1,61	C
5010100503001919	280 x 1920	16	39	245	37-46	63-72	24-33	1	119	1,72	C
5010100504000239	380 x 240	2	39	345	37-46	63-72	24-33	1	119	0,25	C
5010100504000359	380 x 360	3	39	345	37-46	63-72	24-33	1	119	0,37	C
5010100504000479	380 x 480	4	39	345	37-46	63-72	24-33	1	119	0,49	C-E-D
5010100504000599	380 x 600	5	39	345	37-46	63-72	24-33	1	119	0,61	C-E-D
5010100504000719	380 x 720	6	39	345	37-46	63-72	24-33	1	119	0,73	C-E-D
5010100504000839	380 x 840	7	39	345	37-46	63-72	24-33	1	119	0,86	C-E-D
5010100504000959	380 x 960	8	39	345	37-46	63-72	24-33	1	119	0,98	C-E-D
5010100504001079	380 x 1080	9	39	345	37-46	63-72	24-33	1	119	1,10	C-E-D
5010100504001199	380 x 1200	10	39	345	37-46	63-72	24-33	1	119	1,22	C-E-D
5010100504001319	380 x 1320	11	39	345	37-46	63-72	24-33	1	119	1,34	C-E-D
5010100504001439	380 x 1440	12	39	345	37-46	63-72	24-33	1	119	1,46	C
5010100504001559	380 x 1560	13	39	345	37-46	63-72	24-33	1	119	1,58	C
5010100504001679	380 x 1680	14	39	345	37-46	63-72	24-33	1	119	1,71	C
5010100504001799	380 x 1800	15	39	345	37-46	63-72	24-33	1	119	1,83	C
5010100504001919	380 x 1920	16	39	345	37-46	63-72	24-33	1	119	1,95	C
5010100505000239	480 x 240	2	39	445	37-46	63-72	24-33	1	119	0,28	C
5010100505000359	480 x 360	3	39	445	37-46	63-72	24-33	1	119	0,41	C
5010100505000479	480 x 480	4	39	445	37-46	63-72	24-33	1	119	0,55	C-E-D
5010100505000599	480 x 600	5	39	445	37-46	63-72	24-33	1	119	0,68	C-E-D
5010100505000719	480 x 720	6	39	445	37-46	63-72	24-33	1	119	0,82	C-E-D
5010100505000839	480 x 840	7	39	445	37-46	63-72	24-33	1	119	0,96	C-E-D
5010100505000959	480 x 960	8	39	445	37-46	63-72	24-33	1	119	1,09	C-E-D
5010100505001079	480 x 1080	9	39	445	37-46	63-72	24-33	1	119	1,23	C-E-D
5010100505001199	480 x 1200	10	39	445	37-46	63-72	24-33	1	119	1,36	C-E-D
5010100505001319	480 x 1320	11	39	445	37-46	63-72	24-33	1	119	1,50	C-E-D
5010100505001439	480 x 1440	12	39	445	37-46	63-72	24-33	1	119	1,63	C
5010100505001559	480 x 1560	13	39	445	37-46	63-72	24-33	1	119	1,77	C
5010100505001679	480 x 1680	14	39	445	37-46						

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		
	mm	Watt	Btu	Watt	Btu
5010100503000239	62	213	81	277	
5010100503000359	94	319	122	415	
5010100503000479	125	426	162	553	
5010100503000599	156	532	203	691	
5010100503000719	187	638	243	830	
5010100503000839	218	745	284	968	
5010100503000959	250	851	324	1106	
5010100503001079	281	957	365	1245	
5010100503001199	312	1064	406	1383	
5010100503001319	343	1170	446	1521	
5010100503001439	374	1276	487	1659	
5010100503001559	406	1383	527	1798	
5010100503001679	437	1489	568	1936	
5010100503001799	468	1596	608	2074	
5010100503001919	499	1702	649	2212	
5010100504000239	85	290	111	377	
5010100504000359	128	435	166	565	
5010100504000479	170	580	221	754	
5010100504000599	213	725	276	942	
5010100504000719	255	870	332	1131	
5010100504000839	298	1015	387	1319	
5010100504000959	340	1160	442	1508	
5010100504001079	383	1305	497	1696	
5010100504001199	425	1450	553	1884	
5010100504001319	468	1595	608	2073	
5010100504001439	510	1739	663	2261	
5010100504001559	553	1884	718	2450	
5010100504001679	595	2029	774	2638	
5010100504001799	638	2174	829	2827	
5010100504001919	680	2319	884	3015	
5010100505000239	109	370	141	482	
5010100505000359	163	556	212	722	
5010100505000479	217	741	282	963	
5010100505000599	272	926	353	1204	
5010100505000719	326	1111	424	1445	
5010100505000839	380	1296	494	1685	
5010100505000959	434	1482	565	1926	
5010100505001079	489	1667	635	2167	
5010100505001199	543	1852	706	2408	
5010100505001319	597	2037	777	2648	
5010100505001439	652	2222	847	2889	
5010100505001559	706	2408	918	3130	
5010100505001679	760	2593	988	3371	
5010100505001799	815	2778	1059	3611	
5010100505001919	869	2963	1130	3852	
5010100506000239	133	454	173	591	
5010100506000359	200	681	260	886	
5010100506000479	266	909	346	1181	
5010100506000599	333	1136	433	1476	
5010100506000719	400	1363	520	1772	
5010100506000839	466	1590	606	2067	
5010100506000959	533	1817	693	2362	
5010100506001079	599	2044	779	2658	
5010100506001199	666	2271	866	2953	
5010100506001319	733	2499	953	3248	
5010100506001439	799	2726	1039	3543	
5010100506001559	866	2953	1126	3839	
5010100506001679	933	3180	1212	4134	
5010100506001799	999	3407	1299	4429	
5010100506001919	1066	3634	1385	4725	
5010100507000239	152	519	198	674	
5010100507000359	228	778	297	1011	
5010100507000479	304	1037	395	1348	
5010100507000599	380	1296	494	1685	
5010100507000719	456	1556	593	2022	
5010100507000839	532	1815	692	2359	
5010100507000959	608	2074	791	2696	
5010100507001079	684	2333	890	3034	
5010100507001199	760	2593	988	3371	
5010100507001319	836	2852	1087	3708	
5010100507001439	912	3111	1186	4045	
5010100507001559	988	3371	1285	4382	
5010100507001679	1064	3630	1384	4719	
5010100507001799	1141	3889	1483	5056	
5010100507001919	1217	4148	1581	5393	
5010100508000239	170	580	221	754	
5010100508000359	255	870	332	1131	
5010100508000479	340	1160	442	1508	
5010100508000599	425	1450	553	1884	
5010100508000719	510	1739	663	2261	
5010100508000839	595	2029	774	2638	

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
1.44	2.28	0.01	390X274X74
2.16	3.21	0.02	390X394X74
2.87	3.91	0.02	390X514X74
3.59	4.85	0.02	390X634X74
4.30	5.72	0.03	390X754X74
5.02	6.55	0.03	390X874X74
5.73	7.36	0.03	390X994X74
6.45	8.19	0.04	390X1114X74
7.17	9.02	0.04	390X1234X74
7.89	9.84	0.04	390X1354X74
8.59	10.64	0.05	390X1474X74
9.31	11.47	0.05	390X1594X74
10.03	12.29	0.05	390X1714X74
10.75	13.11	0.06	390X1834X74
11.46	13.93	0.06	390X1954X74
1.71	2.63	0.01	490X274X74
2.56	3.71	0.02	490X394X74
3.41	4.59	0.02	490X514X74
4.26	5.67	0.03	490X634X74
5.10	6.68	0.03	490X754X74
5.96	7.67	0.04	490X874X74
6.81	8.65	0.04	490X994X74
7.66	9.63	0.05	490X1114X74
8.51	10.61	0.05	490X1234X74
9.36	11.58	0.05	490X1354X74
10.20	12.55	0.06	490X1474X74
11.06	13.54	0.06	490X1594X74
11.91	14.52	0.07	490X1714X74
12.76	15.50	0.07	490X1834X74
13.61	16.47	0.08	490X1954X74
1.97	2.98	0.02	590X274X74
2.96	4.22	0.02	590X394X74
3.95	5.25	0.03	590X514X74
4.93	6.48	0.03	590X634X74
5.91	7.67	0.04	590X754X74
6.90	8.82	0.04	590X874X74
7.88	9.94	0.05	590X994X74
8.87	11.08	0.05	590X1114X74
9.85	12.20	0.06	590X1234X74
10.84	13.35	0.06	590X1354X74
11.82	14.48	0.07	590X1474X74
12.80	15.61	0.07	590X1594X74
13.79	16.74	0.08	590X1714X74
14.77	17.87	0.09	590X1834X74
15.76	19.02	0.09	590X1954X74
2.24	3.35	0.02	690X274X74
3.36	4.73	0.03	690X394X74
4.48	5.92	0.03	690X514X74
5.60	7.31	0.04	690X634X74
6.72	8.66	0.04	690X754X74
7.84	9.96	0.05	690X874X74
8.96	11.24	0.06	690X994X74
10.08	12.52	0.06	690X1114X74
11.20	13.81	0.07	690X1234X74
12.32	15.10	0.07	690X1354X74
13.43	16.38	0.08	690X1474X74
14.55	17.67	0.09	690X1594X74
15.67	18.97	0.09	690X1714X74
16.79	20.25	0.10	690X1834X74
17.91	21.55	0.10	690X1954X74
2.51	3.70	0.02	790X274X74
3.77	5.25	0.03	790X394X74
5.02	6.59	0.04	790X514X74
6.28	8.15	0.04	790X634X74
7.52	9.64	0.05	790X754X74
8.78	11.08	0.06	790X874X74
10.03	12.53	0.06	790X994X74
11.29	13.99	0.07	790X1114X74
12.54	15.42	0.08	790X1234X74
13.79	16.87	0.08	790X1354X74
15.04	18.32	0.09	790X1474X74
16.29	19.75	0.10	790X1594X74
17.55	21.20	0.11	790X1714X74
18.80	22.65	0.11	790X1834X74
20.06	24.10	0.12	790X1954X74
2.78	4.05	0.02	890X274X74
4.17	5.76	0.03	890X394X74
5.56	7.26	0.04	890X514X74
6.95	8.97	0.05	890X634X74
8.33	10.62	0.05	890X754X74
9.72	12.22	0.06	890X874X74

BAMBOO

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010100508000959	780 x 960	8	39	745	37-46	63-72	24-33	1	119	1.43	C-E-D
5010100508001079	780 x 1080	9	39	745	37-46	63-72	24-33	1	119	1.61	C-E-D
5010100508001199	780 x 1200	10	39	745	37-46	63-72	24-33	1	119	1.79	C-E-D
5010100508001319	780 x 1320	11	39	745	37-46	63-72	24-33	1	119	1.97	C-E-D
5010100508001439	780 x 1440	12	39	745	37-46	63-72	24-33	1	119	2.15	C
5010100508001559	780 x 1560	13	39	745	37-46	63-72	24-33	1	119	2.33	C
5010100508001679	780 x 1680	14	39	745	37-46	63-72	24-33	1	119	2.51	C
5010100508001799	780 x 1800	15	39	745	37-46	63-72	24-33	1	119	2.69	C
5010100508001919	780 x 1920	16	39	745	37-46	63-72	24-33	1	119	2.86	C
5010100509000239	880 x 240	2	39	845	37-46	63-72	24-33	1	119	0.39	C
5010100509000359	880 x 360	3	39	845	37-46	63-72	24-33	1	119	0.58	C
5010100509000479	880 x 480	4	39	845	37-46	63-72	24-33	1	119	0.76	C-E-D
5010100509000599	880 x 600	5	39	845	37-46	63-72	24-33	1	119	0.97	C-E-D
5010100509000719	880 x 720	6	39	845	37-46	63-72	24-33	1	119	1.16	C-E-D
5010100509000839	880 x 840	7	39	845	37-46	63-72	24-33	1	119	1.36	C-E-D
5010100509000959	880 x 960	8	39	845	37-46	63-72	24-33	1	119	1.55	C-E-D
5010100509001079	880 x 1080	9	39	845	37-46	63-72	24-33	1	119	1.74	C-E-D
5010100509001199	880 x 1200	10	39	845	37-46	63-72	24-33	1	119	1.93	C-E-D
5010100509001319	880 x 1320	11	39	845	37-46	63-72	24-33	1	119	2.13	C-E-D
5010100509001439	880 x 1440	12	39	845	37-46	63-72	24-33	1	119	2.32	C
5010100509001559	880 x 1560	13	39	845	37-46	63-72	24-33	1	119	2.51	C
5010100509001679	880 x 1680	14	39	845	37-46	63-72	24-33	1	119	2.71	C
5010100509001799	880 x 1800	15	39	845	37-46	63-72	24-33	1	119	2.90	C
5010100509001919	880 x 1920	16	39	845	37-46	63-72	24-33	1	119	3.09	C
5010100510000239	980 x 240	2	39	945	37-46	63-72	24-33	1	119	0.42	C
5010100510000359	980 x 360	3	39	945	37-46	63-72	24-33	1	119	0.63	C
5010100510000479	980 x 480	4	39	945	37-46	63-72	24-33	1	119	0.83	C-E-D
5010100510000599	980 x 600	5	39	945	37-46	63-72	24-33	1	119	1.04	C-E-D
5010100510000719	980 x 720	6	39	945	37-46	63-72	24-33	1	119	1.25	C-E-D
5010100510000839	980 x 840	7	39	945	37-46	63-72	24-33	1	119	1.46	C-E-D
5010100510000959	980 x 960	8	39	945	37-46	63-72	24-33	1	119	1.66	C-E-D
5010100510001079	980 x 1080	9	39	945	37-46	63-72	24-33	1	119	1.87	C-E-D
5010100510001199	980 x 1200	10	39	945	37-46	63-72	24-33	1	119	2.08	C-E-D
5010100510001319	980 x 1320	11	39	945	37-46	63-72	24-33	1	119	2.29	C-E-D
5010100510001439	980 x 1440	12	39	945	37-46	63-72	24-33	1	119	2.49	C
5010100510001559	980 x 1560	13	39	945	37-46	63-72	24-33	1	119	2.70	C
5010100510001679	980 x 1680	14	39	945	37-46	63-72	24-33	1	119	2.91	C
5010100510001799	980 x 1800	15	39	945	37-46	63-72	24-33	1	119	3.11	C
5010100510001919	980 x 1920	16	39	945	37-46	63-72	24-33	1	119	3.32	C
5010100512000239	1180 x 240	2	39	1145	37-46	63-72	24-33	1	119	0.48	C
5010100512000359	1180 x 360	3	39	1145	37-46	63-72	24-33	1	119	0.71	C
5010100512000479	1180 x 480	4	39	1145	37-46	63-72	24-33	1	119	0.95	C-E-D
5010100512000599	1180 x 600	5	39	1145	37-46	63-72	24-33	1	119	1.18	C-E-D
5010100512000719	1180 x 720	6	39	1145	37-46	63-72	24-33	1	119	1.42	C-E-D
5010100512000839	1180 x 840	7	39	1145	37-46	63-72	24-33	1	119	1.66	C-E-D
5010100512000959	1180 x 960	8	39	1145	37-46	63-72	24-33	1	119	1.89	C-E-D
5010100512001079	1180 x 1080	9	39	1145	37-46	63-72	24-33	1	119	2.13	C-E-D
5010100512001199	1180 x 1200	10	39	1145	37-46	63-72	24-33	1	119	2.36	C-E-D
5010100512001319	1180 x 1320	11	39	1145	37-46	63-72	24-33	1	119	2.60	C-E-D
5010100512001439	1180 x 1440	12	39	1145	37-46	63-72	24-33	1	119	2.84	C
5010100512001559	1180 x 1560	13	39	1145	37-46	63-72	24-33	1	119	3.07	C
5010100512001679	1180 x 1680	14	39	1145	37-46	63-72	24-33	1	119	3.31	C
5010100512001799	1180 x 1800	15	39	1145	37-46	63-72	24-33	1	119	3.54	C
5010100514000239	1380 x 240	2	39	1345	37-46	63-72	24-33	1	119	0.53	C
5010100514000359	1380 x 360	3	39	1345	37-46	63-72	24-33	1	119	0.80	C
5010100514000479	1380 x 480	4	39	1345	37-46	63-72	24-33	1	119	1.06	C-E-D
5010100514000599	1380 x 600	5	39	1345	37-46	63-72	24-33	1	119	1.33	C-E-D
5010100514000719	1380 x 720	6	39	1345	37-46	63-72	24-33	1	119	1.59	C-E-D
5010100514000839	1380 x 840	7	39	1345	37-46	63-72	24-33	1	119	1.86	C-E-D
5010100514000959	1380 x 960	8	39	1345	37-46	63-72	24-33	1	119	2.12	C-E-D
5010100514001079	1380 x 1080	9	39	1345	37-46	63-72	24-33	1	119	2.39	C-E-D
5010100514001199	1380 x 1200	10	39	1345	37-46	63-72	24-33	1	119	2.65	C-E-D
5010100514001319	1380 x 1320	11	39	1345	37-46	63-72	24-33	1	119	2.91	C-E-D
5010100514001439	1380 x 1440	12	39	1345	37-46	63-72	24-33	1	119	3.18	C
5010100514001559	1380 x 1560	13	39	1345	37-46	63-72	24-33	1	119	3.44	C
5010100514001679	1380 x 1680	14	39	1345	37-46	63-72	24-33	1	119	3.71	C
5010100514001799	1380 x 1800	15	39	1345	37-46	63-72	24-33	1	119	3.97	C
5010100516000239	1580 x 240	2	39	1545	37-46	63-72	24-33	1	119	0.59	C
5010100516000359	1580 x 360	3	39	1545	37-46	63-72	24-33	1	119	0.88	C
5010100516000479	1580 x 480	4	39	1545	37-46	63-72	24-33	1	119	1.18	C-E-D
5010100516000599	1580 x 600	5	39	1545	37-46	63-72	24-33	1	119	1.47	C-E-D
5010100516000719	1580 x 720	6	39	1545	37-46	63-72	24-33	1	119	1.76	C-E-D
5010100516000839	1580 x 840	7	39	1545	37-46	63-72	24-33	1	119	2.06	C-E-D
5010100516000959	1580 x 960	8	39	1545	37-46	63-72	24-33	1	119	2.35	C-E-D
5010100516001079	1580 x 1080	9	39	1545	37-46	63-72	24-33	1	119	2.64	C-E-D
5010100516001199	1580 x 1200	10	39	1545	37-46	63-72	24-33	1	119	2.94	C-E-D
5010100518000239	1780 x 240	2	39	1745	37-46	63-72	24-33	1	119	0.65	C
5010100518000359	1780 x 360	3	39	1745	37-46	63-72	24-33	1	119	0.97	C
5010100518000479	1780 x 480	4	39	1745	37-46	63-72	24-33	1	119	1.29	C-E-D
5010100518000599	1780 x 600	5	39	1745	37-46	63-72	24-33	1	119	1.61	C-E-D
5010100518000719	1780 x 720	6	39	1745	37-46	63-72	24-33	1	119	1.93	C-E-D

HEAT OUTPUTS INFORMATION


MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5010100508000959	680	2319	884	3015
5010100508001079	765	2609	995	3392
5010100508001199	850	2899	1105	3769
5010100508001319	935	3189	1216	4146
5010100508001439	1020	3479	1326	4523
5010100508001559	1105	3769	1437	4900
5010100508001679	1190	4059	1547	5276
5010100508001799	1275	4349	1658	5653
5010100508001919	1360	4639	1768	6030
5010100509000239	187	638	243	830
5010100509000359	281	957	365	1245
5010100509000479	374	1276	487	1659
5010100509000599	468	1596	608	2074
5010100509000719	561	1915	730	2489
5010100509000839	655	2234	852	2904
5010100509000959	749	2553	973	3319
5010100509001079	842	2872	1095	3734
5010100509001199	936	3191	1217	4148
5010100509001319	1029	3510	1338	4563
5010100509001439	1123	3829	1460	4978
5010100509001559	1217	4148	1582	5393
5010100509001679	1310	4468	1703	5808
5010100509001799	1404	4787	1825	6223
5010100509001919	1497	5106	1946	6637
5010100510000239	203	694	265	902
5010100510000359	305	1041	397	1353
5010100510000479	407	1388	529	1804
5010100510000599	509	1735	661	2255
5010100510000719	610	2081	794	2706
5010100510000839	712	2428	926	3157
5010100510000959	814	2775	1058	3608
5010100510001079	916	3122	1190	4059
5010100510001199	1017	3469	1323	4510
5010100510001319	1119	3816	1455	4961
5010100510001439	1221	4163	1587	5412
5010100510001559	1323	4510	1719	5863
5010100510001679	1424	4857	1852	6314
5010100510001799	1526	5204	1984	6765
5010100510001919	1628	5550	2116	7216
5010100512000239	234	797	304	1036
5010100512000359	350	1195	456	1553
5010100512000479	467	1593	607	2071
5010100512000599	584	1992	759	2589
5010100512000719	701	2390	911	3107
5010100512000839	818	2788	1063	3625
5010100512000959	934	3186	1215	4142
5010100512001079	1051	3585	1367	4660
5010100512001199	1168	3983	1518	5178
5010100512001319	1285	4381	1670	5696
5010100512001439	1402	4780	1822	6214
5010100512001559	1518	5178	1974	6731
5010100512001679	1635	5576	2126	7249
5010100512001799	1752	5975	2278	7767
5010100514000239	268	915	349	1189
5010100514000359	402	1372	523	1784
5010100514000479	536	1829	697	2378
5010100514000599	671	2287	872	2973
5010100514000719	805	2744	1046	3567
5010100514000839	939	3201	1220	4162
5010100514000959	1073	3659	1395	4756
5010100514001079	1207	4116	1569	5351
5010100514001199	1341	4573	1743	5945
5010100514001319	1475	5030	1918	6540
5010100514001439	1609	5488	2092	7134
5010100514001559	1743	5945	2266	7729
5010100514001679	1878	6402	2441	8323
5010100514001799	2012	6860	2615	8918
5010100514000239	308	1050	400	1365
5010100514000359	462	1575	601	2048
5010100514000479	616	2100	801	2730
5010100514000599	770	2625	1001	3413
5010100514000719	924	3150	1201	4096
5010100514000839	1078	3676	1401	4778
5010100514000959	1232	4201	1601	5461
5010100514001079	1386	4726	1802	6143
5010100514001199	1540	5251	2002	6826
5010100518000239	354	1206	460	1567
5010100518000359	530	1809	690	2351
5010100518000479	707	2411	919	3135
5010100518000599	884	3014	1149	3919
5010100518000719	1061	3617	1379	4702

BAMBOO

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010100518000839	1780 x 840	7	39	1745	37-46	63-72	24-33	1	119	2,26	C-E-D
5010100518000959	1780 x 960	8	39	1745	37-46	63-72	24-33	1	119	2,58	C-E-D
5010100518001079	1780 x 1080	9	39	1745	37-46	63-72	24-33	1	119	2,90	C-E-D
5010100518001199	1780 x 1200	10	39	1745	37-46	63-72	24-33	1	119	3,22	C-E-D

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5010100518000839	1238	4220	1609	5486
5010100518000959	1414	4823	1839	6270
5010100518001079	1591	5426	2068	7054
5010100518001199	1768	6029	2298	7837

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
19,08	23,55	0,13	1890X874X74
21,80	26,70	0,14	1890X994X74
24,52	29,84	0,16	1890X1114X74
27,24	32,99	0,18	1890X1234X74

C: Central Heating / E: Electric / D: Dual Fuel