

BAMBOO DOUBLE		TECHNICAL INFORMATION										(For connection types, please refer to the last page)										HEAT OUTPUTS INFORMATION					LOGISTICS INFORMATION				
MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type	MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)											
	mm	pieces	mm	mm	mm	mm	mm	mm	L	C	mm		Watt	Btu	Watt	Btu					kg	kg	m³	mm							
5010100603000239	280 x 240	2	52	245	52-61	78-87	26-35	1	119	0.22	C	5010100603000239	82	280	107	364	1.94	2.79	0.01	390X274X87											
5010100603000359	280 x 360	3	52	245	52-61	78-87	26-35	1	119	0.33	C	5010100603000359	123	420	160	546	2.91	3.87	0.02	390X394X87											
5010100603000479	280 x 480	4	52	245	52-61	78-87	26-35	1	119	0.43	C-E-D	5010100603000479	164	560	213	728	3.89	4.95	0.02	390X514X87											
5010100603000599	280 x 600	5	52	245	52-61	78-87	26-35	1	119	0.54	C-E-D	5010100603000599	205	700	267	910	4.86	6.03	0.03	390X634X87											
5010100603000719	280 x 720	6	52	245	52-61	78-87	26-35	1	119	0.65	C-E-D	5010100603000719	246	840	320	1092	5.82	7.27	0.03	390X754X87											
5010100603000839	280 x 840	7	52	245	52-61	78-87	26-35	1	119	0.76	C-E-D	5010100603000839	287	980	374	1274	6.79	8.35	0.03	390X874X87											
5010100603000959	280 x 960	8	52	245	52-61	78-87	26-35	1	119	0.86	C-E-D	5010100603000959	328	1120	427	1456	7.76	9.42	0.04	390X994X87											
5010100603001079	280 x 1080	9	52	245	52-61	78-87	26-35	1	119	0.97	C-E-D	5010100603001079	369	1260	480	1638	8.73	10.50	0.04	390X1114X87											
5010100603001199	280 x 1200	10	52	245	52-61	78-87	26-35	1	119	1.08	C-E-D	5010100603001199	410	1400	534	1820	9.70	11.58	0.05	390X1234X87											
5010100603001319	280 x 1320	11	52	245	52-61	78-87	26-35	1	119	1.18	C-E-D	5010100603001319	452	1540	587	2002	10.67	12.65	0.05	390X1354X87											
5010100603001439	280 x 1440	12	52	245	52-61	78-87	26-35	1	119	1.29	C	5010100603001439	493	1680	640	2184	11.63	13.73	0.06	390X1474X87											
5010100603001559	280 x 1560	13	52	245	52-61	78-87	26-35	1	119	1.40	C	5010100603001559	534	1820	694	2365	12.60	14.79	0.06	390X1594X87											
5010100603001679	280 x 1680	14	52	245	52-61	78-87	26-35	1	119	1.51	C	5010100603001679	575	1960	747	2547	13.57	15.88	0.06	390X1714X87											
5010100603001799	280 x 1800	15	52	245	52-61	78-87	26-35	1	119	1.61	C	5010100603001799	616	2100	800	2729	14.54	16.94	0.07	390X1834X87											
5010100603001919	280 x 1920	16	52	245	52-61	78-87	26-35	1	119	1.72	C	5010100603001919	657	2239	854	2911	15.52	18.04	0.07	390X1954X87											
5010100604000239	380 x 240	2	52	345	52-61	78-87	26-35	1	119	0.25	C	5010100604000239	112	382	145	496	2.40	3.34	0.02	490X274X87											
5010100604000359	380 x 360	3	52	345	52-61	78-87	26-35	1	119	0.37	C	5010100604000359	168	572	218	744	3.59	4.66	0.02	490X394X87											
5010100604000479	380 x 480	4	52	345	52-61	78-87	26-35	1	119	0.49	C-E-D	5010100604000479	224	763	291	992	4.79	5.99	0.03	490X514X87											
5010100604000599	380 x 600	5	52	345	52-61	78-87	26-35	1	119	0.61	C-E-D	5010100604000599	280	954	364	1240	5.99	7.32	0.03	490X634X87											
5010100604000719	380 x 720	6	52	345	52-61	78-87	26-35	1	119	0.73	C-E-D	5010100604000719	336	1144	436	1488	7.18	8.79	0.04	490X754X87											
5010100604000839	380 x 840	7	52	345	52-61	78-87	26-35	1	119	0.86	C-E-D	5010100604000839	392	1335	509	1736	8.37	10.11	0.04	490X874X87											
5010100604000959	380 x 960	8	52	345	52-61	78-87	26-35	1	119	0.98	C-E-D	5010100604000959	448	1526	582	1984	9.57	11.44	0.05	490X994X87											
5010100604001079	380 x 1080	9	52	345	52-61	78-87	26-35	1	119	1.10	C-E-D	5010100604001079	503	1717	654	2232	10.77	12.77	0.05	490X1114X87											
5010100604001199	380 x 1200	10	52	345	52-61	78-87	26-35	1	119	1.22	C-E-D	5010100604001199	559	1907	727	2480	11.96	14.10	0.06	490X1234X87											
5010100604001319	380 x 1320	11	52	345	52-61	78-87	26-35	1	119	1.34	C-E-D	5010100604001319	615	2098	800	2728	13.16	15.42	0.06	490X1354X87											
5010100604001439	380 x 1440	12	52	345	52-61	78-87	26-35	1	119	1.46	C	5010100604001439	671	2289	873	2976	14.35	16.74	0.07	490X1474X87											
5010100604001559	380 x 1560	13	52	345	52-61	78-87	26-35	1	119	1.58	C	5010100604001559	727	2480	945	3224	15.55	18.07	0.07	490X1594X87											
5010100604001679	380 x 1680	14	52	345	52-61	78-87	26-35	1	119	1.71	C	5010100604001679	783	2670	1018	3472	16.74	19.39	0.08	490X1714X87											
5010100604001799	380 x 1800	15	52	345	52-61	78-87	26-35	1	119	1.83	C	5010100604001799	839	2861	1091	3720	17.94	20.73	0.08	490X1834X87											
5010100604001919	380 x 1920	16	52	345	52-61	78-87	26-35	1	119	1.95	C	5010100604001919	895	3052	1163	3967	19.14	22.06	0.09	490X1954X87											
5010100605000239	480 x 240	2	52	445	52-61	78-87	26-35	1	119	0.28	C	5010100605000239	143	487	186	634	2.85	3.88	0.02	590X274X87											
5010100605000359	480 x 360	3	52	445	52-61	78-87	26-35	1	119	0.41	C	5010100605000359	214	731	279	950	4.27	5.44	0.03	590X394X87											
5010100605000479	480 x 480	4	52	445	52-61	78-87	26-35	1	119	0.55	C-E-D	5010100605000479	286	975	372	1267	5.70	7.02	0.03	590X514X87											
5010100605000599	480 x 600	5	52	445	52-61	78-87	26-35	1	119	0.68	C-E-D	5010100605000599	357	1218	465	1584	7.12	8.59	0.04	590X634X87											
5010100605000719	480 x 720	6	52	445	52-61	78-87	26-35	1	119	0.82	C-E-D	5010100605000719	429	1462	557	1901	8.53	10.32	0.04	590X754X87											
5010100605000839	480 x 840	7	52	445	52-61	78-87	26-35	1	119	0.96	C-E-D	5010100605000839	500	1706	650	2218	9.96	11.90	0.05	590X874X87											
5010100605000959	480 x 960	8	52	445	52-61	78-87	26-35	1	119	1.09	C-E-D	5010100605000959	572	1950	743	2534	11.38	13.47	0.06	590X994X87											
5010100606001079	480 x 1080	9	52	445	52-61	78-87	26-35	1	119	1.23	C-E-D	5010100606001079	643	2193	836	2851	12.81	15.06	0.06	590X1114X87											
5010100606001199	480 x 1200	10	52	445	52-61	78-87	26-35	1	119	1.36	C-E-D	5010100606001199	715	2437	929	3168	14.23	16.63	0.07	590X1234X87											
5010100606001319	480 x 1320	11	52	445	52-61	78-87	26-35	1	119	1.50	C-E-D	5010100606001319	786	2681	1022	3485	15.65	18.20	0.07	590X1354X87											
5010100606001439	480 x 1440	12	52	445	52-61	78-87	26-35	1	119	1.63	C	5010100606001439	858	2924	1115	3802	17.07	19.77	0.08	590X1474X87											
5010100606001559	480 x 1560	13	52	445	52-61	78-87	26-35	1	119	1.77	C	5010100606001559	929	3168	1208	4118	18.49	21.34	0.09	590X1594X87											
5010100606001679	480 x 1680																														


BAMBOO DOUBLE		TECHNICAL INFORMATION										(For connection types, please refer to the last page)										HEAT OUTPUTS INFORMATION										LOGISTICS INFORMATION			
MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type	MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)															
	mm	pieces	mm	mm	mm	mm	mm	mm	L	mm	Watt		Btu	Watt	Btu	kg					kg	m³	mm												
5010100608000959	780 x 960	8	52	745	52-61	78-87	26-35	1	119	1.43	C-E-D	5010100608000959	895	3052	1163	3967	16.82	19.58	0.08	890X994X87															
5010100608001079	780 x 1080	9	52	745	52-61	78-87	26-35	1	119	1.61	C-E-D	5010100608001079	1007	3433	1309	4463	18.92	21.90	0.09	890X1114X87															
5010100608001199	780 x 1200	10	52	745	52-61	78-87	26-35	1	119	1.79	C-E-D	5010100608001199	1119	3815	1454	4959	21.02	24.22	0.10	890X1234X87															
5010100608001319	780 x 1320	11	52	745	52-61	78-87	26-35	1	119	1.97	C-E-D	5010100608001319	1231	4196	1600	5455	23.12	26.54	0.11	890X1354X87															
5010100608001439	780 x 1440	12	52	745	52-61	78-87	26-35	1	119	2.15	C	5010100608001439	1342	4578	1745	5951	25.22	28.85	0.12	890X1474X87															
5010100608001559	780 x 1560	13	52	745	52-61	78-87	26-35	1	119	2.33	C	5010100608001559	1454	4959	1891	6447	27.32	31.15	0.13	890X1594X87															
5010100608001679	780 x 1680	14	52	745	52-61	78-87	26-35	1	119	2.51	C	5010100608001679	1566	5341	2036	6943	29.42	33.46	0.14	890X1714X87															
5010100608001799	780 x 1800	15	52	745	52-61	78-87	26-35	1	119	2.69	C	5010100608001799	1678	5722	2182	7439	31.52	35.78	0.15	890X1834X87															
5010100608001919	780 x 1920	16	52	745	52-61	78-87	26-35	1	119	2.86	C	5010100608001919	1790	6104	2327	7935	33.63	38.11	0.16	890X1954X87															
5010100609000239	880 x 240	2	52	845	52-61	78-87	26-35	1	119	0.39	C	5010100609000239	246	840	320	1092	4.66	6.05	0.03	990X274X87															
5010100609000359	880 x 360	3	52	845	52-61	78-87	26-35	1	119	0.58	C	5010100609000359	369	1260	480	1638	6.99	8.62	0.04	990X394X87															
5010100609000479	880 x 480	4	52	845	52-61	78-87	26-35	1	119	0.78	C-E-D	5010100609000479	493	1680	640	2184	9.32	11.19	0.05	990X514X87															
5010100609000599	880 x 600	5	52	845	52-61	78-87	26-35	1	119	0.97	C-E-D	5010100609000599	616	2100	800	2729	11.65	13.76	0.06	990X634X87															
5010100609000719	880 x 720	6	52	845	52-61	78-87	26-35	1	119	1.16	C-E-D	5010100609000719	739	2519	960	3275	13.97	16.47	0.07	990X754X87															
5010100609000839	880 x 840	7	52	845	52-61	78-87	26-35	1	119	1.36	C-E-D	5010100609000839	862	2939	1121	3821	16.30	19.05	0.08	990X874X87															
5010100609000959	880 x 960	8	52	845	52-61	78-87	26-35	1	119	1.55	C-E-D	5010100609000959	985	3359	1281	4367	18.63	21.60	0.09	990X994X87															
5010100609001079	880 x 1080	9	52	845	52-61	78-87	26-35	1	119	1.74	C-E-D	5010100609001079	1108	3779	1441	4913	20.96	24.17	0.10	990X1114X87															
5010100609001199	880 x 1200	10	52	845	52-61	78-87	26-35	1	119	1.93	C-E-D	5010100609001199	1231	4199	1601	5459	23.28	26.73	0.11	990X1234X87															
5010100609001319	880 x 1320	11	52	845	52-61	78-87	26-35	1	119	2.13	C-E-D	5010100609001319	1355	4619	1761	6005	25.61	29.29	0.12	990X1354X87															
5010100609001439	880 x 1440	12	52	845	52-61	78-87	26-35	1	119	2.32	C	5010100609001439	1478	5039	1921	6550	27.93	31.85	0.13	990X1474X87															
5010100609001559	880 x 1560	13	52	845	52-61	78-87	26-35	1	119	2.51	C	5010100609001559	1601	5459	2081	7096	30.26	34.42	0.14	990X1594X87															
5010100609001679	880 x 1680	14	52	845	52-61	78-87	26-35	1	119	2.71	C	5010100609001679	1724	5879	2241	7642	32.59	36.99	0.15	990X1714X87															
5010100609001799	880 x 1800	15	52	845	52-61	78-87	26-35	1	119	2.90	C	5010100609001799	1847	6299	2401	8188	34.92	39.56	0.16	990X1834X87															
5010100609001919	880 x 1920	16	52	845	52-61	78-87	26-35	1	119	3.09	C	5010100609001919	1970	6718	2561	8734	37.25	42.12	0.17	990X1954X87															
5010100610000239	980 x 240	2	52	945	52-61	78-87	26-35	1	119	0.42	C	5010100610000239	268	913	348	1187	5.11	6.58	0.03	1090X274X87															
5010100610000359	980 x 360	3	52	945	52-61	78-87	26-35	1	119	0.63	C	5010100610000359	402	1369	522	1780	7.67	9.41	0.04	1090X394X87															
5010100610000479	980 x 480	4	52	945	52-61	78-87	26-35	1	119	0.83	C-E-D	5010100610000479	535	1826	696	2374	10.22	12.21	0.05	1090X514X87															
5010100610000599	980 x 600	5	52	945	52-61	78-87	26-35	1	119	1.04	C-E-D	5010100610000599	669	2282	870	2967	12.78	15.03	0.07	1090X634X87															
5010100610000719	980 x 720	6	52	945	52-61	78-87	26-35	1	119	1.25	C-E-D	5010100610000719	803	2739	1044	3561	15.33	18.01	0.08	1090X754X87															
5010100610000839	980 x 840	7	52	945	52-61	78-87	26-35	1	119	1.46	C-E-D	5010100610000839	937	3195	1218	4154	17.88	20.81	0.09	1090X874X87															
5010100610000959	980 x 960	8	52	945	52-61	78-87	26-35	1	119	1.66	C-E-D	5010100610000959	1071	3652	1392	4747	20.44	23.64	0.10	1090X994X87															
5010100610001079	980 x 1080	9	52	945	52-61	78-87	26-35	1	119	1.87	C-E-D	5010100610001079	1205	4108	1566	5341	22.99	26.44	0.11	1090X1114X87															
5010100610001199	980 x 1200	10	52	945	52-61	78-87	26-35	1	119	2.08	C-E-D	5010100610001199	1339	4565	1740	5934	25.55	29.26	0.12	1090X1234X87															
5010100610001319	980 x 1320	11	52	945	52-61	78-87	26-35	1	119	2.29	C-E-D	5010100610001319	1473	5021	1914	6528	28.10	32.07	0.13	1090X1354X87															
5010100610001439	980 x 1440	12	52	945	52-61	78-87	26-35	1	119	2.49	C	5010100610001439	1606	5478	2088	7121	30.65	34.88	0.14	1090X1474X87															
5010100610001559	980 x 1560	13	52	945	52-61	78-87	26-35	1	119	2.70	C	5010100610001559	1740	5934	2262	7715	33.21	37.70	0.16	1090X1594X87															
5010100610001679	980 x 1680	14	52	945	52-61	78-87	26-35	1	119	2.91	C	5010100610001679	1874	6391	2436	8308	35.76	40.51	0.17	1090X1714X87															
5010100610001799	980 x 1800	15	52	945	52-61	78-87	26-35	1	119	3.11	C	5010100610001799	2008	6847	2610	8901	38.32	43.32	0.18	1090X1834X87															
5010100610001919	980 x 1920	16	52	945	52-61	78-87	26-35	1	119	3.32	C	5010100610001919	2142	7304	2784	9495	40.87	46.14	0.19	1090X1954X87															
5010100612000239	1180 x 240	2	52	1145	52-61	78-87	26-35	1	119	0.48	C	5010100612000239	307	1048	400	1363	6.02	7.69	0.04	1290X274X87															
5010100612000359	1180 x 360	3	52	1145	52-61	78-87	26-35	1	119	0.71	C	5010100612000359	461	1572	599	2044	9.03	11.01	0.05	1290X394X87															
5010100612000479	1180 x 480	4	52	1145	52-61	78-87	26-35	1	119	0.95	C-E-D	5010100612000479	615	2096	799	2725																			

BAMBOO DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010100618000839	1780 x 840	7	52	1745	52-61	78-87	26-35	1	119	2,26	C-E-D
5010100618000959	1780 x 960	8	52	1745	52-61	78-87	26-35	1	119	2,58	C-E-D
5010100618001079	1780 x 1080	9	52	1745	52-61	78-87	26-35	1	119	2,90	C-E-D
5010100618001199	1780 x 1200	10	52	1745	52-61	78-87	26-35	1	119	3,22	C-E-D

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5010100618000839	1628	5553	2117	7219
5010100618000959	1861	6346	2419	8250
5010100618001079	2094	7140	2722	9281
5010100618001199	2326	7933	3024	10313

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
30,52	35,05	0,15	1890X874X87
34,88	39,84	0,17	1890X994X87
39,23	44,61	0,19	1890X1114X87
43,59	49,41	0,21	1890X1234X87

C: Central Heating / E: Electric / D: Dual Fuel