

NISH

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010104203000404	300 x 400	2	41	245	35-44	63-72	22-31	4	200	0,31	C-E-D
5010104203000608	300 x 610	3	41	245	35-44	63-72	22-31	4	200	0,47	C-E-D
5010104203000812	300 x 810	4	41	245	35-44	63-72	22-31	4	200	0,62	C-E-D
5010104203001016	300 x 1020	5	41	245	35-44	63-72	22-31	4	200	0,78	C-E-D
5010104203001220	300 x 1220	6	41	245	35-44	63-72	22-31	4	200	0,93	C-E-D
5010104203001424	300 x 1420	7	41	245	35-44	63-72	22-31	4	200	1,09	C
5010104203001628	300 x 1630	8	41	245	35-44	63-72	22-31	4	200	1,24	C
5010104203001832	300 x 1830	9	41	245	35-44	63-72	22-31	4	200	1,40	C
5010104204000404	400 x 400	2	41	345	35-44	63-72	22-31	4	200	0,34	C-E-D
5010104204000608	400 x 610	3	41	345	35-44	63-72	22-31	4	200	0,51	C-E-D
5010104204000812	400 x 810	4	41	345	35-44	63-72	22-31	4	200	0,68	C-E-D
5010104204001016	400 x 1020	5	41	345	35-44	63-72	22-31	4	200	0,85	C-E-D
5010104204001220	400 x 1220	6	41	345	35-44	63-72	22-31	4	200	1,02	C-E-D
5010104204001424	400 x 1420	7	41	345	35-44	63-72	22-31	4	200	1,19	C
5010104204001628	400 x 1630	8	41	345	35-44	63-72	22-31	4	200	1,36	C
5010104204001832	400 x 1830	9	41	345	35-44	63-72	22-31	4	200	1,52	C
5010104205000404	500 x 400	2	41	445	35-44	63-72	22-31	4	200	0,37	C-E-D
5010104205000608	500 x 610	3	41	445	35-44	63-72	22-31	4	200	0,55	C-E-D
5010104205000812	500 x 810	4	41	445	35-44	63-72	22-31	4	200	0,74	C-E-D
5010104205001016	500 x 1020	5	41	445	35-44	63-72	22-31	4	200	0,92	C-E-D
5010104205001220	500 x 1220	6	41	445	35-44	63-72	22-31	4	200	1,10	C-E-D
5010104205001424	500 x 1420	7	41	445	35-44	63-72	22-31	4	200	1,29	C
5010104205001628	500 x 1630	8	41	445	35-44	63-72	22-31	4	200	1,47	C
5010104205001832	500 x 1830	9	41	445	35-44	63-72	22-31	4	200	1,65	C
5010104206000404	600 x 400	2	41	545	35-44	63-72	22-31	4	200	0,40	C-E-D
5010104206000608	600 x 610	3	41	545	35-44	63-72	22-31	4	200	0,60	C-E-D
5010104206000812	600 x 810	4	41	545	35-44	63-72	22-31	4	200	0,79	C-E-D
5010104206001016	600 x 1020	5	41	545	35-44	63-72	22-31	4	200	0,99	C-E-D
5010104206001220	600 x 1220	6	41	545	35-44	63-72	22-31	4	200	1,19	C-E-D
5010104206001424	600 x 1420	7	41	545	35-44	63-72	22-31	4	200	1,39	C
5010104206001628	600 x 1630	8	41	545	35-44	63-72	22-31	4	200	1,58	C
5010104206001832	600 x 1830	9	41	545	35-44	63-72	22-31	4	200	1,78	C
5010104207000404	700 x 400	2	41	645	35-44	63-72	22-31	4	200	0,43	C-E-D
5010104207000608	700 x 610	3	41	645	35-44	63-72	22-31	4	200	0,64	C-E-D
5010104207000812	700 x 810	4	41	645	35-44	63-72	22-31	4	200	0,85	C-E-D
5010104207001016	700 x 1020	5	41	645	35-44	63-72	22-31	4	200	1,06	C-E-D
5010104207001220	700 x 1220	6	41	645	35-44	63-72	22-31	4	200	1,27	C-E-D
5010104207001424	700 x 1420	7	41	645	35-44	63-72	22-31	4	200	1,49	C
5010104207001628	700 x 1630	8	41	645	35-44	63-72	22-31	4	200	1,70	C
5010104207001832	700 x 1830	9	41	645	35-44	63-72	22-31	4	200	1,91	C
5010104208000404	800 x 400	2	41	745	35-44	63-72	22-31	4	200	0,46	C-E-D
5010104208000608	800 x 610	3	41	745	35-44	63-72	22-31	4	200	0,68	C-E-D
5010104208000812	800 x 810	4	41	745	35-44	63-72	22-31	4	200	0,91	C-E-D
5010104208001016	800 x 1020	5	41	745	35-44	63-72	22-31	4	200	1,13	C-E-D
5010104208001220	800 x 1220	6	41	745	35-44	63-72	22-31	4	200	1,36	C-E-D
5010104208001424	800 x 1420	7	41	745	35-44	63-72	22-31	4	200	1,59	C
5010104208001628	800 x 1630	8	41	745	35-44	63-72	22-31	4	200	1,81	C
5010104208001832	800 x 1830	9	41	745	35-44	63-72	22-31	4	200	2,04	C
5010104209000404	900 x 400	2	41	845	35-44	63-72	22-31	4	200	0,48	C-E-D
5010104209000608	900 x 610	3	41	845	35-44	63-72	22-31	4	200	0,72	C-E-D
5010104209000812	900 x 810	4	41	845	35-44	63-72	22-31	4	200	0,97	C-E-D
5010104209001016	900 x 1020	5	41	845	35-44	63-72	22-31	4	200	1,21	C-E-D
5010104209001220	900 x 1220	6	41	845	35-44	63-72	22-31	4	200	1,45	C-E-D
5010104209001424	900 x 1420	7	41	845	35-44	63-72	22-31	4	200	1,69	C
5010104209001628	900 x 1630	8	41	845	35-44	63-72	22-31	4	200	1,93	C
5010104209001832	900 x 1830	9	41	845	35-44	63-72	22-31	4	200	2,17	C
5010104210000404	1000 x 400	2	41	945	35-44	63-72	22-31	4	200	0,51	C-E-D
5010104210000608	1000 x 610	3	41	945	35-44	63-72	22-31	4	200	0,77	C-E-D
5010104210000812	1000 x 810	4	41	945	35-44	63-72	22-31	4	200	1,02	C-E-D
5010104210001016	1000 x 1020	5	41	945	35-44	63-72	22-31	4	200	1,28	C-E-D
5010104210001220	1000 x 1220	6	41	945	35-44	63-72	22-31	4	200	1,53	C-E-D
5010104210001424	1000 x 1420	7	41	945	35-44	63-72	22-31	4	200	1,79	C
5010104210001628	1000 x 1630	8	41	945	35-44	63-72	22-31	4	200	2,04	C
5010104210001832	1000 x 1830	9	41	945	35-44	63-72	22-31	4	200	2,30	C
5010104212000404	1200 x 400	2	41	1145	35-44	63-72	22-31	4	200	0,57	C-E-D
5010104212000608	1200 x 610	3	41	1145	35-44	63-72	22-31	4	200	0,85	C-E-D
5010104212000812	1200 x 810	4	41	1145	35-44	63-72	22-31	4	200	1,14	C-E-D
5010104212001016	1200 x 1020	5	41	1145	35-44	63-72	22-31	4	200	1,42	C-E-D
5010104212001220	1200 x 1220	6	41	1145	35-44	63-72	22-31	4	200	1,70	C-E-D
5010104212001424	1200 x 1420	7	41	1145	35-44	63-72	22-31	4	200	1,99	C
5010104214000404	1400 x 400	2	41	1345	35-44	63-72	22-31	4	200	0,63	C-E-D
5010104214000608	1400 x 610	3	41	1345	35-44	63-72	22-31	4	200	0,94	C-E-D
5010104214000812	1400 x 810	4	41	1345	35-44	63-72	22-31	4	200	1,25	C-E-D
5010104214001016	1400 x 1020	5	41	1345	35-44	63-72	22-31	4	200	1,56	C-E-D
5010104214001220	1400 x 1220	6	41	1345	35-44	63-72	22-31	4	200	1,88	C-E-D
5010104214001424	1400 x 1420	7	41	1345	35-44	63-72	22-31	4	200	2,19	C
5010104216000200	1600 x 200	1	41	1545	35-44	63-72	22-31	4	200	0,34	C
5010104216000404	1600 x 400	2	41	1545	35-44	63-72	22-31	4	200	0,68	C-E-D
5010104216000608	1600 x 610	3	41	1545	35-44	63-72	22-31	4	200	1,02	C-E-D
5010104216000812	1600 x 810	4	41	1545	35-44	63-72	22-31	4	200	1,37	C-E-D
5010104216001016	1600 x 1020	5	41	1545	35-44	63-72	22-31	4	200	1,71	C-E-D

HEAT OUTPUTS INFORMATION


MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5010104203000404	103	351	134	457
5010104203000608	155	527	201	685
5010104203000812	206	703	268	914
5010104203001016	258	879	335	1142
5010104203001220	309	1054	402	1371
5010104203001424	361	1230	469	1599
5010104203001628	412	1406	536	1828
5010104203001832	464	1582	603	2056
5010104204000404	140	479	183	623
5010104204000608	211	718	274	934
5010104204000812	281	958	365	1245
5010104204001016	351	1197	457	1557
5010104204001220	421	1437	548	1868
5010104204001424	492	1676	639	2179
5010104204001628	562	1916	730	2491
5010104204001832	632	2155	822	2802
5010104205000404	179	612	233	796
5010104205000608	269	918	350	1193
5010104205000812	359	1224	467	1591
5010104205001016	449	1530	583	1989
5010104205001220	538	1836	700	2387
5010104205001424	628	2142	817	2784
5010104205001628	718	2448	933	3182
5010104205001832	808	2754	1050	3580
5010104206000404	220	751	286	976
5010104206000608	330	1126	429	1464
5010104206000812	440	1501	572	1951
5010104206001016	550	1876	715	2439
5010104206001220	660	2252	858	2927
5010104206001424	770	2627	1001	3415
5010104206001628	880	3002	1145	3903
5010104206001832	990	3377	1288	4391
5010104207000404	251	857	327	1114
5010104207000608	377	1285	490	1671
5010104207000812	502	1713	653	2227
5010104207001016	628	2142	817	2784
5010104207001220	754	2570	980	3341
5010104207001424	879	2998	1143	3898
5010104207001628	1005	3427	1306	4455
5010104207001832	1131	3855	1470	5012
5010104208000404	281	958	365	1245
5010104208000608	421	1437	548	1868
5010104208000812	562	1916	730	2491
5010104208001016	702	2395	913	3113
5010104208001220	843	2874	1096	3736
5010104208001424	983	3353	1278	4359
5010104208001628	1124	3832	1461	4981
5010104208001832	1264	4311	1643	5604
5010104209000404	309	1054	402	1371
5010104209000608	464	1582	603	2056
5010104209000812	618	2109	804	2741
5010104209001016	773	2636	1005	3427
5010104209001220	928	3163	1206	4112
5010104209001424	1082	3690	1407	4798
5010104209001628	1237	4218	1608	5483
5010104209001832	1391	4745	1809	6168
5010104210000404	336	1146	437	1490
5010104210000608	504	1719	655	2235
5010104210000812	672	2293	874	2980
5010104210001016	840	2866	1092	3725
5010104210001220	1008	3439	1311	4470
5010104210001424	1177	4012	1529	5215
5010104210001628	1345	4585	1748	5961
5010104210001832	1513	5158	1966	6706
5010104212000404	386	1316	502	1711
5010104212000608	579	1974	753	2566
5010104212000812	772	2632	1003	3422
5010104212001016	965	3290	1254	4277
5010104212001220	1158	3948	1505	5133
5010104212001424	1351	4606	1756	5988
5010104214000404	443	1511	576	1964
5010104214000608	665	2267	864	2947
5010104214000812	886	3022	1152	3929
5010104214001016	1108	3778	1440	4911
5010104214001220	1329	4533	1728	5893
5010104214001424	1551	5289	2016	6875
5010104214000200	254	868	331	1128
5010104214000404	509	1735	661	2255
5010104214000608	763	2602	992	3383
5010104214000812	1018	3470	1323	4511
5010104214001016	1272	4337	1654	5639

NISH

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010104218000200	1800 x 200	1	41	1745	35-44	63-72	22-31	4	200	0,37	C
5010104218000404	1800 x 400	2	41	1745	35-44	63-72	22-31	4	200	0,74	C-E-D
5010104218000608	1800 x 610	3	41	1745	35-44	63-72	22-31	4	200	1,11	C-E-D
5010104218000812	1800 x 810	4	41	1745	35-44	63-72	22-31	4	200	1,48	C-E-D
5010104218001016	1800 x 1020	5	41	1745	35-44	63-72	22-31	4	200	1,85	C-E-D

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		
	mm	Watt	Btu	Watt	Btu
5010104218000200		292	996	380	1295
5010104218000404		584	1992	759	2590
5010104218000608		876	2988	1139	3884
5010104218000812		1168	3984	1519	5179
5010104218001016		1460	4980	1899	6474

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
5,38	7,34	0,04	1910X235X76
10,75	13,59	0,07	1910X439X76
16,12	19,80	0,10	1910X643X76
21,50	26,16	0,13	1910X847X76
26,87	32,25	0,16	1910X1051X76

C: Central Heating / E: Electric / D: Dual Fuel