

NISH LINE		TECHNICAL INFORMATION											(For connection types, please refer to the last page)											HEAT OUTPUTS INFORMATION					LOGISTICS INFORMATION				
MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type	MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)													
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L			mm	Watt	Btu	Watt	Btu	kg	kg	m³	mm												
5010104503000404	300 x 400	2	62	245	49-58	79-88	20-29	4	200	0.30	C-E-D	5010104503000404	103	351	134	457	2.59	3.67	0.02	420X444X102													
5010104503000608	300 x 610	3	62	245	49-58	79-88	20-29	4	200	0.44	C-E-D	5010104503000608	155	527	201	685	3.89	5.31	0.03	420X648X102													
5010104503000812	300 x 810	4	62	245	49-58	79-88	20-29	4	200	0.59	C-E-D	5010104503000812	206	703	268	914	5.19	7.07	0.04	420X852X102													
5010104503001016	300 x 1020	5	62	245	49-58	79-88	20-29	4	200	0.73	C-E-D	5010104503001016	258	879	335	1142	6.49	8.59	0.05	420X1056X102													
5010104503001220	300 x 1220	6	62	245	49-58	79-88	20-29	4	200	0.88	C-E-D	5010104503001220	309	1054	402	1371	7.78	10.11	0.06	420X1260X102													
5010104503001424	300 x 1420	7	62	245	49-58	79-88	20-29	4	200	1.03	C	5010104503001424	361	1230	469	1599	9.08	11.63	0.07	420X1464X102													
5010104503001628	300 x 1630	8	62	245	49-58	79-88	20-29	4	200	1.17	C	5010104503001628	412	1406	536	1828	10.38	13.14	0.08	420X1668X102													
5010104503001832	300 x 1830	9	62	245	49-58	79-88	20-29	4	200	1.32	C	5010104503001832	464	1582	603	2056	11.68	14.67	0.09	420X1872X102													
5010104504000404	400 x 400	2	62	345	49-58	79-88	20-29	4	200	0.32	C-E-D	5010104504000404	140	479	183	623	3.13	4.35	0.03	520X444X102													
5010104504000608	400 x 610	3	62	345	49-58	79-88	20-29	4	200	0.48	C-E-D	5010104504000608	211	718	274	934	4.70	6.31	0.04	520X648X102													
5010104504000812	400 x 810	4	62	345	49-58	79-88	20-29	4	200	0.65	C-E-D	5010104504000812	281	958	365	1245	6.27	8.37	0.05	520X852X102													
5010104504001016	400 x 1020	5	62	345	49-58	79-88	20-29	4	200	0.81	C-E-D	5010104504001016	351	1197	457	1557	7.84	10.20	0.06	520X1056X102													
5010104504001220	400 x 1220	6	62	345	49-58	79-88	20-29	4	200	0.97	C-E-D	5010104504001220	421	1437	548	1868	9.40	12.02	0.07	520X1260X102													
5010104504001424	400 x 1420	7	62	345	49-58	79-88	20-29	4	200	1.13	C	5010104504001424	492	1676	639	2179	10.97	13.85	0.08	520X1464X102													
5010104504001628	400 x 1630	8	62	345	49-58	79-88	20-29	4	200	1.29	C	5010104504001628	562	1916	730	2491	12.54	15.67	0.09	520X1668X102													
5010104504001832	400 x 1830	9	62	345	49-58	79-88	20-29	4	200	1.45	C	5010104504001832	632	2155	822	2802	14.11	17.50	0.10	520X1872X102													
5010104505000404	500 x 400	2	62	445	49-58	79-88	20-29	4	200	0.35	C-E-D	5010104505000404	179	612	233	796	3.67	5.03	0.03	620X444X102													
5010104505000608	500 x 610	3	62	445	49-58	79-88	20-29	4	200	0.53	C-E-D	5010104505000608	269	918	350	1193	5.51	7.29	0.05	620X648X102													
5010104505000812	500 x 810	4	62	445	49-58	79-88	20-29	4	200	0.70	C-E-D	5010104505000812	359	1224	467	1591	7.35	9.66	0.06	620X852X102													
5010104505001016	500 x 1020	5	62	445	49-58	79-88	20-29	4	200	0.88	C-E-D	5010104505001016	449	1530	583	1989	9.19	11.79	0.07	620X1056X102													
5010104505001220	500 x 1220	6	62	445	49-58	79-88	20-29	4	200	1.05	C-E-D	5010104505001220	538	1836	700	2387	11.02	13.92	0.08	620X1260X102													
5010104505001424	500 x 1420	7	62	445	49-58	79-88	20-29	4	200	1.23	C	5010104505001424	628	2142	817	2784	12.86	16.06	0.10	620X1464X102													
5010104505001628	500 x 1630	8	62	445	49-58	79-88	20-29	4	200	1.40	C	5010104505001628	718	2448	933	3182	14.70	18.19	0.11	620X1668X102													
5010104505001832	500 x 1830	9	62	445	49-58	79-88	20-29	4	200	1.58	C	5010104505001832	808	2754	1050	3580	16.54	20.33	0.12	620X1872X102													
5010104506000404	600 x 400	2	62	545	49-58	79-88	20-29	4	200	0.38	C-E-D	5010104506000404	220	751	286	976	4.21	5.70	0.04	720X444X102													
5010104506000608	600 x 610	3	62	545	49-58	79-88	20-29	4	200	0.57	C-E-D	5010104506000608	330	1126	429	1464	6.32	8.28	0.05	720X648X102													
5010104506000812	600 x 810	4	62	545	49-58	79-88	20-29	4	200	0.76	C-E-D	5010104506000812	440	1501	572	1951	8.43	10.93	0.07	720X852X102													
5010104506001016	600 x 1020	5	62	545	49-58	79-88	20-29	4	200	0.95	C-E-D	5010104506001016	550	1876	715	2439	10.54	13.39	0.08	720X1056X102													
5010104506001220	600 x 1220	6	62	545	49-58	79-88	20-29	4	200	1.14	C-E-D	5010104506001220	660	2252	858	2927	12.64	15.82	0.10	720X1260X102													
5010104506001424	600 x 1420	7	62	545	49-58	79-88	20-29	4	200	1.33	C	5010104506001424	770	2627	1001	3415	14.75	18.26	0.11	720X1464X102													
5010104506001628	600 x 1630	8	62	545	49-58	79-88	20-29	4	200	1.52	C	5010104506001628	880	3002	1145	3903	16.86	20.70	0.13	720X1668X102													
5010104506001832	600 x 1830	9	62	545	49-58	79-88	20-29	4	200	1.71	C	5010104506001832	990	3377	1288	4391	18.97	23.14	0.14	720X1872X102													
5010104507000404	700 x 400	2	62	645	49-58	79-88	20-29	4	200	0.41	C-E-D	5010104507000404	251	857	327	1114	4.75	6.38	0.04	820X444X102													
5010104507000608	700 x 610	3	62	645	49-58	79-88	20-29	4	200	0.61	C-E-D	5010104507000608	377	1285	490	1671	7.13	9.25	0.06	820X648X102													
5010104507000812	700 x 810	4	62	645	49-58	79-88	20-29	4	200	0.82	C-E-D	5010104507000812	502	1713	653	2227	9.51	12.23	0.08	820X852X102													
5010104507001016	700 x 1020	5	62	645	49-58	79-88	20-29	4	200	1.02	C-E-D	5010104507001016	628	2142	817	2784	11.89	14.98	0.09	820X1056X102													
5010104507001220	700 x 1220	6	62	645	49-58	79-88	20-29	4	200	1.22	C-E-D	5010104507001220	754	2570	980	3341	14.26	17.72	0.11	820X1260X102													
5010104507001424	700 x 1420	7	62	645	49-58	79-88	20-29	4	200	1.43	C	5010104507001424	879	2998	1143	3898	16.64	20.47	0.13	820X1464X102													
5010104507001628	700 x 1630	8	62	645	49-58	79-88	20-29	4	200	1.63	C	5010104507001628	1005	3427	1306	4455	19.02	23.21	0.14	820X1668X102													
5010104507001832	700 x 1830	9	62	645	49-58	79-88	20-29	4	200	1.83	C	5010104507001832	1131	3855	1470	5012	21.40	25.97	0.16	820X1872X102													
5010104508000404	800 x 400	2	62	745	49-58	79-88	20-29	4	200	0.44	C-E-D	5010104508000404	281	958	365	1245	5.29	7.05	0.05	920X444X102													
5010104508000608	800 x 610	3	62	745	49-58	79-88	20-29	4	200	0.66	C-E-D	5010104508000608	421	1437	548	1868	7.94	10.24															

NISH LINE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5010104518000200	1800 x 200	1	62	1745	49-58	79-88	20-29	4	200	0,36	C
5010104518000404	1800 x 400	2	62	1745	49-58	79-88	20-29	4	200	0,72	C-E-D
5010104518000608	1800 x 610	3	62	1745	49-58	79-88	20-29	4	200	1,09	C-E-D
5010104518000812	1800 x 810	4	62	1745	49-58	79-88	20-29	4	200	1,45	C-E-D
5010104518001016	1800 x 1020	5	62	1745	49-58	79-88	20-29	4	200	1,81	C-E-D

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	mm			
5010104518000200	292	996	380	1295
5010104518000404	584	1992	759	2590
5010104518000608	876	2988	1139	3884
5010104518000812	1168	3984	1519	5179
5010104518001016	1460	4980	1899	6474

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
5,34	7,71	0,05	1920X240X102
10,69	13,93	0,09	1920X444X102
16,04	20,18	0,13	1920X648X102
21,39	26,53	0,17	1920X852X102
26,74	32,65	0,21	1920X1056X102

C: Central Heating / E: Electric / D: Dual Fuel