

BALLOSS STYLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020101504500550	450 x 550	3 (1+1)	40	50	58-83	83-108	43-68			0,30	0,3	C-E-D
5020101504500740	450 x 740	4 (1+1)	40	50	58-83	83-108	43-68			0,39	0,39	C-E-D
5020101504500940	450 x 940	5 (1+1)	40	50	58-83	83-108	43-68			0,48	0,48	C-E-D
5020101504501140	450 x 1140	6 (1+1)	40	50	58-83	83-108	43-68			0,58	0,58	C-E-D
5020101504501340	450 x 1340	7 (1+1)	40	50	58-83	83-108	43-68			0,67	0,67	C-E-D
5020101504501540	450 x 1540	8 (1+1)	40	50	58-83	83-108	43-68			0,77	0,77	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020101504500550	192	655	250	853
5020101504500740	258	880	336	1146
5020101504500940	327	1116	426	1453
5020101504501140	395	1347	514	1753
5020101504501340	464	1583	604	2060
5020101504501540	532	1815	692	2360

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020101504500550	4	4,6	0,02	650 x 540 x 55
5020101504500740	5,2	6	0,03	840 x 540 x 55
5020101504500940	6,5	7,4	0,04	1040 x 540 x 55
5020101504501140	7,7	8,8	0,04	1240 x 540 x 55
5020101504501340	8,9	10,2	0,05	1440 x 540 x 55
5020101504501540	10,1	11,6	0,05	1640 x 540 x 55