

BAMITO

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020101606000250	600 x 250	3 (3+3)	40	50	58-83	83-108	43-68	3	50	0,16	0,16	C-E-D
5020101606000450	600 x 450	6 (3+3)	40	50	58-83	83-108	43-68	3	48	0,25	0,25	C-E-D
5020101606000660	600 x 660	9 (3+3)	40	50	58-83	83-108	43-68	3	51	0,35	0,35	C-E-D
5020101606000864	600 x 864	12 (3+3)	40	50	58-83	83-108	43-68	3	50	0,45	0,45	C-E-D
5020101606001070	600 x 1070	15 (3+3)	40	50	58-83	83-108	43-68	3	50	0,55	0,55	C-E-D
5020101606001276	600 x 1276	18 (3+3)	40	50	58-83	83-108	43-68	3	50	0,64	0,64	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020101606000250	118	403	154	526
5020101606000450	221	754	288	983
5020101606000660	327	1116	426	1453
5020101606000864	432	1474	562	1917
5020101606001070	537	1832	699	2384
5020101606001276	642	2190	835	2848

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020101606000250	3	3,4	0,02	350 x 640 x 55
5020101606000450	5,3	5,9	0,02	550 x 640 x 55
5020101606000660	7,6	8,4	0,03	760 x 640 x 55
5020101606000864	9,9	11	0,04	964 x 640 x 55
5020101606001070	12,3	13,5	0,05	1170 x 640 x 55
5020101606001276	14,6	16	0,05	1376 x 640 x 55