

DUAL DOUBLE PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020104403000800	300 x 800	6 (2+4)	88	255	88/108	132/152	44/64	4	164	0,46	0,46	C-E-D
5020104403001200	300 x 1200	10 (4+6)	88	255	88/108	132/152	44/64	4	148	0,68	0,68	C-E-D
5020104403001550	300 x 1550	12 (2+4+6)	88	255	88/108	132/152	44/64	4	147	0,88	0,88	C-E-D
5020104404000800	400 x 800	6 (2+4)	88	355	88/108	132/152	44/64	4	164	0,46	0,46	C-E-D
5020104404001200	400 x 1200	10 (4+6)	88	355	88/108	132/152	44/64	4	148	0,68	0,68	C-E-D
5020104404001550	400 x 1550	12 (2+4+6)	88	355	88/108	132/152	44/64	4	147	0,88	0,88	C-E-D
5020104405000800	500 x 800	6 (2+4)	88	455	88/108	132/152	44/64	4	164	0,46	0,46	C-E-D
5020104405001200	500 x 1200	10 (4+6)	88	455	88/108	132/152	44/64	4	148	0,68	0,68	C-E-D
5020104405001550	500 x 1550	12 (2+4+6)	88	455	88/108	132/152	44/64	4	147	0,88	0,88	C-E-D
5020104406000800	600 x 800	6 (2+4)	88	555	88/108	132/152	44/64	4	164	0,46	0,46	C-E-D
5020104406001200	600 x 1200	10 (4+6)	88	555	88/108	132/152	44/64	4	148	0,68	0,68	C-E-D
5020104406001550	600 x 1550	12 (2+4+6)	88	555	88/108	132/152	44/64	4	147	0,88	0,88	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020104403000800	359	1225	467	1593
5020104403001200	579	1975	753	2568
5020104403001550	711	2425	925	3155
5020104404000800	479	1634	623	2125
5020104404001200	778	2653	1012	3451
5020104404001550	950	3240	1235	4212
5020104405000800	604	2060	786	2681
5020104405001200	986	3363	1282	4372
5020104405001550	1199	4089	1559	5317
5020104406000800	734	2503	955	3257
5020104406001200	1203	4103	1564	5334
5020104406001550	1459	4976	1897	6469

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020104403000800	6,8	7,7	0,06	900 x 540 x 110
5020104403001200	10,8	12,1	0,08	1300 x 540 x 110
5020104403001550	13,2	15	0,12	1650 x 640 x 110
5020104404000800	8,2	9,3	0,07	900 x 640 x 110
5020104404001200	13,2	14,7	0,1	1300 x 640 x 110
5020104404001550	16	17,1	0,05	1650 x 340 x 85
5020104405000800	9,7	10,3	0,03	900 x 340 x 85
5020104405001200	15,6	16,4	0,04	1300 x 340 x 85
5020104405001550	18,9	20	0,05	1650 x 340 x 85
5020104406000800	11,1	11,9	0,04	900 x 440 x 85
5020104406001200	18	19	0,05	1300 x 440 x 85
5020104406001550	21,8	23,1	0,07	1650 x 440 x 85