

IDA

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020106606000400	600 x 400	4 (2+2)	40	50	58-83	83-108	43-68	5	100	0,23	0,23	C-E-D
5020106606000605	600 x 605	6 (2+2)	40	50	58-83	83-108	43-68	5	100	0,33	0,33	C-E-D
5020106606000810	600 x 810	8 (2+2)	40	50	58-83	83-108	43-68	5	100	0,42	0,42	C-E-D
5020106606001015	600 x 1015	10 (2+2)	40	50	58-83	83-108	43-68	5	100	0,52	0,52	C-E-D
5020106606001220	600 x 1220	12 (2+2)	40	50	58-83	83-108	43-68	5	100	0,62	0,62	C-E-D
5020106606001425	600 x 1425	14 (2+2)	40	50	58-83	83-108	43-68	5	100	0,71	0,71	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020106606000400	175	597	228	778
5020106606000605	264	901	344	1174
5020106606000810	353	1204	459	1566
5020106606001015	442	1508	575	1961
5020106606001220	249	850	324	1105
5020106606001425	620	2115	806	2749

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020106606000400	5	5,6	0,02	500 x 640 x 55
5020106606000605	7,3	8,1	0,03	705 x 640 x 55
5020106606000810	9,6	10,6	0,04	910 x 640 x 55
5020106606001015	11,9	13,1	0,04	1115 x 640 x 55
5020106606001220	14,2	15,6	0,05	1320 x 640 x 55
5020106606001425	16,5	18,1	0,06	1525 x 640 x 55