

KAUNOS LINE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020106904500500	450 x 500	4 (2+2)	40	50	58-83	83-108	43-68	5	200	0,28	0,28	C-E-D
5020106904500805	450 x 805	6 (2+2)	40	50	58-83	83-108	43-68	5	200	0,42	0,42	C-E-D
5020106904501110	450 x 1110	8 (2+2)	40	50	58-83	83-108	43-68	5	200	0,57	0,57	C-E-D
5020106904501415	450 x 1415	10 (2+2)	40	50	58-83	83-108	43-68	5	200	0,71	0,71	C-E-D
5020106904501720	450 x 1720	12 (2+2)	40	50	58-83	83-108	43-68	5	200	0,85	0,85	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020106904500500	191	652	249	850
5020106904500805	302	1030	393	1341
5020106904501110	413	1409	537	1832
5020106904501415	523	1784	680	2319
5020106904501720	634	2162	825	2814

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020106904500500	4,5	5,1	0,02	600 x 540 x 55
5020106904500805	6,7	7,5	0,03	905 x 540 x 55
5020106904501110	8,9	10	0,04	1210 x 540 x 55
5020106904501415	11,1	12,4	0,05	1515 x 540 x 55
5020106904501720	13,2	14,9	0,06	1820 x 540 x 55