

KAUNOS STYLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020107004500340	450 x 340	2 (1+1)	40	50	58-83	83-108	43-68			0,20	0,2	C-E-D
5020107004500540	450 x 540	3 (1+1)	40	50	58-83	83-108	43-68			0,29	0,29	C-E-D
5020107004500740	450 x 740	4 (1+1)	40	50	58-83	83-108	43-68			0,39	0,39	C-E-D
5020107004500940	450 x 940	5 (1+1)	40	50	58-83	83-108	43-68			0,48	0,48	C-E-D
5020107004501140	450 x 1140	6 (1+1)	40	50	58-83	83-108	43-68			0,58	0,58	C-E-D
5020107004501340	450 x 1340	7 (1+1)	40	50	58-83	83-108	43-68			0,67	0,67	C-E-D
5020107004501540	450 x 1540	8 (1+1)	40	50	58-83	83-108	43-68			0,77	0,77	C-E-D
5020107004501740	450 x 1740	9 (1+1)	40	50	58-83	83-108	43-68			0,86	0,86	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020107004500340	121	413	158	539
5020107004500540	189	645	246	839
5020107004500740	258	880	336	1146
5020107004500940	327	1116	426	1453
5020107004501140	395	1347	514	1753
5020107004501340	464	1583	604	2060
5020107004501540	532	1815	692	2360
5020107004501740	601	2050	782	2667

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020107004500340	2,8	3,2	0,02	440 x 540 x 55
5020107004500540	4	4,6	0,02	640 x 540 x 55
5020107004500740	5,2	6	0,03	840 x 540 x 55
5020107004500940	6,5	7,4	0,04	1040 x 540 x 55
5020107004501140	7,7	8,8	0,04	1240 x 540 x 55
5020107004501340	8,9	10,2	0,05	1440 x 540 x 55
5020107004501540	10,1	11,6	0,05	1640 x 540 x 55
5020107004501740	11,4	13	0,06	1840 x 540 x 55