

LODOS LINE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020107803000750	300 x 750	8 (2+2)	26	255	70-90	80-105	54-74	21	158	0,43	0,43	C-E-D
5020107803001000	300 x 1000	10 (2+2)	26	255	70-90	80-105	54-74	21	166	0,57	0,57	C-E-D
5020107803001250	300 x 1250	12 (2+2)	26	255	70-90	80-105	54-74	21	171	0,71	0,71	C-E-D
5020107803001500	300 x 1500	14 (2+2)	26	255	70-90	80-105	54-74	21	174	0,85	0,85	C-E-D
5020107803001700	300 x 1700	16 (2+2)	26	255	70-90	80-105	54-74	21	170	0,97	0,97	C-E-D
5020107804000750	400 x 750	8 (2+2)	26	355	70-90	80-105	54-74	21	158	0,43	0,43	C-E-D
5020107804001000	400 x 1000	10 (2+2)	26	355	70-90	80-105	54-74	21	166	0,57	0,57	C-E-D
5020107804001250	400 x 1250	12 (2+2)	26	355	70-90	80-105	54-74	21	171	0,71	0,71	C-E-D
5020107804001500	400 x 1500	14 (2+2)	26	355	70-90	80-105	54-74	21	174	0,85	0,85	C-E-D
5020107804001700	400 x 1700	16 (2+2)	26	355	70-90	80-105	54-74	21	170	0,97	0,97	C-E-D
5020107805000750	500 x 750	8 (2+2)	26	455	70-90	80-105	54-74	21	158	0,43	0,43	C-E-D
5020107805001000	500 x 1000	10 (2+2)	26	455	70-90	80-105	54-74	21	166	0,57	0,57	C-E-D
5020107805001250	500 x 1250	12 (2+2)	26	455	70-90	80-105	54-74	21	171	0,71	0,71	C-E-D
5020107805001500	500 x 1500	14 (2+2)	26	455	70-90	80-105	54-74	21	174	0,85	0,85	C-E-D
5020107805001700	500 x 1700	16 (2+2)	26	455	70-90	80-105	54-74	21	170	0,97	0,97	C-E-D
5020107806000750	600 x 750	8 (2+2)	26	555	70-90	80-105	54-74	21	158	0,43	0,43	C-E-D
5020107806001000	600 x 1000	10 (2+2)	26	555	70-90	80-105	54-74	21	166	0,57	0,57	C-E-D
5020107806001250	600 x 1250	12 (2+2)	26	555	70-90	80-105	54-74	21	171	0,71	0,71	C-E-D
5020107806001500	600 x 1500	14 (2+2)	26	555	70-90	80-105	54-74	21	174	0,85	0,85	C-E-D
5020107806001700	600 x 1700	16 (2+2)	26	555	70-90	80-105	54-74	21	170	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020107803000750	172	587	224	764
5020107803001000	226	771	294	1003
5020107803001250	279	952	363	1238
5020107803001500	332	1133	432	1474
5020107803001700	378	1289	492	1678
5020107804000750	198	676	258	880
5020107804001000	258	880	336	1146
5020107804001250	318	1085	414	1412
5020107804001500	378	1289	492	1678
5020107804001700	429	1463	558	1903
5020107805000750	225	768	293	1000
5020107805001000	292	996	380	1296
5020107805001250	358	1221	466	1590
5020107805001500	425	1450	553	1886
5020107805001700	483	1648	628	2142
5020107806000750	253	863	329	1122
5020107806001000	327	1116	426	1453
5020107806001250	400	1364	520	1774
5020107806001500	474	1617	617	2104
5020107806001700	539	1838	701	2391

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020107803000750	3,4	3,9	0,02	850 x 340 x 55
5020107803001000	4,3	4,9	0,03	1100 x 340 x 55
5020107803001250	5,2	6	0,03	1350 x 340 x 55
5020107803001500	6,2	7,1	0,03	1600 x 340 x 55
5020107803001700	6,9	8	0,04	1800 x 340 x 55
5020107804000750	3,6	4,2	0,03	850 x 440 x 55
5020107804001000	4,6	5,4	0,03	1100 x 440 x 55
5020107804001250	5,6	6,6	0,04	1350 x 440 x 55
5020107804001500	6,6	7,8	0,04	1600 x 440 x 55
5020107804001700	7,4	8,8	0,05	1800 x 440 x 55
5020107805000750	3,8	4,6	0,03	850 x 540 x 55
5020107805001000	4,9	5,9	0,04	1100 x 540 x 55
5020107805001250	6	7,2	0,05	1350 x 540 x 55
5020107805001500	7	8,4	0,05	1600 x 540 x 55
5020107805001700	7,9	9,5	0,06	1800 x 540 x 55
5020107806000750	4,1	5,1	0,05	850 x 640 x 85
5020107806001000	5,2	6,4	0,06	1100 x 640 x 85
5020107806001250	6,3	7,8	0,08	1350 x 640 x 85
5020107806001500	7,4	9,2	0,09	1600 x 640 x 85
5020107806001700	8,4	10,4	0,1	1800 x 640 x 85