

LODOS PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020108003000800	300 x 800	14 (3+5+6)	26	255	70-90	80-105	54-74	21	131	0,46	0,46	C-E-D
5020108003001000	300 x 1000	18 (4+6+8)	26	255	70-90	80-105	54-74	21	151	0,57	0,57	C-E-D
5020108003001200	300 x 1200	21 (4+5+6+6)	26	255	70-90	80-105	54-74	21	134	0,68	0,68	C-E-D
5020108003001450	300 x 1450	28 (4+6+8+10)	26	255	70-90	80-105	54-74	21	124	0,83	0,83	C-E-D
5020108003001700	300 x 1700	30 (6+6+6+6+6+6)	26	255	70-90	80-105	54-74	21	141	0,97	0,97	C-E-D
5020108004000800	400 x 800	14 (3+5+6)	26	355	70-90	80-105	54-74	21	131	0,46	0,46	C-E-D
5020108004001000	400 x 1000	18 (4+6+8)	26	355	70-90	80-105	54-74	21	151	0,57	0,57	C-E-D
5020108004001200	400 x 1200	21 (4+5+6+6)	26	355	70-90	80-105	54-74	21	134	0,68	0,68	C-E-D
5020108004001450	400 x 1450	28 (4+6+8+10)	26	355	70-90	80-105	54-74	21	124	0,83	0,83	C-E-D
5020108004001700	400 x 1700	30 (6+6+6+6+6+6)	26	355	70-90	80-105	54-74	21	141	0,97	0,97	C-E-D
5020108005000800	500 x 800	14 (3+5+6)	26	455	70-90	80-105	54-74	21	131	0,46	0,46	C-E-D
5020108005001000	500 x 1000	18 (4+6+8)	26	455	70-90	80-105	54-74	21	151	0,57	0,57	C-E-D
5020108005001200	500 x 1200	21 (4+5+6+6)	26	455	70-90	80-105	54-74	21	134	0,68	0,68	C-E-D
5020108005001450	500 x 1450	28 (4+6+8+10)	26	455	70-90	80-105	54-74	21	124	0,83	0,83	C-E-D
5020108005001700	500 x 1700	30 (6+6+6+6+6+6)	26	455	70-90	80-105	54-74	21	141	0,97	0,97	C-E-D
5020108006000800	600 x 800	14 (3+5+6)	26	555	70-90	80-105	54-74	21	131	0,46	0,46	C-E-D
5020108006001000	600 x 1000	18 (4+6+8)	26	555	70-90	80-105	54-74	21	151	0,57	0,57	C-E-D
5020108006001200	600 x 1200	21 (4+5+6+6)	26	555	70-90	80-105	54-74	21	134	0,68	0,68	C-E-D
5020108006001450	600 x 1450	28 (4+6+8+10)	26	555	70-90	80-105	54-74	21	124	0,83	0,83	C-E-D
5020108006001700	600 x 1700	30 (6+6+6+6+6+6)	26	555	70-90	80-105	54-74	21	141	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020108003000800	215	734	280	955
5020108003001000	271	925	353	1204
5020108003001200	322	1099	419	1429
5020108003001450	404	1378	526	1794
5020108003001700	457	1559	595	2029
5020108004000800	260	887	338	1153
5020108004001000	329	1122	428	1460
5020108004001200	390	1330	507	1729
5020108004001450	494	1685	643	2193
5020108004001700	554	1890	721	2459
5020108005000800	307	1047	400	1364
5020108005001000	390	1330	507	1729
5020108005001200	460	1569	598	2040
5020108005001450	589	2009	766	2613
5020108005001700	655	2234	852	2906
5020108006000800	356	1214	463	1579
5020108006001000	453	1545	589	2009
5020108006001200	534	1821	695	2370
5020108006001450	687	2343	894	3049
5020108006001700	760	2592	988	3370

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020108003000800	4,1	4,6	0,02	900 x 340 x 55
5020108003001000	5,1	5,7	0,03	1100 x 340 x 55
5020108003001200	5,9	6,7	0,03	1300 x 340 x 55
5020108003001450	7,4	8,3	0,03	1550 x 340 x 55
5020108003001700	8,3	9,3	0,04	1800 x 340 x 55
5020108004000800	4,5	5,2	0,03	900 x 440 x 55
5020108004001000	5,6	6,4	0,03	1100 x 440 x 55
5020108004001200	6,6	7,5	0,04	1300 x 440 x 55
5020108004001450	8,2	9,4	0,04	1550 x 440 x 55
5020108004001700	9,2	10,5	0,05	1800 x 440 x 55
5020108005000800	4,9	5,8	0,03	900 x 540 x 55
5020108005001000	6,2	7,2	0,04	1100 x 540 x 55
5020108005001200	7,2	8,4	0,04	1300 x 540 x 55
5020108005001450	9,1	10,4	0,05	1550 x 540 x 55
5020108005001700	10,1	11,7	0,06	1800 x 540 x 55
5020108006000800	5,4	6,4	0,05	900 x 640 x 85
5020108006001000	6,7	7,9	0,06	1100 x 640 x 85
5020108006001200	7,9	9,3	0,08	1300 x 640 x 85
5020108006001450	9,9	11,6	0,09	1550 x 640 x 85
5020108006001700	11	13	0,1	1800 x 640 x 85