

LODOS STYLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020108203000700	300 x 700	6 (2+1+1+2)	26	255	70-90	80-105	54-74	21	168	0,40	0,4	C-E-D
5020108203001000	300 x 1000	6 (2+1+1+2)	26	255	70-90	80-105	54-74	21	153	0,57	0,57	C-E-D
5020108203001200	300 x 1200	6 (2+1+1+2)	26	255	70-90	80-105	54-74	21	132	0,68	0,68	C-E-D
5020108203001400	300 x 1400	6 (2+1+1+2)	26	255	70-90	80-105	54-74	21	121	0,80	0,8	C-E-D
5020108203001700	300 x 1700	6 (2+1+1+2)	26	255	70-90	80-105	54-74	21	123	0,97	0,97	C-E-D
5020108204000700	400 x 700	6 (2+1+1+2)	26	355	70-90	80-105	54-74	21	168	0,40	0,4	C-E-D
5020108204001000	400 x 1000	6 (2+1+1+2)	26	355	70-90	80-105	54-74	21	153	0,57	0,57	C-E-D
5020108204001200	400 x 1200	6 (2+1+1+2)	26	355	70-90	80-105	54-74	21	132	0,68	0,68	C-E-D
5020108204001400	400 x 1400	6 (2+1+1+2)	26	355	70-90	80-105	54-74	21	121	0,80	0,8	C-E-D
5020108204001700	400 x 1700	6 (2+1+1+2)	26	355	70-90	80-105	54-74	21	123	0,97	0,97	C-E-D
5020108205000700	500 x 700	6 (2+1+1+2)	26	455	70-90	80-105	54-74	21	168	0,40	0,4	C-E-D
5020108205001000	500 x 1000	6 (2+1+1+2)	26	455	70-90	80-105	54-74	21	153	0,57	0,57	C-E-D
5020108205001200	500 x 1200	6 (2+1+1+2)	26	455	70-90	80-105	54-74	21	132	0,68	0,68	C-E-D
5020108205001400	500 x 1400	6 (2+1+1+2)	26	455	70-90	80-105	54-74	21	121	0,80	0,8	C-E-D
5020108205001700	500 x 1700	6 (2+1+1+2)	26	455	70-90	80-105	54-74	21	123	0,97	0,97	C-E-D
5020108206000700	600 x 700	6 (2+1+1+2)	26	555	70-90	80-105	54-74	21	168	0,40	0,4	C-E-D
5020108206001000	600 x 1000	6 (2+1+1+2)	26	555	70-90	80-105	54-74	21	153	0,57	0,57	C-E-D
5020108206001200	600 x 1200	6 (2+1+1+2)	26	555	70-90	80-105	54-74	21	132	0,68	0,68	C-E-D
5020108206001400	600 x 1400	6 (2+1+1+2)	26	555	70-90	80-105	54-74	21	121	0,80	0,8	C-E-D
5020108206001700	600 x 1700	6 (2+1+1+2)	26	555	70-90	80-105	54-74	21	123	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020108203000700	152	519	198	676
5020108203001000	214	730	279	952
5020108203001200	259	884	337	1150
5020108203001400	304	1037	396	1351
5020108203001700	366	1249	476	1624
5020108204000700	172	587	224	764
5020108204001000	240	819	312	1064
5020108204001200	292	996	380	1296
5020108204001400	343	1170	446	1521
5020108204001700	411	1402	535	1825
5020108205000700	192	655	250	853
5020108205001000	267	911	348	1187
5020108205001200	325	1109	423	1443
5020108205001400	383	1307	498	1699
5020108205001700	458	1562	596	2033
5020108206000700	213	727	277	945
5020108206001000	295	1006	384	1310
5020108206001200	360	1228	468	1596
5020108206001400	425	1450	553	1886
5020108206001700	476	1624	619	2111

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020108203000700	3	3,5	0,02	800 x 340 x 55
5020108203001000	4,1	4,8	0,03	1100 x 340 x 55
5020108203001200	4,9	5,7	0,03	1300 x 340 x 55
5020108203001400	5,7	6,5	0,03	1500 x 340 x 55
5020108203001700	6,7	7,8	0,04	1800 x 340 x 55
5020108204000700	3,2	3,8	0,02	800 x 440 x 55
5020108204001000	4,3	5,2	0,03	1100 x 440 x 55
5020108204001200	5,2	6,2	0,04	1300 x 440 x 55
5020108204001400	6	7,1	0,04	1500 x 440 x 55
5020108204001700	7,2	8,5	0,05	1800 x 440 x 55
5020108205000700	3,4	4,1	0,03	800 x 540 x 55
5020108205001000	4,6	5,6	0,04	1100 x 540 x 55
5020108205001200	5,5	6,7	0,04	1300 x 540 x 55
5020108205001400	6,4	7,7	0,05	1500 x 540 x 55
5020108205001700	7,6	9,2	0,06	1800 x 540 x 55
5020108206000700	3,6	4,5	0,05	800 x 640 x 85
5020108206001000	4,8	6,1	0,06	1100 x 640 x 85
5020108206001200	5,8	7,2	0,08	1300 x 640 x 85
5020108206001400	6,8	8,4	0,09	1500 x 640 x 85
5020108206001700	8	10	0,1	1800 x 640 x 85