

MYRA

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020109503000520	300 x 520	2 (1+1)	41	255	36/45	63,5/72,5	23,1/32,1			0,30	0,3	C-E-D
5020109503000800	300 x 800	3 (1+1)	41	255	36/45	63,5/72,5	23,1/32,1			0,46	0,46	C-E-D
5020109503001100	300 x 1100	4 (1+1)	41	255	36/45	63,5/72,5	23,1/32,1			0,63	0,63	C-E-D
5020109503001400	300 x 1400	5 (1+1)	41	255	36/45	63,5/72,5	23,1/32,1			0,80	0,8	C-E-D
5020109503001700	300 x 1700	6 (1+1)	41	255	36/45	63,5/72,5	23,1/32,1			0,97	0,97	C-E-D
5020109504000520	400 x 520	2 (1+1)	41	355	36/45	63,5/72,5	23,1/32,1			0,30	0,3	C-E-D
5020109504000800	400 x 800	3 (1+1)	41	355	36/45	63,5/72,5	23,1/32,1			0,46	0,46	C-E-D
5020109504001100	400 x 1100	4 (1+1)	41	355	36/45	63,5/72,5	23,1/32,1			0,63	0,63	C-E-D
5020109504001400	400 x 1400	5 (1+1)	41	355	36/45	63,5/72,5	23,1/32,1			0,80	0,8	C-E-D
5020109504001700	400 x 1700	6 (1+1)	41	355	36/45	63,5/72,5	23,1/32,1			0,97	0,97	C-E-D
5020109505000520	500 x 520	2 (1+1)	41	455	36/45	63,5/72,5	23,1/32,1			0,30	0,3	C-E-D
5020109505000800	500 x 800	3 (1+1)	41	455	36/45	63,5/72,5	23,1/32,1			0,46	0,46	C-E-D
5020109505001100	500 x 1100	4 (1+1)	41	455	36/45	63,5/72,5	23,1/32,1			0,63	0,63	C-E-D
5020109505001400	500 x 1400	5 (1+1)	41	455	36/45	63,5/72,5	23,1/32,1			0,80	0,8	C-E-D
5020109505001700	500 x 1700	6 (1+1)	41	455	36/45	63,5/72,5	23,1/32,1			0,97	0,97	C-E-D
5020109506000520	600 x 520	2 (1+1)	41	555	36/45	63,5/72,5	23,1/32,1			0,30	0,3	C-E-D
5020109506000800	600 x 800	3 (1+1)	41	555	36/45	63,5/72,5	23,1/32,1			0,46	0,46	C-E-D
5020109506001100	600 x 1100	4 (1+1)	41	555	36/45	63,5/72,5	23,1/32,1			0,63	0,63	C-E-D
5020109506001400	600 x 1400	5 (1+1)	41	555	36/45	63,5/72,5	23,1/32,1			0,80	0,8	C-E-D
5020109506001700	600 x 1700	6 (1+1)	41	555	36/45	63,5/72,5	23,1/32,1			0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020109503000520	121	413	158	539
5020109503000800	184	628	240	819
5020109503001100	250	853	325	1109
5020109503001400	317	1081	413	1409
5020109503001700	383	1307	498	1699
5020109504000520	158	539	206	703
5020109504000800	240	819	312	1064
5020109504001100	325	1109	423	1443
5020109504001400	410	1399	533	1818
5020109504001700	495	1688	644	2197
5020109505000520	197	672	257	877
5020109505000800	299	1020	389	1327
5020109505001100	403	1375	524	1787
5020109505001400	508	1733	661	2255
5020109505001700	612	2087	796	2715
5020109506000520	238	812	310	1058
5020109506000800	360	1228	468	1596
5020109506001100	485	1654	631	2152
5020109506001400	609	2077	792	2701
5020109506001700	734	2503	955	3257

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020109503000520	3,3	3,7	0,02	620 x 340 x 55
5020109503000800	4,9	5,4	0,02	900 x 340 x 55
5020109503001100	6,5	7,2	0,03	1200 x 340 x 55
5020109503001400	8,1	9	0,03	1500 x 340 x 55
5020109503001700	9,7	10,8	0,04	1800 x 340 x 55
5020109504000520	3,9	4,4	0,02	620 x 440 x 70
5020109504000800	5,7	6,4	0,03	900 x 440 x 70
5020109504001100	7,6	8,5	0,04	1200 x 440 x 70
5020109504001400	9,5	10,6	0,05	1500 x 440 x 70
5020109504001700	11,4	12,7	0,06	1800 x 440 x 70
5020109505000520	4,4	5	0,02	620 x 540 x 55
5020109505000800	6,5	7,3	0,03	900 x 540 x 55
5020109505001100	8,7	9,8	0,04	1200 x 540 x 55
5020109505001400	10,8	12,2	0,05	1500 x 540 x 55
5020109505001700	13	14,6	0,06	1800 x 540 x 55
5020109506000520	5	5,6	0,03	620 x 640 x 55
5020109506000800	7,3	8,3	0,04	900 x 640 x 55
5020109506001100	9,8	11	0,05	1200 x 640 x 55
5020109506001400	12,2	13,7	0,06	1500 x 640 x 55
5020109506001700	14,6	16,5	0,07	1800 x 640 x 55