

MYRA DOUBLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020109603000520	300 x 520	2 (1+1)	56	255	50,6/59,6	78,1/87,1	37,7/46,7			0,30	0,3	C-E-D
5020109603000800	300 x 800	3 (1+1)	56	255	50,6/59,6	78,1/87,1	37,7/46,7			0,46	0,46	C-E-D
5020109603001100	300 x 1100	4 (1+1)	56	255	50,6/59,6	78,1/87,1	37,7/46,7			0,63	0,63	C-E-D
5020109603001400	300 x 1400	5 (1+1)	56	255	50,6/59,6	78,1/87,1	37,7/46,7			0,80	0,8	C-E-D
5020109603001700	300 x 1700	6 (1+1)	56	255	50,6/59,6	78,1/87,1	37,7/46,7			0,97	0,97	C-E-D
5020109604000520	400 x 520	2 (1+1)	56	355	50,6/59,6	78,1/87,1	37,7/46,7			0,30	0,3	C-E-D
5020109604000800	400 x 800	3 (1+1)	56	355	50,6/59,6	78,1/87,1	37,7/46,7			0,46	0,46	C-E-D
5020109604001100	400 x 1100	4 (1+1)	56	355	50,6/59,6	78,1/87,1	37,7/46,7			0,63	0,63	C-E-D
5020109604001400	400 x 1400	5 (1+1)	56	355	50,6/59,6	78,1/87,1	37,7/46,7			0,80	0,8	C-E-D
5020109604001700	400 x 1700	6 (1+1)	56	355	50,6/59,6	78,1/87,1	37,7/46,7			0,97	0,97	C-E-D
5020109605000520	500 x 520	2 (1+1)	56	455	50,6/59,6	78,1/87,1	37,7/46,7			0,30	0,3	C-E-D
5020109605000800	500 x 800	3 (1+1)	56	455	50,6/59,6	78,1/87,1	37,7/46,7			0,46	0,46	C-E-D
5020109605001100	500 x 1100	4 (1+1)	56	455	50,6/59,6	78,1/87,1	37,7/46,7			0,63	0,63	C-E-D
5020109605001400	500 x 1400	5 (1+1)	56	455	50,6/59,6	78,1/87,1	37,7/46,7			0,80	0,8	C-E-D
5020109605001700	500 x 1700	6 (1+1)	56	455	50,6/59,6	78,1/87,1	37,7/46,7			0,97	0,97	C-E-D
5020109606000520	600 x 520	2 (1+1)	56	555	50,6/59,6	78,1/87,1	37,7/46,7			0,30	0,3	C-E-D
5020109606000800	600 x 800	3 (1+1)	56	555	50,6/59,6	78,1/87,1	37,7/46,7			0,46	0,46	C-E-D
5020109606001100	600 x 1100	4 (1+1)	56	555	50,6/59,6	78,1/87,1	37,7/46,7			0,63	0,63	C-E-D
5020109606001400	600 x 1400	5 (1+1)	56	555	50,6/59,6	78,1/87,1	37,7/46,7			0,80	0,8	C-E-D
5020109606001700	600 x 1700	6 (1+1)	56	555	50,6/59,6	78,1/87,1	37,7/46,7			0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020109603000520	121	413	158	539
5020109603000800	184	628	240	819
5020109603001100	250	853	325	1109
5020109603001400	317	1081	413	1409
5020109603001700	383	1307	498	1699
5020109604000520	159	543	207	706
5020109604000800	240	819	312	1064
5020109604001100	325	1109	423	1443
5020109604001400	410	1399	533	1818
5020109604001700	495	1688	644	2197
5020109605000520	197	672	257	877
5020109605000800	299	1020	389	1327
5020109605001100	403	1375	524	1787
5020109605001400	508	1733	661	2255
5020109605001700	612	2087	796	2715
5020109606000520	238	812	310	1058
5020109606000800	360	1228	468	1596
5020109606001100	485	1654	631	2152
5020109606001400	609	2077	792	2701
5020109606001700	734	2503	955	3257

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020109603000520	4,4	4,8	0,02	620 x 340 x 85
5020109603000800	6,5	7,1	0,03	900 x 340 x 85
5020109603001100	8,6	9,4	0,04	1200 x 340 x 85
5020109603001400	10,8	11,7	0,05	1500 x 340 x 85
5020109603001700	12,9	14,1	0,06	1800 x 340 x 85
5020109604000520	5,3	5,8	0,03	620 x 440 x 85
5020109604000800	7,9	8,6	0,04	900 x 440 x 85
5020109604001100	10,5	11,4	0,05	1200 x 440 x 85
5020109604001400	13,1	14,3	0,06	1500 x 440 x 85
5020109604001700	15,7	17,1	0,07	1800 x 440 x 85
5020109605000520	6,2	6,9	0,03	620 x 540 x 85
5020109605000800	9,2	10,1	0,05	900 x 540 x 85
5020109605001100	12,3	13,4	0,06	1200 x 540 x 85
5020109605001400	15,3	16,8	0,07	1500 x 540 x 85
5020109605001700	18,4	20,1	0,09	1800 x 540 x 85
5020109606000520	7,1	7,9	0,04	620 x 640 x 85
5020109606000800	10,6	11,6	0,05	900 x 640 x 85
5020109606001100	14,1	15,4	0,07	1200 x 640 x 85
5020109606001400	17,6	19,3	0,09	1500 x 640 x 85
5020109606001700	21,1	23,1	0,1	1800 x 640 x 85