

NUMMO

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020109704500250	450 x 250	3 (3+3)	40	50	58-83	83-108	43-68	5	140	0,16	0,16	C-E-D
5020109704500540	450 x 540	6 (3+3)	40	50	58-83	83-108	43-68	5	130	0,29	0,29	C-E-D
5020109704500830	450 x 830	9 (3+3)	40	50	58-83	83-108	43-68	5	130	0,43	0,43	C-E-D
5020109704501120	450 x 1120	12 (3+3)	40	50	58-83	83-108	43-68	5	130	0,57	0,57	C-E-D
5020109704501410	450 x 1410	15 (3+3)	40	50	58-83	83-108	43-68	5	130	0,71	0,71	C-E-D
5020109704501700	450 x 1700	18 (3+3)	40	50	58-83	83-108	43-68	5	130	0,84	0,84	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020109704500250	109	372	142	485
5020109704500540	228	778	297	1013
5020109704500830	348	1187	453	1545
5020109704501120	468	1596	609	2077
5020109704501410	587	2002	764	2606
5020109704501700	707	2411	920	3138

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020109704500250	3,2	3,5	0,02	350 x 540 x 55
5020109704500540	5,9	6,5	0,02	640 x 540 x 55
5020109704500830	8,7	9,6	0,03	930 x 540 x 55
5020109704501120	11,5	12,6	0,04	1220 x 540 x 55
5020109704501410	14,3	15,6	0,05	1510 x 540 x 55
5020109704501700	17	18,6	0,06	1800 x 540 x 55