

NUMMO LINE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020109804500500	450 x 500	4 (2+2)	40	50	58-83	83-108	43-68	5	200	0,28	0,28	C-E-D
5020109804500800	450 x 800	6 (2+2)	40	50	58-83	83-108	43-68	5	197	0,42	0,42	C-E-D
5020109804501100	450 x 1100	8 (2+2)	40	50	58-83	83-108	43-68	5	196	0,56	0,56	C-E-D
5020109804501400	450 x 1400	10 (2+2)	40	50	58-83	83-108	43-68	5	196	0,70	0,7	C-E-D
5020109804501700	450 x 1700	12 (2+2)	40	50	58-83	83-108	43-68	5	196	0,84	0,84	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020109804500500	191	652	249	850
5020109804500800	301	1027	392	1337
5020109804501100	410	1399	533	1818
5020109804501400	519	1770	675	2302
5020109804501700	629	2145	818	2790

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020109804500500	4,5	5,1	0,02	600 x 540 x 55
5020109804500800	6,7	7,5	0,03	900 x 540 x 55
5020109804501100	8,9	9,9	0,04	1200 x 540 x 55
5020109804501400	11	12,4	0,05	1500 x 540 x 55
5020109804501700	13,2	14,8	0,06	1800 x 540 x 55