

RUBY PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020114903000600	300 x 600	7 (3+4)	52	255	63/73	102/122	51/71	4,5	204	0,34	0,34	C-E-D
5020114903000900	300 x 900	12 (5+7)	52	255	63/73	102/122	51/71	4,5	229	0,51	0,51	C-E-D
5020114903001200	300 x 1200	13 (3+4+6)	52	255	63/73	102/122	51/71	4,5	239	0,68	0,68	C-E-D
5020114903001400	300 x 1400	16 (4+6+6)	52	255	63/73	102/122	51/71	4,5	257	0,80	0,8	C-E-D
5020114903001700	300 x 1700	18 (3+3+6+6)	52	255	63/73	102/122	51/71	4,5	236	0,97	0,97	C-E-D
5020114904000600	400 x 600	7 (3+4)	52	355	63/73	102/122	51/71	4,5	204	0,34	0,34	C-E-D
5020114904000900	400 x 900	12 (5+7)	52	355	63/73	102/122	51/71	4,5	229	0,51	0,51	C-E-D
5020114904001200	400 x 1200	13 (3+4+6)	52	355	63/73	102/122	51/71	4,5	239	0,68	0,68	C-E-D
5020114904001400	400 x 1400	16 (4+6+6)	52	355	63/73	102/122	51/71	4,5	257	0,80	0,8	C-E-D
5020114904001700	400 x 1700	18 (3+3+6+6)	52	355	63/73	102/122	51/71	4,5	236	0,97	0,97	C-E-D
5020114905000600	500 x 600	7 (3+4)	52	455	63/73	102/122	51/71	4,5	204	0,34	0,34	C-E-D
5020114905000900	500 x 900	12 (5+7)	52	455	63/73	102/122	51/71	4,5	229	0,51	0,51	C-E-D
5020114905001200	500 x 1200	13 (3+4+6)	52	455	63/73	102/122	51/71	4,5	239	0,68	0,68	C-E-D
5020114905001400	500 x 1400	16 (4+6+6)	52	455	63/73	102/122	51/71	4,5	257	0,80	0,8	C-E-D
5020114905001700	500 x 1700	18 (3+3+6+6)	52	455	63/73	102/122	51/71	4,5	236	0,97	0,97	C-E-D
5020114906000600	600 x 600	7 (3+4)	52	555	63/73	102/122	51/71	4,5	204	0,34	0,34	C-E-D
5020114906000900	600 x 900	12 (5+7)	52	555	63/73	102/122	51/71	4,5	229	0,51	0,51	C-E-D
5020114906001200	600 x 1200	13 (3+4+6)	52	555	63/73	102/122	51/71	4,5	239	0,68	0,68	C-E-D
5020114906001400	600 x 1400	16 (4+6+6)	52	555	63/73	102/122	51/71	4,5	257	0,80	0,8	C-E-D
5020114906001700	600 x 1700	18 (3+3+6+6)	52	555	63/73	102/122	51/71	4,5	236	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020114903000600	207	706	270	921
5020114903000900	337	1150	439	1497
5020114903001200	397	1354	517	1763
5020114903001400	478	1630	622	2122
5020114903001700	556	1896	723	2466
5020114904000600	269	918	350	1194
5020114904000900	443	1511	576	1965
5020114904001200	512	1746	666	2272
5020114904001400	619	2111	805	2746
5020114904001700	715	2439	930	3172
5020114905000600	334	1139	435	1484
5020114905000900	553	1886	719	2452
5020114905001200	632	2156	822	2804
5020114905001400	767	2616	998	3404
5020114905001700	881	3005	1146	3908
5020114906000600	401	1368	522	1781
5020114906000900	668	2278	869	2964
5020114906001200	757	2582	985	3359
5020114906001400	920	3138	1196	4079
5020114906001700	1053	3591	1369	4669

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020114903000600	4,1	4,6	0,03	700 x 340 x 85
5020114903000900	6,5	7,1	0,03	1000 x 340 x 85
5020114903001200	7,6	8,4	0,04	1300 x 340 x 85
5020114903001400	9,1	10	0,05	1500 x 340 x 85
5020114903001700	10,5	11,6	0,06	1800 x 340 x 85
5020114904000600	4,8	5,4	0,03	700 x 440 x 85
5020114904000900	7,7	8,5	0,04	1000 x 440 x 85
5020114904001200	8,9	9,9	0,05	1300 x 440 x 85
5020114904001400	10,7	11,9	0,06	1500 x 440 x 85
5020114904001700	12,3	13,7	0,07	1800 x 440 x 85
5020114905000600	5,5	6,2	0,04	700 x 540 x 85
5020114905000900	8,9	9,9	0,05	1000 x 540 x 85
5020114905001200	10,2	11,4	0,06	1300 x 540 x 85
5020114905001400	12,3	13,7	0,07	1500 x 540 x 85
5020114905001700	14,1	15,8	0,09	1800 x 540 x 85
5020114906000600	6,2	7	0,04	700 x 640 x 85
5020114906000900	10,1	11,2	0,06	1000 x 640 x 85
5020114906001200	11,5	12,9	0,08	1300 x 640 x 85
5020114906001400	13,9	15,5	0,09	1500 x 640 x 85
5020114906001700	15,9	17,9	0,1	1800 x 640 x 85