

SIRIUS DOUBLE PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020115403000700	300 x 700	5 (2+3)	65	255	42/51	82/91	29/38	1	182	0,40	0,4	C-E-D
5020115403001000	300 x 1000	8 (3+5)	65	255	42/51	82/91	29/38	1	182	0,57	0,57	C-E-D
5020115403001200	300 x 1200	10 (4+6)	65	255	42/51	82/91	29/38	1	182	0,68	0,68	C-E-D
5020115403001500	300 x 1500	12 (3+4+5)	65	255	42/51	82/91	29/38	1	142	0,85	0,85	C-E-D
5020115403001700	300 x 1700	14 (3+5+6)	65	255	42/51	82/91	29/38	1	142	0,97	0,97	C-E-D
5020115404000700	400 x 700	5 (2+3)	65	355	42/51	82/91	29/38	1	182	0,40	0,4	C-E-D
5020115404001000	400 x 1000	8 (3+5)	65	355	42/51	82/91	29/38	1	182	0,57	0,57	C-E-D
5020115404001200	400 x 1200	10 (4+6)	65	355	42/51	82/91	29/38	1	182	0,68	0,68	C-E-D
5020115404001500	400 x 1500	12 (3+4+5)	65	355	42/51	82/91	29/38	1	142	0,85	0,85	C-E-D
5020115404001700	400 x 1700	14 (3+5+6)	65	355	42/51	82/91	29/38	1	142	0,97	0,97	C-E-D
5020115405000700	500 x 700	5 (2+3)	65	455	42/51	82/91	29/38	1	182	0,40	0,4	C-E-D
5020115405001000	500 x 1000	8 (3+5)	65	455	42/51	82/91	29/38	1	182	0,57	0,57	C-E-D
5020115405001200	500 x 1200	10 (4+6)	65	455	42/51	82/91	29/38	1	182	0,68	0,68	C-E-D
5020115405001500	500 x 1500	12 (3+4+5)	65	455	42/51	82/91	29/38	1	142	0,85	0,85	C-E-D
5020115405001700	500 x 1700	14 (3+5+6)	65	455	42/51	82/91	29/38	1	142	0,97	0,97	C-E-D
5020115406000700	600 x 700	5 (2+3)	65	555	42/51	82/91	29/38	1	182	0,40	0,4	C-E-D
5020115406001000	600 x 1000	8 (3+5)	65	555	42/51	82/91	29/38	1	182	0,57	0,57	C-E-D
5020115406001200	600 x 1200	10 (4+6)	65	555	42/51	82/91	29/38	1	182	0,68	0,68	C-E-D
5020115406001500	600 x 1500	12 (3+4+5)	65	555	42/51	82/91	29/38	1	142	0,85	0,85	C-E-D
5020115406001700	600 x 1700	14 (3+5+6)	65	555	42/51	82/91	29/38	1	142	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020115403000700	284	969	370	1262
5020115403001000	437	1491	569	1941
5020115403001200	539	1838	701	2391
5020115403001500	655	2234	852	2906
5020115403001700	757	2582	985	3359
5020115404000700	376	1283	489	1668
5020115404001000	584	1992	760	2592
5020115404001200	723	2466	940	3206
5020115404001500	876	2988	1139	3884
5020115404001700	1015	3462	1320	4502
5020115405000700	472	1610	614	2094
5020115405001000	738	2517	960	3274
5020115405001200	915	3121	1190	4058
5020115405001500	1107	3775	1440	4911
5020115405001700	1284	4379	1670	5695
5020115406000700	572	1951	744	2538
5020115406001000	898	3063	1168	3983
5020115406001200	1115	3803	1450	4945
5020115406001500	1347	4594	1752	5975
5020115406001700	1564	5334	2034	6936

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020115403000700	5,6	6,1	0,03	800 x 340 x 85
5020115403001000	8,4	9,1	0,04	1100 x 340 x 85
5020115403001200	10,3	11,2	0,04	1300 x 340 x 85
5020115403001500	12,5	13,5	0,05	1600 x 340 x 85
5020115403001700	14,4	15,5	0,06	1800 x 340 x 85
5020115404000700	6,7	7,4	0,03	800 x 440 x 85
5020115404001000	10,2	11,1	0,05	1100 x 440 x 85
5020115404001200	12,6	13,6	0,05	1300 x 440 x 85
5020115404001500	15,2	16,4	0,06	1600 x 440 x 85
5020115404001700	17,5	18,9	0,07	1800 x 440 x 85
5020115405000700	7,8	8,6	0,04	800 x 540 x 85
5020115405001000	12	13,1	0,06	1100 x 540 x 85
5020115405001200	14,8	16	0,06	1300 x 540 x 85
5020115405001500	17,8	19,3	0,08	1600 x 540 x 85
5020115405001700	20,6	22,3	0,09	1800 x 540 x 85
5020115406000700	8,9	9,9	0,05	800 x 640 x 85
5020115406001000	13,8	15	0,06	1100 x 640 x 85
5020115406001200	17	18,5	0,08	1300 x 640 x 85
5020115406001500	20,5	22,3	0,09	1600 x 640 x 85
5020115406001700	23,7	25,7	0,1	1800 x 640 x 85