

SIRIUS PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020115703000700	300 x 700	5 (2+3)	53	255	60/104	100/126	47/91	1	182	0,40	0,4	C-E-D
5020115703001000	300 x 1000	8 (3+5)	53	255	60/104	100/126	47/91	1	182	0,57	0,57	C-E-D
5020115703001200	300 x 1200	10 (4+6)	53	255	60/104	100/126	47/91	1	182	0,68	0,68	C-E-D
5020115703001500	300 x 1500	12 (3+4+5)	53	255	60/104	100/126	47/91	1	142	0,85	0,85	C-E-D
5020115703001700	300 x 1700	14 (3+5+6)	53	255	60/104	100/126	47/91	1	142	0,97	0,97	C-E-D
5020115704000700	400 x 700	5 (2+3)	53	355	60/104	100/126	47/91	1	182	0,40	0,4	C-E-D
5020115704001000	400 x 1000	8 (3+5)	53	355	60/104	100/126	47/91	1	182	0,57	0,57	C-E-D
5020115704001200	400 x 1200	10 (4+6)	53	355	60/104	100/126	47/91	1	182	0,68	0,68	C-E-D
5020115704001500	400 x 1500	12 (3+4+5)	53	355	60/104	100/126	47/91	1	142	0,85	0,85	C-E-D
5020115704001700	400 x 1700	14 (3+5+6)	53	355	60/104	100/126	47/91	1	142	0,97	0,97	C-E-D
5020115705000700	500 x 700	5 (2+3)	53	455	60/104	100/126	47/91	1	182	0,40	0,4	C-E-D
5020115705001000	500 x 1000	8 (3+5)	53	455	60/104	100/126	47/91	1	182	0,57	0,57	C-E-D
5020115705001200	500 x 1200	10 (4+6)	53	455	60/104	100/126	47/91	1	182	0,68	0,68	C-E-D
5020115705001500	500 x 1500	12 (3+4+5)	53	455	60/104	100/126	47/91	1	142	0,85	0,85	C-E-D
5020115705001700	500 x 1700	14 (3+5+6)	53	455	60/104	100/126	47/91	1	142	0,97	0,97	C-E-D
5020115706000700	600 x 700	5 (2+3)	53	555	60/104	100/126	47/91	1	182	0,40	0,4	C-E-D
5020115706001000	600 x 1000	8 (3+5)	53	555	60/104	100/126	47/91	1	182	0,57	0,57	C-E-D
5020115706001200	600 x 1200	10 (4+6)	53	555	60/104	100/126	47/91	1	182	0,68	0,68	C-E-D
5020115706001500	600 x 1500	12 (3+4+5)	53	555	60/104	100/126	47/91	1	142	0,85	0,85	C-E-D
5020115706001700	600 x 1700	14 (3+5+6)	53	555	60/104	100/126	47/91	1	142	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020115703000700	223	761	290	989
5020115703001000	340	1160	442	1508
5020115703001200	417	1422	543	1852
5020115703001500	509	1736	662	2258
5020115703001700	586	1999	762	2599
5020115704000700	293	1000	381	1300
5020115704001000	451	1538	587	2002
5020115704001200	557	1900	725	2473
5020115704001500	677	2309	881	3005
5020115704001700	782	2667	1017	3468
5020115705000700	366	1249	476	1624
5020115705001000	568	1937	739	2520
5020115705001200	703	2398	914	3117
5020115705001500	852	2906	1108	3779
5020115705001700	987	3366	1284	4379
5020115706000700	442	1508	575	1961
5020115706001000	690	2353	897	3059
5020115706001200	855	2916	1112	3792
5020115706001500	1035	3530	1346	4590
5020115706001700	1200	4092	1560	5320

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020115703000700	4,3	4,9	0,03	800 x 340 x 85
5020115703001000	6,4	7,1	0,04	1100 x 340 x 85
5020115703001200	7,8	8,6	0,04	1300 x 340 x 85
5020115703001500	9,4	10,5	0,05	1600 x 340 x 85
5020115703001700	10,8	12	0,06	1800 x 340 x 85
5020115704000700	5	5,7	0,03	800 x 440 x 85
5020115704001000	7,5	8,4	0,05	1100 x 440 x 85
5020115704001200	9,1	10,2	0,05	1300 x 440 x 85
5020115704001500	11	12,3	0,06	1600 x 440 x 85
5020115704001700	12,7	14,1	0,07	1800 x 440 x 85
5020115705000700	5,7	6,4	0,04	800 x 540 x 85
5020115705001000	8,5	9,6	0,06	1100 x 540 x 85
5020115705001200	10,5	11,7	0,06	1300 x 540 x 85
5020115705001500	12,6	14,2	0,08	1600 x 540 x 85
5020115705001700	14,6	16,3	0,09	1800 x 540 x 85
5020115706000700	6,3	7,2	0,05	800 x 640 x 85
5020115706001000	9,6	10,8	0,06	1100 x 640 x 85
5020115706001200	11,8	13,2	0,08	1300 x 640 x 85
5020115706001500	14,2	16	0,09	1600 x 640 x 85
5020115706001700	16,4	18,4	0,1	1800 x 640 x 85