

SOLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020115903000755	300 x 755	6 (3+3)	29	255	56-82	72-98	43-69	4	119	0,76	0,76	C-E-D
5020115903001180	300 x 1180	9 (3+3)	29	255	56-82	72-98	43-69	4	118	1,17	1,17	C-E-D
5020115903001615	300 x 1615	12 (3+3)	29	255	56-82	72-98	43-69	4	121	1,58	1,58	C-E-D
5020115904000755	400 x 755	6 (3+3)	29	355	56-82	72-98	43-69	4	119	0,85	0,85	C-E-D
5020115904001180	400 x 1180	9 (3+3)	29	355	56-82	72-98	43-69	4	118	1,30	1,3	C-E-D
5020115904001615	400 x 1615	12 (3+3)	29	355	56-82	72-98	43-69	4	121	1,75	1,75	C-E-D
5020115905000755	500 x 755	6 (3+3)	29	455	56-82	72-98	43-69	4	119	0,93	0,93	C-E-D
5020115905001180	500 x 1180	9 (3+3)	29	455	56-82	72-98	43-69	4	118	1,43	1,43	C-E-D
5020115905001615	500 x 1615	12 (3+3)	29	455	56-82	72-98	43-69	4	121	1,92	1,92	C-E-D
5020115906000755	600 x 755	6 (3+3)	29	555	56-82	72-98	43-69	4	119	1,02	1,02	C-E-D
5020115906001180	600 x 1180	9 (3+3)	29	555	56-82	72-98	43-69	4	118	1,55	1,55	C-E-D
5020115906001615	600 x 1615	12 (3+3)	29	555	56-82	72-98	43-69	4	121	2,09	2,09	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020115903000755	187	638	244	833
5020115903001180	288	983	375	1279
5020115903001615	389	1327	506	1726
5020115904000755	247	843	322	1099
5020115904001180	377	1286	491	1675
5020115904001615	508	1733	661	2255
5020115905000755	309	1054	402	1371
5020115905001180	470	1603	611	2084
5020115905001615	633	2159	823	2807
5020115906000755	374	1276	487	1661
5020115906001180	567	1934	738	2517
5020115906001615	762	2599	991	3380

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020115903000755	4,6	5,2	0,02	855 x 340 x 55
5020115903001180	6,9	7,7	0,03	1280 x 340 x 55
5020115903001615	9,3	10,3	0,04	1715 x 340 x 55
5020115904000755	5,2	5,9	0,03	855 x 440 x 55
5020115904001180	7,8	8,7	0,04	1280 x 440 x 55
5020115904001615	10,4	11,7	0,05	1715 x 440 x 55
5020115905000755	5,8	6,6	0,03	855 x 540 x 55
5020115905001180	8,6	9,8	0,04	1280 x 540 x 55
5020115905001615	11,5	13,1	0,06	1715 x 540 x 55
5020115906000755	6,3	7,3	0,05	855 x 640 x 85
5020115906001180	9,5	10,9	0,07	1280 x 640 x 85
5020115906001615	12,7	14,6	0,1	1715 x 640 x 85