

SOLE PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020116103000685	300 x 685	5 (2+3)	29	255	56-82	72-98	43-69	4	153	0,67	0,67	C-E-D
5020116103001000	300 x 1000	8 (3+5)	29	255	56-82	72-98	43-69	4	155	1,01	1,01	C-E-D
5020116103001200	300 x 1200	10 (4+6)	29	255	56-82	72-98	43-69	4	148	1,23	1,23	C-E-D
5020116103001550	300 x 1550	12 (3+4+5)	29	255	56-82	72-98	43-69	4	147	1,54	1,54	C-E-D
5020116103001770	300 x 1770	14 (3+5+6)	29	255	56-82	72-98	43-69	4	153	1,78	1,78	C-E-D
5020116104000685	400 x 685	5 (2+3)	29	355	56-82	72-98	43-69	4	153	0,74	0,74	C-E-D
5020116104001000	400 x 1000	8 (3+5)	29	355	56-82	72-98	43-69	4	155	1,13	1,13	C-E-D
5020116104001200	400 x 1200	10 (4+6)	29	355	56-82	72-98	43-69	4	148	1,38	1,38	C-E-D
5020116104001550	400 x 1550	12 (3+4+5)	29	355	56-82	72-98	43-69	4	147	1,71	1,71	C-E-D
5020116104001770	400 x 1770	14 (3+5+6)	29	355	56-82	72-98	43-69	4	153	1,98	1,98	C-E-D
5020116105000685	500 x 685	5 (2+3)	29	455	56-82	72-98	43-69	4	153	0,81	0,81	C-E-D
5020116105001000	500 x 1000	8 (3+5)	29	455	56-82	72-98	43-69	4	155	1,24	1,24	C-E-D
5020116105001200	500 x 1200	10 (4+6)	29	455	56-82	72-98	43-69	4	148	1,52	1,52	C-E-D
5020116105001550	500 x 1550	12 (3+4+5)	29	455	56-82	72-98	43-69	4	147	1,89	1,89	C-E-D
5020116105001770	500 x 1770	14 (3+5+6)	29	455	56-82	72-98	43-69	4	153	2,18	2,18	C-E-D
5020116106000685	600 x 685	5 (2+3)	29	555	56-82	72-98	43-69	4	153	0,88	0,88	C-E-D
5020116106001000	600 x 1000	8 (3+5)	29	555	56-82	72-98	43-69	4	155	1,35	1,35	C-E-D
5020116106001200	600 x 1200	10 (4+6)	29	555	56-82	72-98	43-69	4	148	1,66	1,66	C-E-D
5020116106001550	600 x 1550	12 (3+4+5)	29	555	56-82	72-98	43-69	4	147	2,06	2,06	C-E-D
5020116106001770	600 x 1770	14 (3+5+6)	29	555	56-82	72-98	43-69	4	153	2,38	2,38	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020116103000685	164	560	214	730
5020116103001000	249	850	324	1105
5020116103001200	303	1034	394	1344
5020116103001550	380	1296	494	1685
5020116103001770	438	1494	570	1944
5020116104000685	214	730	279	952
5020116104001000	328	1119	427	1457
5020116104001200	402	1371	523	1784
5020116104001550	499	1702	649	2214
5020116104001770	576	1965	749	2555
5020116105000685	266	908	346	1180
5020116105001000	411	1402	535	1825
5020116105001200	506	1726	658	2244
5020116105001550	623	2125	810	2763
5020116105001770	721	2459	938	3199
5020116106000685	320	1092	416	1419
5020116106001000	497	1695	647	2207
5020116106001200	614	2094	799	2725
5020116106001550	753	2568	979	3339
5020116106001770	872	2974	1134	3867

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020116103000685	4,1	4,5	0,02	785 x 340 x 55
5020116103001000	6,1	6,7	0,03	1100 x 340 x 55
5020116103001200	7,4	8,2	0,03	1300 x 340 x 55
5020116103001550	9,1	10,1	0,04	1650 x 340 x 55
5020116103001770	10,5	11,6	0,04	1870 x 340 x 55
5020116104000685	4,5	5,1	0,02	785 x 440 x 55
5020116104001000	6,8	7,7	0,03	1100 x 440 x 55
5020116104001200	8,3	9,3	0,04	1300 x 440 x 55
5020116104001550	10,2	11,5	0,04	1650 x 440 x 55
5020116104001770	11,8	13,2	0,05	1870 x 440 x 55
5020116105000685	5	5,7	0,03	785 x 540 x 55
5020116105001000	7,6	8,6	0,04	1100 x 540 x 55
5020116105001200	9,3	10,4	0,04	1300 x 540 x 55
5020116105001550	11,4	12,8	0,05	1650 x 540 x 55
5020116105001770	13,1	14,8	0,06	1870 x 540 x 55
5020116106000685	5,5	6,4	0,05	785 x 640 x 85
5020116106001000	8,3	9,6	0,06	1100 x 640 x 85
5020116106001200	10,2	11,7	0,08	1300 x 640 x 85
5020116106001550	12,5	14,3	0,09	1650 x 640 x 85
5020116106001770	14,5	16,5	0,11	1870 x 640 x 85