

STELLA DOUBLE PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020117503000700	300 x 700	5 (2+3)	63	255	57/66	88/97	26/35	4	188	0,40	0,4	C-E-D
5020117503001000	300 x 1000	8 (3+5)	63	255	57/66	88/97	26/35	4	188	0,57	0,57	C-E-D
5020117503001250	300 x 1250	9 (2+3+4)	63	255	57/66	88/97	26/35	4	171	0,71	0,71	C-E-D
5020117503001550	300 x 1550	12 (3+4+5)	63	255	57/66	88/97	26/35	4	171	0,88	0,88	C-E-D
5020117503001750	300 x 1750	14 (3+5+6)	63	255	57/66	88/97	26/35	4	171	1,00	1	C-E-D
5020117504000700	400 x 700	5 (2+3)	63	355	57/66	88/97	26/35	4	188	0,40	0,4	C-E-D
5020117504001000	400 x 1000	8 (3+5)	63	355	57/66	88/97	26/35	4	188	0,57	0,57	C-E-D
5020117504001250	400 x 1250	9 (2+3+4)	63	355	57/66	88/97	26/35	4	171	0,71	0,71	C-E-D
5020117504001550	400 x 1550	12 (3+4+5)	63	355	57/66	88/97	26/35	4	171	0,88	0,88	C-E-D
5020117504001750	400 x 1750	14 (3+5+6)	63	355	57/66	88/97	26/35	4	171	1,00	1	C-E-D
5020117505000700	500 x 700	5 (2+3)	63	455	57/66	88/97	26/35	4	188	0,40	0,4	C-E-D
5020117505001000	500 x 1000	8 (3+5)	63	455	57/66	88/97	26/35	4	188	0,57	0,57	C-E-D
5020117505001250	500 x 1250	9 (2+3+4)	63	455	57/66	88/97	26/35	4	171	0,71	0,71	C-E-D
5020117505001550	500 x 1550	12 (3+4+5)	63	455	57/66	88/97	26/35	4	171	0,88	0,88	C-E-D
5020117505001750	500 x 1750	14 (3+5+6)	63	455	57/66	88/97	26/35	4	171	1,00	1	C-E-D
5020117506000700	600 x 700	5 (2+3)	63	555	57/66	88/97	26/35	4	188	0,40	0,4	C-E-D
5020117506001000	600 x 1000	8 (3+5)	63	555	57/66	88/97	26/35	4	188	0,57	0,57	C-E-D
5020117506001250	600 x 1250	9 (2+3+4)	63	555	57/66	88/97	26/35	4	171	0,71	0,71	C-E-D
5020117506001550	600 x 1550	12 (3+4+5)	63	555	57/66	88/97	26/35	4	171	0,88	0,88	C-E-D
5020117506001750	600 x 1750	14 (3+5+6)	63	555	57/66	88/97	26/35	4	171	1,00	1	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020117503000700	285	972	371	1266
5020117503001000	439	1497	571	1948
5020117503001250	512	1746	666	2272
5020117503001550	665	2268	865	2950
5020117503001750	767	2616	998	3404
5020117504000700	377	1286	491	1675
5020117504001000	585	1995	761	2596
5020117504001250	677	2309	881	3005
5020117504001550	885	3018	1151	3925
5020117504001750	1024	3492	1332	4543
5020117505000700	473	1613	615	2098
5020117505001000	738	2517	960	3274
5020117505001250	849	2896	1104	3765
5020117505001550	1114	3799	1449	4942
5020117505001750	1291	4403	1679	5726
5020117506000700	572	1951	744	2538
5020117506001000	898	3063	1168	3983
5020117506001250	1028	3506	1337	4560
5020117506001550	1353	4614	1759	5999
5020117506001750	1570	5354	2041	6960

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020117503000700	5	5,5	0,03	800 x 340 x 85
5020117503001000	7,5	8,2	0,04	1100 x 340 x 85
5020117503001250	8,7	9,6	0,04	1350 x 340 x 85
5020117503001550	11,2	12,2	0,05	1650 x 340 x 85
5020117503001750	12,8	14	0,06	1850 x 340 x 85
5020117504000700	5,9	6,6	0,03	800 x 440 x 85
5020117504001000	8,9	9,8	0,05	1100 x 440 x 85
5020117504001250	10,3	11,4	0,06	1350 x 440 x 85
5020117504001550	13,3	14,7	0,07	1650 x 440 x 85
5020117504001750	15,4	16,8	0,07	1850 x 440 x 85
5020117505000700	6,8	7,6	0,04	800 x 540 x 85
5020117505001000	10,4	11,4	0,06	1100 x 540 x 85
5020117505001250	12	13,2	0,07	1350 x 540 x 85
5020117505001550	15,5	17,1	0,08	1650 x 540 x 85
5020117505001750	17,9	19,6	0,09	1850 x 540 x 85
5020117506000700	7,7	8,6	0,05	800 x 640 x 85
5020117506001000	11,8	13,1	0,06	1100 x 640 x 85
5020117506001250	13,6	15,1	0,08	1350 x 640 x 85
5020117506001550	17,7	19,5	0,09	1650 x 640 x 85
5020117506001750	20,5	22,5	0,11	1850 x 640 x 85