

STELLA PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020117703000700	300 x 700	5 (2+3)	44	255	35/44	70/79	26/35	4	188	0,40	0,4	C-E-D
5020117703001000	300 x 1000	8 (3+5)	44	255	35/44	70/79	26/35	4	188	0,57	0,57	C-E-D
5020117703001250	300 x 1250	9 (2+3+4)	44	255	35/44	70/79	26/35	4	171	0,71	0,71	C-E-D
5020117703001550	300 x 1550	12 (3+4+5)	44	255	35/44	70/79	26/35	4	171	0,88	0,88	C-E-D
5020117703001750	300 x 1750	14 (3+5+6)	44	255	35/44	70/79	26/35	4	171	1,00	1	C-E-D
5020117704000700	400 x 700	5 (2+3)	44	355	35/44	70/79	26/35	4	188	0,40	0,4	C-E-D
5020117704001000	400 x 1000	8 (3+5)	44	355	35/44	70/79	26/35	4	188	0,57	0,57	C-E-D
5020117704001250	400 x 1250	9 (2+3+4)	44	355	35/44	70/79	26/35	4	171	0,71	0,71	C-E-D
5020117704001550	400 x 1550	12 (3+4+5)	44	355	35/44	70/79	26/35	4	171	0,88	0,88	C-E-D
5020117704001750	400 x 1750	14 (3+5+6)	44	355	35/44	70/79	26/35	4	171	1,00	1	C-E-D
5020117705000700	500 x 700	5 (2+3)	44	455	35/44	70/79	26/35	4	188	0,40	0,4	C-E-D
5020117705001000	500 x 1000	8 (3+5)	44	455	35/44	70/79	26/35	4	188	0,57	0,57	C-E-D
5020117705001250	500 x 1250	9 (2+3+4)	44	455	35/44	70/79	26/35	4	171	0,71	0,71	C-E-D
5020117705001550	500 x 1550	12 (3+4+5)	44	455	35/44	70/79	26/35	4	171	0,88	0,88	C-E-D
5020117705001750	500 x 1750	14 (3+5+6)	44	455	35/44	70/79	26/35	4	171	1,00	1	C-E-D
5020117706000700	600 x 700	5 (2+3)	44	555	35/44	70/79	26/35	4	188	0,40	0,4	C-E-D
5020117706001000	600 x 1000	8 (3+5)	44	555	35/44	70/79	26/35	4	188	0,57	0,57	C-E-D
5020117706001250	600 x 1250	9 (2+3+4)	44	555	35/44	70/79	26/35	4	171	0,71	0,71	C-E-D
5020117706001550	600 x 1550	12 (3+4+5)	44	555	35/44	70/79	26/35	4	171	0,88	0,88	C-E-D
5020117706001750	600 x 1750	14 (3+5+6)	44	555	35/44	70/79	26/35	4	171	1,00	1	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020117703000700	225	768	293	1000
5020117703001000	342	1167	445	1518
5020117703001250	403	1375	524	1787
5020117703001550	519	1770	675	2302
5020117703001750	597	2036	777	2650
5020117704000700	294	1003	383	1307
5020117704001000	453	1545	589	2009
5020117704001250	528	1801	687	2343
5020117704001550	687	2343	894	3049
5020117704001750	792	2701	1030	3513
5020117705000700	367	1252	478	1630
5020117705001000	569	1941	740	2524
5020117705001250	659	2248	857	2923
5020117705001550	861	2937	1120	3820
5020117705001750	996	3397	1295	4416
5020117706000700	443	1511	576	1965
5020117706001000	690	2353	897	3059
5020117706001250	795	2711	1034	3526
5020117706001550	1043	3557	1356	4624
5020117706001750	1208	4120	1571	5358

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020117703000700	4,3	4,8	0,02	800 x 340 x 55
5020117703001000	6,3	7	0,03	1100 x 340 x 55
5020117703001250	7,4	8,2	0,03	1350 x 340 x 55
5020117703001550	9,5	10,4	0,04	1650 x 340 x 55
5020117703001750	10,8	11,9	0,04	1850 x 340 x 55
5020117704000700	4,9	5,6	0,03	800 x 440 x 70
5020117704001000	7,4	8,3	0,04	1100 x 440 x 70
5020117704001250	8,6	9,7	0,05	1350 x 440 x 70
5020117704001550	11,1	12,3	0,06	1650 x 440 x 70
5020117704001750	12,7	14,1	0,06	1850 x 440 x 70
5020117705000700	5,6	6,3	0,03	800 x 540 x 55
5020117705001000	8,5	9,5	0,04	1100 x 540 x 55
5020117705001250	9,8	11	0,05	1350 x 540 x 55
5020117705001550	12,7	14,1	0,05	1650 x 540 x 55
5020117705001750	14,6	16,2	0,06	1850 x 540 x 55
5020117706000700	6,3	7,1	0,03	800 x 640 x 55
5020117706001000	9,5	10,7	0,04	1100 x 640 x 55
5020117706001250	11	12,4	0,05	1350 x 640 x 55
5020117706001550	14,3	16	0,06	1650 x 640 x 55
5020117706001750	16,4	18,3	0,07	1850 x 640 x 55