

TALIA LINE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020118403000650	300 x 650	6 (2+2)	52	255	60-86	94-120	43-69	9	151	0,37	0,37	C-E-D
5020118403000950	300 x 950	8 (2+2)	52	255	60-86	94-120	43-69	9	165	0,54	0,54	C-E-D
5020118403001200	300 x 1200	10 (2+2)	52	255	60-86	94-120	43-69	9	159	0,68	0,68	C-E-D
5020118403001400	300 x 1400	12 (2+2)	52	255	60-86	94-120	43-69	9	145	0,80	0,8	C-E-D
5020118403001700	300 x 1700	14 (2+2)	52	255	60-86	94-120	43-69	9	153	0,97	0,97	C-E-D
5020118404000650	400 x 650	6 (2+2)	52	355	60-86	94-120	43-69	9	151	0,37	0,37	C-E-D
5020118404000950	400 x 950	8 (2+2)	52	355	60-86	94-120	43-69	9	165	0,54	0,54	C-E-D
5020118404001200	400 x 1200	10 (2+2)	52	355	60-86	94-120	43-69	9	159	0,68	0,68	C-E-D
5020118404001400	400 x 1400	12 (2+2)	52	355	60-86	94-120	43-69	9	145	0,80	0,8	C-E-D
5020118404001700	400 x 1700	14 (2+2)	52	355	60-86	94-120	43-69	9	153	0,97	0,97	C-E-D
5020118405000650	500 x 650	6 (2+2)	52	455	60-86	94-120	43-69	9	151	0,37	0,37	C-E-D
5020118405000950	500 x 950	8 (2+2)	52	455	60-86	94-120	43-69	9	165	0,54	0,54	C-E-D
5020118405001200	500 x 1200	10 (2+2)	52	455	60-86	94-120	43-69	9	159	0,68	0,68	C-E-D
5020118405001400	500 x 1400	12 (2+2)	52	455	60-86	94-120	43-69	9	145	0,80	0,8	C-E-D
5020118405001700	500 x 1700	14 (2+2)	52	455	60-86	94-120	43-69	9	153	0,97	0,97	C-E-D
5020118406000650	600 x 650	6 (2+2)	52	555	60-86	94-120	43-69	9	151	0,37	0,37	C-E-D
5020118406000950	600 x 950	8 (2+2)	52	555	60-86	94-120	43-69	9	165	0,54	0,54	C-E-D
5020118406001200	600 x 1200	10 (2+2)	52	555	60-86	94-120	43-69	9	159	0,68	0,68	C-E-D
5020118406001400	600 x 1400	12 (2+2)	52	555	60-86	94-120	43-69	9	145	0,80	0,8	C-E-D
5020118406001700	600 x 1700	14 (2+2)	52	555	60-86	94-120	43-69	9	153	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020118403000650	226	771	294	1003
5020118403000950	313	1068	407	1388
5020118403001200	393	1341	511	1743
5020118403001400	465	1586	605	2064
5020118403001700	552	1883	718	2449
5020118404000650	289	986	376	1283
5020118404000950	397	1354	517	1763
5020118404001200	498	1699	648	2210
5020118404001400	591	2016	769	2623
5020118404001700	700	2387	910	3104
5020118405000650	354	1208	461	1573
5020118405000950	485	1654	631	2152
5020118405001200	608	2074	791	2698
5020118405001400	723	2466	940	3206
5020118405001700	853	2909	1109	3782
5020118406000650	423	1443	550	1876
5020118406000950	576	1965	749	2555
5020118406001200	722	2463	939	3202
5020118406001400	860	2933	1118	3813
5020118406001700	1013	3455	1317	4491

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020118403000650	3,5	4	0,03	750 x 340 x 85
5020118403000950	4,8	5,5	0,04	1050 x 340 x 85
5020118403001200	5,9	6,8	0,04	1300 x 340 x 85
5020118403001400	7	7,9	0,05	1500 x 340 x 85
5020118403001700	8,3	9,4	0,06	1800 x 340 x 85
5020118404000650	3,9	4,6	0,03	750 x 440 x 85
5020118404000950	5,4	6,2	0,04	1050 x 440 x 85
5020118404001200	6,7	7,7	0,05	1300 x 440 x 85
5020118404001400	7,9	9,1	0,06	1500 x 440 x 85
5020118404001700	9,3	10,7	0,07	1800 x 440 x 85
5020118405000650	4,4	5,1	0,04	750 x 540 x 85
5020118405000950	6	7	0,05	1050 x 540 x 85
5020118405001200	7,4	8,7	0,06	1300 x 540 x 85
5020118405001400	8,8	10,2	0,07	1500 x 540 x 85
5020118405001700	10,4	12,1	0,09	1800 x 540 x 85
5020118406000650	4,8	5,7	0,05	750 x 640 x 85
5020118406000950	6,6	7,8	0,06	1050 x 640 x 85
5020118406001200	8,2	9,6	0,08	1300 x 640 x 85
5020118406001400	9,7	11,3	0,09	1500 x 640 x 85
5020118406001700	11,4	13,4	0,1	1800 x 640 x 85