

VIOLA LINE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020120203000700	300 x 700	6 (2+2)	33	255	69-91	84-106	54-76	15	172	0,40	0,4	C-E-D
5020120203001000	300 x 1000	8 (2+2)	33	255	69-91	84-106	54-76	15	180	0,57	0,57	C-E-D
5020120203001200	300 x 1200	10 (2+2)	33	255	69-91	84-106	54-76	15	159	0,68	0,68	C-E-D
5020120203001500	300 x 1500	12 (2+2)	33	255	69-91	84-106	54-76	15	166	0,85	0,85	C-E-D
5020120203001700	300 x 1700	14 (2+2)	33	255	69-91	84-106	54-76	15	154	0,97	0,97	C-E-D
5020120204000700	400 x 700	6 (2+2)	33	355	69-91	84-106	54-76	15	172	0,40	0,4	C-E-D
5020120204001000	400 x 1000	8 (2+2)	33	355	69-91	84-106	54-76	15	180	0,57	0,57	C-E-D
5020120204001200	400 x 1200	10 (2+2)	33	355	69-91	84-106	54-76	15	159	0,68	0,68	C-E-D
5020120204001500	400 x 1500	12 (2+2)	33	355	69-91	84-106	54-76	15	166	0,85	0,85	C-E-D
5020120204001700	400 x 1700	14 (2+2)	33	355	69-91	84-106	54-76	15	154	0,97	0,97	C-E-D
5020120205000700	500 x 700	6 (2+2)	33	455	69-91	84-106	54-76	15	172	0,40	0,4	C-E-D
5020120205001000	500 x 1000	8 (2+2)	33	455	69-91	84-106	54-76	15	180	0,57	0,57	C-E-D
5020120205001200	500 x 1200	10 (2+2)	33	455	69-91	84-106	54-76	15	159	0,68	0,68	C-E-D
5020120205001500	500 x 1500	12 (2+2)	33	455	69-91	84-106	54-76	15	166	0,85	0,85	C-E-D
5020120205001700	500 x 1700	14 (2+2)	33	455	69-91	84-106	54-76	15	154	0,97	0,97	C-E-D
5020120206000700	600 x 700	6 (2+2)	33	555	69-91	84-106	54-76	15	172	0,40	0,4	C-E-D
5020120206001000	600 x 1000	8 (2+2)	33	555	69-91	84-106	54-76	15	180	0,57	0,57	C-E-D
5020120206001200	600 x 1200	10 (2+2)	33	555	69-91	84-106	54-76	15	159	0,68	0,68	C-E-D
5020120206001500	600 x 1500	12 (2+2)	33	555	69-91	84-106	54-76	15	166	0,85	0,85	C-E-D
5020120206001700	600 x 1700	14 (2+2)	33	555	69-91	84-106	54-76	15	154	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020120203000700	161	550	210	717
5020120203001000	224	764	292	996
5020120203001200	273	931	355	1211
5020120203001500	335	1143	436	1487
5020120203001700	384	1310	500	1705
5020120204000700	197	672	257	877
5020120204001000	272	928	354	1208
5020120204001200	333	1136	433	1477
5020120204001500	408	1392	531	1811
5020120204001700	469	1600	610	2081
5020120205000700	236	805	307	1047
5020120205001000	323	1102	420	1433
5020120205001200	397	1354	517	1763
5020120205001500	485	1654	631	2152
5020120205001700	558	1903	726	2476
5020120206000700	275	938	358	1221
5020120206001000	376	1283	489	1668
5020120206001200	463	1579	602	2053
5020120206001500	564	1924	734	2503
5020120206001700	651	2220	847	2889

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020120203000700	3,3	3,8	0,02	800 x 340 x 55
5020120203001000	4,5	5,1	0,03	1100 x 340 x 55
5020120203001200	5,3	6,1	0,03	1300 x 340 x 55
5020120203001500	6,5	7,5	0,03	1600 x 340 x 55
5020120203001700	7,4	8,5	0,04	1800 x 340 x 55
5020120204000700	3,7	4,3	0,02	800 x 440 x 55
5020120204001000	5	5,8	0,03	1100 x 440 x 55
5020120204001200	6	7	0,04	1300 x 440 x 55
5020120204001500	7,3	8,5	0,04	1600 x 440 x 55
5020120204001700	8,3	9,6	0,05	1800 x 440 x 55
5020120205000700	4,1	4,8	0,03	800 x 540 x 55
5020120205001000	5,5	6,5	0,04	1100 x 540 x 55
5020120205001200	6,6	7,8	0,04	1300 x 540 x 55
5020120205001500	8	9,5	0,05	1600 x 540 x 55
5020120205001700	9,2	10,8	0,06	1800 x 540 x 55
5020120206000700	4,5	5,4	0,05	800 x 640 x 85
5020120206001000	6	7,2	0,06	1100 x 640 x 85
5020120206001200	7,3	8,7	0,08	1300 x 640 x 85
5020120206001500	8,8	10,6	0,09	1600 x 640 x 85
5020120206001700	10,1	12,1	0,1	1800 x 640 x 85