

VISTA PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020121403000700	300 x 700	7 (1+2+3+1)	33	255	69-90	84-105	54-75	15	120	0,40	0,4	C-E-D
5020121403001000	300 x 1000	11 (1+2+3+4+1)	33	255	69-90	84-105	54-75	15	109	0,57	0,57	C-E-D
5020121403001300	300 x 1300	14 (1+3+4+5+1)	33	255	69-90	84-105	54-75	15	139	0,74	0,74	C-E-D
5020121403001500	300 x 1500	16 (1+3+4+5+1)	33	255	69-90	84-105	54-75	15	130	0,85	0,85	C-E-D
5020121403001700	300 x 1700	18 (1+3+4+5+1)	33	255	69-90	84-105	54-75	15	122	0,97	0,97	C-E-D
5020121404000700	400 x 700	7 (1+2+3+1)	33	355	69-90	84-105	54-75	15	120	0,40	0,4	C-E-D
5020121404001000	400 x 1000	11 (1+2+3+4+1)	33	355	69-90	84-105	54-75	15	109	0,57	0,57	C-E-D
5020121404001300	400 x 1300	14 (1+3+4+5+1)	33	355	69-90	84-105	54-75	15	139	0,74	0,74	C-E-D
5020121404001500	400 x 1500	16 (1+3+4+5+1)	33	355	69-90	84-105	54-75	15	130	0,85	0,85	C-E-D
5020121404001700	400 x 1700	18 (1+3+4+5+1)	33	355	69-90	84-105	54-75	15	122	0,97	0,97	C-E-D
5020121405000700	500 x 700	7 (1+2+3+1)	33	455	69-90	84-105	54-75	15	120	0,40	0,4	C-E-D
5020121405001000	500 x 1000	11 (1+2+3+4+1)	33	455	69-90	84-105	54-75	15	109	0,57	0,57	C-E-D
5020121405001300	500 x 1300	14 (1+3+4+5+1)	33	455	69-90	84-105	54-75	15	139	0,74	0,74	C-E-D
5020121405001500	500 x 1500	16 (1+3+4+5+1)	33	455	69-90	84-105	54-75	15	130	0,85	0,85	C-E-D
5020121405001700	500 x 1700	18 (1+3+4+5+1)	33	455	69-90	84-105	54-75	15	122	0,97	0,97	C-E-D
5020121406000700	600 x 700	7 (1+2+3+1)	33	555	69-90	84-105	54-75	15	120	0,40	0,4	C-E-D
5020121406001000	600 x 1000	11 (1+2+3+4+1)	33	555	69-90	84-105	54-75	15	109	0,57	0,57	C-E-D
5020121406001300	600 x 1300	14 (1+3+4+5+1)	33	555	69-90	84-105	54-75	15	139	0,74	0,74	C-E-D
5020121406001500	600 x 1500	16 (1+3+4+5+1)	33	555	69-90	84-105	54-75	15	130	0,85	0,85	C-E-D
5020121406001700	600 x 1700	18 (1+3+4+5+1)	33	555	69-90	84-105	54-75	15	122	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020121403000700	159	543	207	706
5020121403001000	235	802	306	1044
5020121403001300	303	1034	394	1344
5020121403001500	348	1187	453	1545
5020121403001700	410	1399	533	1818
5020121404000700	196	669	255	870
5020121404001000	295	1006	384	1310
5020121404001300	379	1293	493	1682
5020121404001500	435	1484	566	1931
5020121404001700	519	1770	675	2302
5020121405000700	236	805	307	1047
5020121405001000	357	1218	465	1586
5020121405001300	458	1562	596	2033
5020121405001500	525	1791	683	2330
5020121405001700	632	2156	822	2804
5020121406000700	277	945	361	1232
5020121406001000	422	1440	549	1873
5020121406001300	540	1842	702	2394
5020121406001500	619	2111	805	2746
5020121406001700	750	2558	975	3325

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
	kg	kg	m³	mm
5020121403000700	3,6	4,1	0,02	800 x 340 x 55
5020121403001000	5,2	5,8	0,03	1100 x 340 x 55
5020121403001300	6,5	7,4	0,03	1400 x 340 x 55
5020121403001500	7,5	8,4	0,03	1600 x 340 x 55
5020121403001700	8,8	9,8	0,04	1800 x 340 x 55
5020121404000700	4,1	4,7	0,02	800 x 440 x 55
5020121404001000	5,9	6,8	0,03	1100 x 440 x 55
5020121404001300	7,5	8,6	0,04	1400 x 440 x 55
5020121404001500	8,6	9,8	0,04	1600 x 440 x 55
5020121404001700	10,2	11,5	0,05	1800 x 440 x 55
5020121405000700	4,6	5,3	0,03	800 x 540 x 55
5020121405001000	6,7	7,7	0,04	1100 x 540 x 55
5020121405001300	8,5	9,8	0,05	1400 x 540 x 55
5020121405001500	9,8	11,2	0,05	1600 x 540 x 55
5020121405001700	11,7	13,3	0,06	1800 x 540 x 55
5020121406000700	5	6	0,05	800 x 640 x 85
5020121406001000	7,5	8,7	0,06	1100 x 640 x 85
5020121406001300	9,5	11,1	0,08	1400 x 640 x 85
5020121406001500	10,9	12,7	0,09	1600 x 640 x 85
5020121406001700	13,1	15,1	0,1	1800 x 640 x 85