

WALDO

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020122003000755	300 x 755	6 (3+3)	47	255	60/80	90/110	45/65	4	119	0,43	0,43	C-E-D
5020122003001180	300 x 1180	9 (3+3)	47	255	60/80	90/110	45/65	4	118	0,67	0,67	C-E-D
5020122003001615	300 x 1615	12 (3+3)	47	255	60/80	90/110	45/65	4	121	0,92	0,92	C-E-D
5020122004000755	400 x 755	6 (3+3)	47	355	60/80	90/110	45/65	4	119	0,43	0,43	C-E-D
5020122004001180	400 x 1180	9 (3+3)	47	355	60/80	90/110	45/65	4	118	0,67	0,67	C-E-D
5020122004001615	400 x 1615	12 (3+3)	47	355	60/80	90/110	45/65	4	121	0,92	0,92	C-E-D
5020122005000755	500 x 755	6 (3+3)	47	455	60/80	90/110	45/65	4	119	0,43	0,43	C-E-D
5020122005001180	500 x 1180	9 (3+3)	47	455	60/80	90/110	45/65	4	118	0,67	0,67	C-E-D
5020122005001615	500 x 1615	12 (3+3)	47	455	60/80	90/110	45/65	4	121	0,92	0,92	C-E-D
5020122006000755	600 x 755	6 (3+3)	47	555	60/80	90/110	45/65	4	119	0,43	0,43	C-E-D
5020122006001180	600 x 1180	9 (3+3)	47	555	60/80	90/110	45/65	4	118	0,67	0,67	C-E-D
5020122006001615	600 x 1615	12 (3+3)	47	555	60/80	90/110	45/65	4	121	0,92	0,92	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020122003000755	252	860	328	1119
5020122003001180	385	1313	501	1709
5020122003001615	519	1770	675	2302
5020122004000755	335	1143	436	1487
5020122004001180	510	1740	663	2261
5020122004001615	685	2336	891	3039
5020122005000755	422	1440	549	1873
5020122005001180	639	2179	831	2834
5020122005001615	859	2930	1117	3809
5020122006000755	512	1746	666	2272
5020122006001180	775	2643	1008	3438
5020122006001615	1039	3543	1351	4607

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020122003000755	4,4	4,9	0,02	855 x 340 x 55
5020122003001180	6,6	7,3	0,03	1280 x 340 x 55
5020122003001615	8,8	9,8	0,04	1715 x 340 x 55
5020122004000755	5	5,7	0,03	855 x 440 x 70
5020122004001180	7,5	8,5	0,04	1280 x 440 x 70
5020122004001615	10	11,4	0,06	1715 x 440 x 70
5020122005000755	5,7	6,5	0,03	855 x 540 x 55
5020122005001180	8,5	9,6	0,04	1280 x 540 x 55
5020122005001615	11,3	12,8	0,06	1715 x 540 x 55
5020122006000755	6,3	7,2	0,04	855 x 640 x 55
5020122006001180	9,5	10,8	0,05	1280 x 640 x 55
5020122006001615	12,6	14,4	0,07	1715 x 640 x 55