

WALDO DOUBLE STYLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020122403000680	300 x 680	3 (1+1)	68	255	80/100	115/135	45/65			0,39	0,39	C-E-D
5020122403000960	300 x 960	4 (1+1)	68	255	80/100	115/135	45/65			0,55	0,55	C-E-D
5020122403001240	300 x 1240	5 (1+1)	68	255	80/100	115/135	45/65			0,71	0,71	C-E-D
5020122403001520	300 x 1520	6 (1+1)	68	255	80/100	115/135	45/65			0,87	0,87	C-E-D
5020122403001800	300 x 1800	7 (1+1)	68	255	80/100	115/135	45/65			1,02	1,02	C-E-D
5020122404000680	400 x 680	3 (1+1)	68	355	80/100	115/135	45/65			0,39	0,39	C-E-D
5020122404000960	400 x 960	4 (1+1)	68	355	80/100	115/135	45/65			0,55	0,55	C-E-D
5020122404001240	400 x 1240	5 (1+1)	68	355	80/100	115/135	45/65			0,71	0,71	C-E-D
5020122404001520	400 x 1520	6 (1+1)	68	355	80/100	115/135	45/65			0,87	0,87	C-E-D
5020122404001800	400 x 1800	7 (1+1)	68	355	80/100	115/135	45/65			1,02	1,02	C-E-D
5020122405000680	500 x 680	3 (1+1)	68	455	80/100	115/135	45/65			0,39	0,39	C-E-D
5020122405000960	500 x 960	4 (1+1)	68	455	80/100	115/135	45/65			0,55	0,55	C-E-D
5020122405001240	500 x 1240	5 (1+1)	68	455	80/100	115/135	45/65			0,71	0,71	C-E-D
5020122405001520	500 x 1520	6 (1+1)	68	455	80/100	115/135	45/65			0,87	0,87	C-E-D
5020122405001800	500 x 1800	7 (1+1)	68	455	80/100	115/135	45/65			1,02	1,02	C-E-D
5020122406000680	600 x 680	3 (1+1)	68	555	80/100	115/135	45/65			0,39	0,39	C-E-D
5020122406000960	600 x 960	4 (1+1)	68	555	80/100	115/135	45/65			0,55	0,55	C-E-D
5020122406001240	600 x 1240	5 (1+1)	68	555	80/100	115/135	45/65			0,71	0,71	C-E-D
5020122406001520	600 x 1520	6 (1+1)	68	555	80/100	115/135	45/65			0,87	0,87	C-E-D
5020122406001800	600 x 1800	7 (1+1)	68	555	80/100	115/135	45/65			1,02	1,02	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020122403000680	207	706	270	921
5020122403000960	283	966	368	1255
5020122403001240	360	1228	468	1596
5020122403001520	436	1487	567	1934
5020122403001800	513	1750	667	2275
5020122404000680	261	891	340	1160
5020122404000960	356	1214	463	1579
5020122404001240	451	1538	587	2002
5020122404001520	546	1862	710	2422
5020122404001800	640	2183	832	2838
5020122405000680	318	1085	414	1412
5020122405000960	432	1474	562	1917
5020122405001240	546	1862	710	2422
5020122405001520	660	2251	858	2926
5020122405001800	773	2636	1005	3428
5020122406000680	378	1289	492	1678
5020122406000960	511	1743	665	2268
5020122406001240	645	2200	839	2861
5020122406001520	778	2653	1012	3451
5020122406001800	912	3110	1186	4045

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020122403000680	3,8	4,4	0,03	780 x 340 x 90
5020122403000960	5,1	5,9	0,04	1060 x 340 x 90
5020122403001240	6,5	7,3	0,05	1340 x 340 x 90
5020122403001520	7,8	8,8	0,05	1620 x 340 x 90
5020122403001800	9,1	10,3	0,06	1900 x 340 x 90
5020122404000680	4,4	5	0,03	780 x 440 x 85
5020122404000960	5,9	6,8	0,04	1060 x 440 x 85
5020122404001240	7,4	8,5	0,06	1340 x 440 x 85
5020122404001520	8,9	10,2	0,07	1620 x 440 x 85
5020122404001800	10,4	11,9	0,08	1900 x 440 x 85
5020122405000680	4,9	5,7	0,04	780 x 540 x 90
5020122405000960	6,6	7,7	0,06	1060 x 540 x 90
5020122405001240	8,3	9,6	0,07	1340 x 540 x 90
5020122405001520	10	11,5	0,08	1620 x 540 x 90
5020122405001800	11,7	13,5	0,1	1900 x 540 x 90
5020122406000680	5,5	6,4	0,05	780 x 640 x 85
5020122406000960	7,4	8,6	0,06	1060 x 640 x 85
5020122406001240	9,2	10,7	0,08	1340 x 640 x 85
5020122406001520	11,1	12,9	0,09	1620 x 640 x 85
5020122406001800	13	15	0,11	1900 x 640 x 85