

WALDO PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020122603000685	300 x 685	5 (2+3)	47	255	60/80	90/110	45/65	4	153	0,39	0,39	C-E-D
5020122603001000	300 x 1000	8 (3+5)	47	255	60/80	90/110	45/65	4	155	0,57	0,57	C-E-D
5020122603001200	300 x 1200	10 (4+6)	47	255	60/80	90/110	45/65	4	148	0,68	0,68	C-E-D
5020122603001550	300 x 1550	12 (3+4+5)	47	255	60/80	90/110	45/65	4	147	0,88	0,88	C-E-D
5020122603001770	300 x 1770	14 (3+5+6)	47	255	60/80	90/110	45/65	4	153	1,01	1,01	C-E-D
5020122604000685	400 x 685	5 (2+3)	47	355	60/80	90/110	45/65	4	153	0,39	0,39	C-E-D
5020122604001000	400 x 1000	8 (3+5)	47	355	60/80	90/110	45/65	4	155	0,57	0,57	C-E-D
5020122604001200	400 x 1200	10 (4+6)	47	355	60/80	90/110	45/65	4	148	0,68	0,68	C-E-D
5020122604001550	400 x 1550	12 (3+4+5)	47	355	60/80	90/110	45/65	4	147	0,88	0,88	C-E-D
5020122604001770	400 x 1770	14 (3+5+6)	47	355	60/80	90/110	45/65	4	153	1,01	1,01	C-E-D
5020122605000685	500 x 685	5 (2+3)	47	455	60/80	90/110	45/65	4	153	0,39	0,39	C-E-D
5020122605001000	500 x 1000	8 (3+5)	47	455	60/80	90/110	45/65	4	155	0,57	0,57	C-E-D
5020122605001200	500 x 1200	10 (4+6)	47	455	60/80	90/110	45/65	4	148	0,68	0,68	C-E-D
5020122605001550	500 x 1550	12 (3+4+5)	47	455	60/80	90/110	45/65	4	147	0,88	0,88	C-E-D
5020122605001770	500 x 1770	14 (3+5+6)	47	455	60/80	90/110	45/65	4	153	1,01	1,01	C-E-D
5020122606000685	600 x 685	5 (2+3)	47	555	60/80	90/110	45/65	4	153	0,39	0,39	C-E-D
5020122606001000	600 x 1000	8 (3+5)	47	555	60/80	90/110	45/65	4	155	0,57	0,57	C-E-D
5020122606001200	600 x 1200	10 (4+6)	47	555	60/80	90/110	45/65	4	148	0,68	0,68	C-E-D
5020122606001550	600 x 1550	12 (3+4+5)	47	555	60/80	90/110	45/65	4	147	0,88	0,88	C-E-D
5020122606001770	600 x 1770	14 (3+5+6)	47	555	60/80	90/110	45/65	4	153	1,01	1,01	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020122603000685	218	744	284	969
5020122603001000	335	1143	436	1487
5020122603001200	411	1402	535	1825
5020122603001550	510	1740	663	2261
5020122603001770	589	2009	766	2613
5020122604000685	288	983	375	1279
5020122604001000	446	1521	580	1978
5020122604001200	550	1876	715	2439
5020122604001550	676	2306	879	2998
5020122604001770	783	2671	1018	3472
5020122605000685	360	1228	468	1596
5020122605001000	561	1914	730	2490
5020122605001200	694	2367	903	3080
5020122605001550	849	2896	1104	3765
5020122605001770	985	3359	1281	4369
5020122606000685	435	1484	566	1931
5020122606001000	682	2326	887	3025
5020122606001200	845	2882	1099	3748
5020122606001550	1030	3513	1339	4566
5020122606001770	1196	4079	1555	5303

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020122603000685	3,9	4,3	0,02	785 x 340 x 55
5020122603001000	5,7	6,4	0,03	1100 x 340 x 55
5020122603001200	7	7,7	0,03	1300 x 340 x 55
5020122603001550	8,6	9,6	0,04	1650 x 340 x 55
5020122603001770	9,9	11	0,04	1870 x 340 x 55
5020122604000685	4,4	5	0,03	785 x 440 x 70
5020122604001000	6,6	7,5	0,04	1100 x 440 x 70
5020122604001200	8	9	0,05	1300 x 440 x 70
5020122604001550	9,9	11,1	0,06	1650 x 440 x 70
5020122604001770	11,4	12,8	0,06	1870 x 440 x 70
5020122605000685	4,9	5,7	0,03	785 x 540 x 55
5020122605001000	7,5	8,4	0,04	1100 x 540 x 55
5020122605001200	9,1	10,3	0,04	1300 x 540 x 55
5020122605001550	11,2	12,6	0,05	1650 x 540 x 55
5020122605001770	12,9	14,5	0,06	1870 x 540 x 55
5020122606000685	5,5	6,3	0,03	785 x 640 x 55
5020122606001000	8,3	9,5	0,04	1100 x 640 x 55
5020122606001200	10,2	11,5	0,05	1300 x 640 x 55
5020122606001550	12,4	14,2	0,06	1650 x 640 x 55
5020122606001770	14,4	16,3	0,07	1870 x 640 x 55