

WALDO STYLE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020122703000680	300 x 680	3 (1+1)	47	255	60/80	90/110	45/65			0,39	0,39	C-E-D
5020122703000960	300 x 960	4 (1+1)	47	255	60/80	90/110	45/65			0,55	0,55	C-E-D
5020122703001240	300 x 1240	5 (1+1)	47	255	60/80	90/110	45/65			0,71	0,71	C-E-D
5020122703001520	300 x 1520	6 (1+1)	47	255	60/80	90/110	45/65			0,87	0,87	C-E-D
5020122703001800	300 x 1800	7 (1+1)	47	255	60/80	90/110	45/65			1,02	1,02	C-E-D
5020122704000680	400 x 680	3 (1+1)	47	355	60/80	90/110	45/65			0,39	0,39	C-E-D
5020122704000960	400 x 960	4 (1+1)	47	355	60/80	90/110	45/65			0,55	0,55	C-E-D
5020122704001240	400 x 1240	5 (1+1)	47	355	60/80	90/110	45/65			0,71	0,71	C-E-D
5020122704001520	400 x 1520	6 (1+1)	47	355	60/80	90/110	45/65			0,87	0,87	C-E-D
5020122704001800	400 x 1800	7 (1+1)	47	355	60/80	90/110	45/65			1,02	1,02	C-E-D
5020122705000680	500 x 680	3 (1+1)	47	455	60/80	90/110	45/65			0,39	0,39	C-E-D
5020122705000960	500 x 960	4 (1+1)	47	455	60/80	90/110	45/65			0,55	0,55	C-E-D
5020122705001240	500 x 1240	5 (1+1)	47	455	60/80	90/110	45/65			0,71	0,71	C-E-D
5020122705001520	500 x 1520	6 (1+1)	47	455	60/80	90/110	45/65			0,87	0,87	C-E-D
5020122705001800	500 x 1800	7 (1+1)	47	455	60/80	90/110	45/65			1,02	1,02	C-E-D
5020122706000680	600 x 680	3 (1+1)	47	555	60/80	90/110	45/65			0,39	0,39	C-E-D
5020122706000960	600 x 960	4 (1+1)	47	555	60/80	90/110	45/65			0,55	0,55	C-E-D
5020122706001240	600 x 1240	5 (1+1)	47	555	60/80	90/110	45/65			0,71	0,71	C-E-D
5020122706001520	600 x 1520	6 (1+1)	47	555	60/80	90/110	45/65			0,87	0,87	C-E-D
5020122706001800	600 x 1800	7 (1+1)	47	555	60/80	90/110	45/65			1,02	1,02	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020122703000680	171	584	223	761
5020122703000960	235	802	306	1044
5020122703001240	299	1020	389	1327
5020122703001520	364	1242	474	1617
5020122703001800	428	1460	557	1900
5020122704000680	212	723	276	942
5020122704000960	290	989	377	1286
5020122704001240	369	1259	480	1637
5020122704001520	447	1525	582	1985
5020122704001800	525	1791	683	2330
5020122705000680	255	870	332	1133
5020122705000960	348	1187	453	1545
5020122705001240	441	1504	574	1958
5020122705001520	534	1821	695	2370
5020122705001800	626	2135	814	2776
5020122706000680	301	1027	392	1337
5020122706000960	408	1392	531	1811
5020122706001240	516	1760	671	2289
5020122706001520	624	2128	812	2769
5020122706001800	732	2497	952	3247

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
5020122703000680	3,2	3,6	0,02	780 x 340 x 55
5020122703000960	4,3	4,9	0,02	1060 x 340 x 55
5020122703001240	5,3	6,1	0,03	1340 x 340 x 55
5020122703001520	6,4	7,4	0,04	1620 x 340 x 55
5020122703001800	7,5	8,6	0,04	1900 x 340 x 55
5020122704000680	3,5	4,1	0,03	780 x 440 x 70
5020122704000960	4,7	5,5	0,04	1060 x 440 x 70
5020122704001240	5,9	6,9	0,05	1340 x 440 x 70
5020122704001520	7,1	8,3	0,05	1620 x 440 x 70
5020122704001800	8,3	9,7	0,06	1900 x 440 x 70
5020122705000680	3,8	4,5	0,03	780 x 540 x 55
5020122705000960	5,1	6,1	0,04	1060 x 540 x 55
5020122705001240	6,4	7,6	0,04	1340 x 540 x 55
5020122705001520	7,7	9,2	0,05	1620 x 540 x 55
5020122705001800	9	10,7	0,06	1900 x 540 x 55
5020122706000680	4,1	5	0,03	780 x 640 x 55
5020122706000960	5,5	6,7	0,04	1060 x 640 x 55
5020122706001240	7	8,4	0,05	1340 x 640 x 55
5020122706001520	8,4	10	0,06	1620 x 640 x 55
5020122706001800	9,8	11,7	0,07	1900 x 640 x 55