

KALSEDON SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020124001851600	185 x 1600	2 (1+1)	43	50	35/44	65/74	22/31			0,11	0,11	C-E-D
5020124001851800	185 x 1800	2 (1+1)	43	50	35/44	65/74	22/31			0,11	0,11	C-E-D
5020124002801600	280 x 1600	3 (1+1)	43	50	35/44	65/74	22/31			0,16	0,16	C-E-D
5020124002801800	280 x 1800	3 (1+1)	43	50	35/44	65/74	22/31			0,16	0,16	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020124001851600	573	1954	745	2541
5020124001851800	656	2237	853	2909
5020124002801600	742	2531	965	3291
5020124002801800	852	2906	1108	3779

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
	kg	kg	m³	mm
5020124001851600	4,4	5,5	0,05	1700 x 340 x 85
5020124001851800	4,9	6,4	0,08	1900 x 440 x 85
5020124002801600	6,6	7,7	0,05	1700 x 340 x 85
5020124002801800	7,3	8,5	0,06	1900 x 340 x 85