

OTIS SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020124102041600	204 x 1600	2 (1+1)	47	50	35/44	69/78	22/31			0,12	0,12	C-E-D
5020124102041800	204 x 1800	2 (1+1)	47	50	35/44	69/78	22/31			0,12	0,12	C-E-D
5020124103081600	308 x 1600	3 (1+1)	47	50	35/44	69/78	22/31			0,18	0,18	C-E-D
5020124103081800	308 x 1800	3 (1+1)	47	50	35/44	69/78	22/31			0,18	0,18	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020124102041600	582	1985	757	2582
5020124102041800	667	2275	868	2960
5020124103081600	756	2578	983	3353
5020124103081800	869	2964	1130	3854

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020124102041600	4,3	5,4	0,06	1700 x 340 x 90
5020124102041800	4,7	6,2	0,08	1900 x 440 x 85
5020124103081600	6,3	7,4	0,05	1700 x 340 x 85
5020124103081800	6,9	8,2	0,06	1900 x 340 x 85