

DIAMOND SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020124201961600	196 x 1600	2 (1+1)	44	50	35/44	72/81	22/31			0,12	0,12	C-E-D
5020124201961800	196 x 1800	2 (1+1)	44	50	35/44	72/81	22/31			0,12	0,12	C-E-D
5020124202961600	296 x 1600	3 (1+1)	44	50	35/44	72/81	22/31			0,17	0,17	C-E-D
5020124202961800	296 x 1800	3 (1+1)	44	50	35/44	72/81	22/31			0,17	0,17	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020124201961600	585	1995	761	2596
5020124201961800	671	2289	873	2977
5020124202961600	761	2596	990	3376
5020124202961800	874	2981	1137	3878

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020124201961600	5,1	6,2	0,05	1700 x 340 x 85
5020124201961800	5,6	6,8	0,06	1900 x 340 x 85
5020124202961600	7,5	8,6	0,05	1700 x 340 x 85
5020124202961800	8,3	9,5	0,06	1900 x 340 x 85