

VOLE SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020124901881600	188 x 1600	3 (1+1)	80	50	56/65	106/115	26/35			0,11	0,11	C-E-D
5020124901881800	188 x 1800	3 (1+1)	80	50	56/65	106/115	26/35			0,11	0,11	C-E-D
5020124902521600	252 x 1600	4 (1+1)	80	50	56/65	106/115	26/35			0,15	0,15	C-E-D
5020124902521800	252 x 1800	4 (1+1)	80	50	56/65	106/115	26/35			0,15	0,15	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020124901881600	726	2476	944	3220
5020124901881800	832	2838	1082	3690
5020124902521600	890	3035	1157	3946
5020124902521800	1022	3486	1329	4532

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020124901881600	8	9,3	0,07	1700 x 440 x 85
5020124901881800	8,9	10,3	0,06	1900 x 440 x 70
5020124902521600	10,6	11,6	0,04	1700 x 340 x 55
5020124902521800	11,8	12,9	0,04	1900 x 340 x 55