

OTIS DOUBLE SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020125702041600	204 x 1600	2 (1+1)	68	50	60/69	123/132	26/35			0,12	0,12	C-E-D
5020125702041800	204 x 1800	2 (1+1)	68	50	60/69	123/132	26/35			0,12	0,12	C-E-D
5020125703081600	308 x 1600	3 (1+1)	68	50	60/69	123/132	26/35			0,18	0,18	C-E-D
5020125703081800	308 x 1800	3 (1+1)	68	50	60/69	123/132	26/35			0,18	0,18	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020125702041600	701	2391	912	3110
5020125702041800	804	2742	1046	3567
5020125703081600	934	3185	1215	4144
5020125703081800	1074	3663	1397	4764

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020125702041600	6,8	8,1	0,07	1700 x 440 x 85
5020125702041800	7,5	9	0,06	1900 x 440 x 70
5020125703081600	10	11	0,04	1700 x 340 x 55
5020125703081800	11,1	12,2	0,04	1900 x 340 x 55