

**ORPIMENT SLIM**

**TECHNICAL INFORMATION**

MODEL CODE	Width x Height ( W x H )	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020126102041600	204 x 1600	2 (1+1)	48	50	35/44	70/79	22/31			0,12	0,12	C-E-D
5020126102041800	204 x 1800	2 (1+1)	48	50	35/44	70/79	22/31			0,12	0,12	C-E-D
5020126103081600	308 x 1600	3 (1+1)	48	50	35/44	70/79	22/31			0,18	0,18	C-E-D
5020126103081800	308 x 1800	3 (1+1)	48	50	35/44	70/79	22/31			0,18	0,18	C-E-D

**HEAT OUTPUTS INFORMATION**

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020126102041600	421	1436	548	1869
5020126102041800	483	1648	628	2142
5020126103081600	515	1757	670	2285
5020126103081800	592	2019	770	2626

**LOGISTICS INFORMATION**

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions ( H x W x D )
mm	kg	kg	m³	mm
5020126102041600	5,3	6,3	0,05	1700 x 340 x 85
5020126102041800	5,8	6,9	0,04	1900 x 340 x 60
5020126103081600	7,7	8,7	0,04	1700 x 340 x 60
5020126103081800	8,5	9,7	0,04	1900 x 340 x 60