

ROYAL DOUBLE SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020126302181600	218 x 1600	3 (1+1)	52	50	52/61	78/87	26/35			0,13	0,13	C-E-D
5020126302181800	218 x 1800	3 (1+1)	52	50	52/61	78/87	26/35			0,13	0,13	C-E-D
5020126302921600	292 x 1600	4 (1+1)	52	50	52/61	78/87	26/35			0,17	0,17	C-E-D
5020126302921800	292 x 1800	4 (1+1)	52	50	52/61	78/87	26/35			0,17	0,17	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020126302181600	654	2231	851	2902
5020126302181800	750	2558	975	3325
5020126302921600	794	2708	1033	3523
5020126302921800	913	3114	1187	4048

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
	kg	kg	m³	mm
5020126302181600	7,5	8,6	0,05	1700 x 340 x 85
5020126302181800	8,4	9,6	0,06	1900 x 340 x 85
5020126302921600	9,9	11	0,05	1700 x 340 x 85
5020126302921800	11,1	12,3	0,06	1900 x 340 x 85