

OPAL PLUS SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020126601901600	190 x 1600	4 (1+1)	82	50	82/102	123/143	42/62			0,11	0,11	C-E-D
5020126601901800	190 x 1800	4 (1+1)	82	50	82/102	123/143	42/62			0,11	0,11	C-E-D
5020126602401600	240 x 1600	5 (1+1)	82	50	82/102	123/143	42/62			0,14	0,14	C-E-D
5020126602401800	240 x 1800	5 (1+1)	82	50	82/102	123/143	42/62			0,14	0,14	C-E-D
5020126602901600	290 x 1600	6 (1+1)	82	50	82/102	123/143	42/62			0,17	0,17	C-E-D
5020126602901800	290 x 1800	6 (1+1)	82	50	82/102	123/143	42/62			0,17	0,17	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020126601901600	834	2844	1085	3700
5020126601901800	956	3260	1243	4239
5020126602401600	984	3356	1280	4365
5020126602401800	1129	3850	1468	5006
5020126602901600	1134	3867	1475	5030
5020126602901800	1302	4440	1693	5774

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020126601901600	10	11	0,04	1700 x 340 x 60
5020126601901800	11,1	12,3	0,06	1900 x 340 x 85
5020126602401600	12,5	13,5	0,04	1700 x 340 x 60
5020126602401800	13,9	15,1	0,06	1900 x 340 x 85
5020126602901600	14,9	15,9	0,04	1700 x 340 x 60
5020126602901800	16,6	17,8	0,06	1900 x 340 x 85