

BAMBOO SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020127502391600	239 x 1600	2 (1+1)	29	50	84/93	63/72	24/33			0,14	0,14	C-E-D
5020127502391800	239 x 1800	2 (1+1)	29	50	84/93	63/72	24/33			0,14	0,14	C-E-D
5020127503591600	359 x 1600	3 (1+1)	29	50	84/93	63/72	24/33			0,21	0,21	C-E-D
5020127503591800	359 x 1800	3 (1+1)	29	50	84/93	63/72	24/33			0,21	0,21	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020127502391600	508	1733	661	2255
5020127502391800	582	1985	757	2582
5020127503591600	644	2197	838	2858
5020127503591800	742	2531	965	3291

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020127502391600	5,2	6,4	0,07	1700 x 340 x 110
5020127502391800	5,8	7,1	0,08	1900 x 340 x 110
5020127503591600	7,7	8,9	0,07	1700 x 340 x 110
5020127503591800	8,5	9,7	0,06	1900 x 340 x 85