

BAMBOO DOUBLE SLIM

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020127602391600	239 x 1600	2 (1+1)	52	50	50/59	78/87	26/35			0,14	0,14	C-E-D
5020127602391800	239 x 1800	2 (1+1)	52	50	50/59	78/87	26/35			0,14	0,14	C-E-D
5020127603591600	359 x 1600	3 (1+1)	52	50	50/59	78/87	26/35			0,21	0,21	C-E-D
5020127603591800	359 x 1800	3 (1+1)	52	50	50/59	78/87	26/35			0,21	0,21	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020127602391600	605	2064	787	2684
5020127602391800	694	2367	903	3080
5020127603591600	790	2694	1027	3503
5020127603591800	909	3100	1182	4031

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
	kg	kg	m³	mm
5020127602391600	8,1	9,4	0,05	1700 x 440 x 55
5020127602391800	9	10,3	0,08	1900 x 340 x 110
5020127603591600	12	13,2	0,07	1700 x 340 x 110
5020127603591800	13,4	14,7	0,08	1900 x 340 x 110