

VIOLA PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020128503000700	300 x 700	9 (3+6)	33	255	69-91	84-106	54-76	15	149	0,40	0,4	C-E-D
5020128503001000	300 x 1000	12 (3+4+5)	33	255	69-91	84-106	54-76	15	142	0,57	0,57	C-E-D
5020128503001250	300 x 1250	15 (4+5+6)	33	255	69-91	84-106	54-76	15	177	0,71	0,71	C-E-D
5020128503001550	300 x 1550	18 (4+4+5+5)	33	255	69-91	84-106	54-76	15	163	0,88	0,88	C-E-D
5020128503001700	300 x 1700	20 (4+4+5+7)	33	255	69-91	84-106	54-76	15	173	0,97	0,97	C-E-D
5020128504000700	400 x 700	9 (3+6)	33	355	69-91	84-106	54-76	15	149	0,40	0,4	C-E-D
5020128504001000	400 x 1000	12 (3+4+5)	33	355	69-91	84-106	54-76	15	142	0,57	0,57	C-E-D
5020128504001250	400 x 1250	15 (4+5+6)	33	355	69-91	84-106	54-76	15	177	0,71	0,71	C-E-D
5020128504001550	400 x 1550	18 (4+4+5+5)	33	355	69-91	84-106	54-76	15	163	0,88	0,88	C-E-D
5020128504001700	400 x 1700	20 (4+4+5+7)	33	355	69-91	84-106	54-76	15	173	0,97	0,97	C-E-D
5020128505000700	500 x 700	9 (3+6)	33	455	69-91	84-106	54-76	15	149	0,40	0,4	C-E-D
5020128505001000	500 x 1000	12 (3+4+5)	33	455	69-91	84-106	54-76	15	142	0,57	0,57	C-E-D
5020128505001250	500 x 1250	15 (4+5+6)	33	455	69-91	84-106	54-76	15	177	0,71	0,71	C-E-D
5020128505001550	500 x 1550	18 (4+4+5+5)	33	455	69-91	84-106	54-76	15	163	0,88	0,88	C-E-D
5020128505001700	500 x 1700	20 (4+4+5+7)	33	455	69-91	84-106	54-76	15	173	0,97	0,97	C-E-D
5020128506000700	600 x 700	9 (3+6)	33	555	69-91	84-106	54-76	15	149	0,40	0,4	C-E-D
5020128506001000	600 x 1000	12 (3+4+5)	33	555	69-91	84-106	54-76	15	142	0,57	0,57	C-E-D
5020128506001250	600 x 1250	15 (4+5+6)	33	555	69-91	84-106	54-76	15	177	0,71	0,71	C-E-D
5020128506001550	600 x 1550	18 (4+4+5+5)	33	555	69-91	84-106	54-76	15	163	0,88	0,88	C-E-D
5020128506001700	600 x 1700	20 (4+4+5+7)	33	555	69-91	84-106	54-76	15	173	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020128503000700	193	659	251	856
5020128503001000	266	908	346	1180
5020128503001250	332	1133	432	1474
5020128503001550	405	1382	527	1798
5020128503001700	447	1525	582	1985
5020128504000700	247	843	322	1099
5020128504001000	339	1156	441	1504
5020128504001250	423	1443	550	1876
5020128504001550	515	1757	670	2285
5020128504001700	569	1941	740	2524
5020128505000700	305	1041	397	1354
5020128505001000	415	1416	540	1842
5020128505001250	519	1770	675	2302
5020128505001550	629	2145	818	2790
5020128505001700	696	2374	905	3087
5020128506000700	364	1242	474	1617
5020128506001000	495	1688	644	2197
5020128506001250	618	2108	804	2742
5020128506001550	748	2551	973	3318
5020128506001700	829	2827	1078	3676

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020128503000700	3,8	4,3	0,02	800 x 340 x 55
5020128503001000	5,1	5,8	0,03	1100 x 340 x 55
5020128503001250	6,3	7,1	0,03	1350 x 340 x 55
5020128503001550	7,7	8,6	0,04	1650 x 340 x 55
5020128503001700	8,4	9,5	0,04	1800 x 340 x 55
5020128504000700	4,4	5	0,02	800 x 440 x 55
5020128504001000	5,9	6,7	0,03	1100 x 440 x 55
5020128504001250	7,3	8,3	0,04	1350 x 440 x 55
5020128504001550	8,8	10	0,04	1650 x 440 x 55
5020128504001700	9,7	11	0,05	1800 x 440 x 55
5020128505000700	5	5,7	0,03	800 x 540 x 55
5020128505001000	6,7	7,7	0,04	1100 x 540 x 55
5020128505001250	8,3	9,5	0,05	1350 x 540 x 55
5020128505001550	10	11,4	0,05	1650 x 540 x 55
5020128505001700	11	12,6	0,06	1800 x 540 x 55
5020128506000700	5,5	6,5	0,05	800 x 640 x 85
5020128506001000	7,5	8,7	0,06	1100 x 640 x 85
5020128506001250	9,2	10,7	0,08	1350 x 640 x 85
5020128506001550	11,1	12,9	0,09	1650 x 640 x 85
5020128506001700	12,3	14,2	0,1	1800 x 640 x 85