

POYRAZ LINE

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020128603000700	300 x 700	6 (2+2)	26	255	70-90	85-105	55-75	15	172	0,40	0,4	C-E-D
5020128603001000	300 x 1000	8 (2+2)	26	255	70-90	85-105	55-75	15	180	0,57	0,57	C-E-D
5020128603001200	300 x 1200	10 (2+2)	26	255	70-90	85-105	55-75	15	159	0,68	0,68	C-E-D
5020128603001500	300 x 1500	12 (2+2)	26	255	70-90	85-105	55-75	15	166	0,85	0,85	C-E-D
5020128603001700	300 x 1700	14 (2+2)	26	255	70-90	85-105	55-75	15	154	0,97	0,97	C-E-D
5020128604000700	400 x 700	6 (2+2)	26	355	70-90	85-105	55-75	15	172	0,40	0,4	C-E-D
5020128604001000	400 x 1000	8 (2+2)	26	355	70-90	85-105	55-75	15	180	0,57	0,57	C-E-D
5020128604001200	400 x 1200	10 (2+2)	26	355	70-90	85-105	55-75	15	159	0,68	0,68	C-E-D
5020128604001500	400 x 1500	12 (2+2)	26	355	70-90	85-105	55-75	15	166	0,85	0,85	C-E-D
5020128604001700	400 x 1700	14 (2+2)	26	355	70-90	85-105	55-75	15	154	0,97	0,97	C-E-D
5020128605000700	500 x 700	6 (2+2)	26	455	70-90	85-105	55-75	15	172	0,40	0,4	C-E-D
5020128605001000	500 x 1000	8 (2+2)	26	455	70-90	85-105	55-75	15	180	0,57	0,57	C-E-D
5020128605001200	500 x 1200	10 (2+2)	26	455	70-90	85-105	55-75	15	159	0,68	0,68	C-E-D
5020128605001500	500 x 1500	12 (2+2)	26	455	70-90	85-105	55-75	15	166	0,85	0,85	C-E-D
5020128605001700	500 x 1700	14 (2+2)	26	455	70-90	85-105	55-75	15	154	0,97	0,97	C-E-D
5020128606000700	600 x 700	6 (2+2)	26	555	70-90	85-105	55-75	15	172	0,40	0,4	C-E-D
5020128606001000	600 x 1000	8 (2+2)	26	555	70-90	85-105	55-75	15	180	0,57	0,57	C-E-D
5020128606001200	600 x 1200	10 (2+2)	26	555	70-90	85-105	55-75	15	159	0,68	0,68	C-E-D
5020128606001500	600 x 1500	12 (2+2)	26	555	70-90	85-105	55-75	15	166	0,85	0,85	C-E-D
5020128606001700	600 x 1700	14 (2+2)	26	555	70-90	85-105	55-75	15	154	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020128603000700	173	590	225	768
5020128603001000	242	826	315	1075
5020128603001200	294	1003	383	1307
5020128603001500	363	1238	472	1610
5020128603001700	415	1416	540	1842
5020128604000700	210	717	273	931
5020128604001000	291	993	379	1293
5020128604001200	355	1211	462	1576
5020128604001500	436	1487	567	1934
5020128604001700	501	1709	652	2224
5020128605000700	248	846	323	1102
5020128605001000	342	1167	445	1518
5020128605001200	419	1429	545	1859
5020128605001500	513	1750	667	2275
5020128605001700	590	2012	767	2616
5020128606000700	288	983	375	1279
5020128606001000	395	1347	514	1753
5020128606001200	485	1654	631	2152
5020128606001500	592	2019	770	2626
5020128606001700	682	2326	887	3025

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020128603000700	3,5	4	0,02	800 x 340 x 55
5020128603001000	4,7	5,4	0,03	1100 x 340 x 55
5020128603001200	5,6	6,4	0,03	1300 x 340 x 55
5020128603001500	6,9	7,8	0,03	1600 x 340 x 55
5020128603001700	7,8	8,9	0,04	1800 x 340 x 55
5020128604000700	3,9	4,5	0,02	800 x 440 x 55
5020128604001000	5,2	6	0,03	1100 x 440 x 55
5020128604001200	6,3	7,2	0,04	1300 x 440 x 55
5020128604001500	7,6	8,8	0,04	1600 x 440 x 55
5020128604001700	8,7	10	0,05	1800 x 440 x 55
5020128605000700	4,2	5	0,03	800 x 540 x 55
5020128605001000	5,7	6,7	0,04	1100 x 540 x 55
5020128605001200	6,9	8,1	0,04	1300 x 540 x 55
5020128605001500	8,4	9,8	0,05	1600 x 540 x 55
5020128605001700	9,6	11,2	0,06	1800 x 540 x 55
5020128606000700	4,6	5,5	0,05	800 x 640 x 85
5020128606001000	6,2	7,5	0,06	1100 x 640 x 85
5020128606001200	7,6	9	0,08	1300 x 640 x 85
5020128606001500	9,2	10,9	0,09	1600 x 640 x 85
5020128606001700	10,5	12,5	0,1	1800 x 640 x 85