

CREA PLUS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5020129203000600	300 x 600	5 (2+3)	40	255	84/110	125/151	44/70	4	163	0,34	0,34	C-E-D
5020129203000830	300 x 830	8 (3+5)	40	255	84/110	125/151	44/70	4	138	0,47	0,47	C-E-D
5020129203001150	300 x 1150	10 (3+3+4)	40	255	84/110	125/151	44/70	4	146	0,66	0,66	C-E-D
5020129203001320	300 x 1320	12 (3+4+5)	40	255	84/110	125/151	44/70	4	146	0,75	0,75	C-E-D
5020129203001700	300 x 1700	15 (3+3+4+5)	40	255	84/110	125/151	44/70	4	140	0,97	0,97	C-E-D
5020129204000600	400 x 600	5 (2+3)	40	355	84/110	125/151	44/70	4	163	0,34	0,34	C-E-D
5020129204000830	400 x 830	8 (3+5)	40	355	84/110	125/151	44/70	4	138	0,47	0,47	C-E-D
5020129204001150	400 x 1150	10 (3+3+4)	40	355	84/110	125/151	44/70	4	146	0,66	0,66	C-E-D
5020129204001320	400 x 1320	12 (3+4+5)	40	355	84/110	125/151	44/70	4	146	0,75	0,75	C-E-D
5020129204001700	400 x 1700	15 (3+3+4+5)	40	355	84/110	125/151	44/70	4	140	0,97	0,97	C-E-D
5020129205000600	500 x 600	5 (2+3)	40	455	84/110	125/151	44/70	4	163	0,34	0,34	C-E-D
5020129205000830	500 x 830	8 (3+5)	40	455	84/110	125/151	44/70	4	138	0,47	0,47	C-E-D
5020129205001150	500 x 1150	10 (3+3+4)	40	455	84/110	125/151	44/70	4	146	0,66	0,66	C-E-D
5020129205001320	500 x 1320	12 (3+4+5)	40	455	84/110	125/151	44/70	4	146	0,75	0,75	C-E-D
5020129205001700	500 x 1700	15 (3+3+4+5)	40	455	84/110	125/151	44/70	4	140	0,97	0,97	C-E-D
5020129206000600	600 x 600	5 (2+3)	40	555	84/110	125/151	44/70	4	163	0,34	0,34	C-E-D
5020129206000830	600 x 830	8 (3+5)	40	555	84/110	125/151	44/70	4	138	0,47	0,47	C-E-D
5020129206001150	600 x 1150	10 (3+3+4)	40	555	84/110	125/151	44/70	4	146	0,66	0,66	C-E-D
5020129206001320	600 x 1320	12 (3+4+5)	40	555	84/110	125/151	44/70	4	146	0,75	0,75	C-E-D
5020129206001700	600 x 1700	15 (3+3+4+5)	40	555	84/110	125/151	44/70	4	140	0,97	0,97	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5020129203000600	187	638	244	833
5020129203000830	280	955	364	1242
5020129203001150	366	1249	476	1624
5020129203001320	430	1467	559	1907
5020129203001700	545	1859	709	2418
5020129204000600	244	833	318	1085
5020129204000830	371	1266	483	1648
5020129204001150	480	1637	624	2128
5020129204001320	568	1937	739	2520
5020129204001700	717	2445	933	3182
5020129205000600	304	1037	396	1351
5020129205000830	467	1593	608	2074
5020129205001150	600	2046	780	2660
5020129205001320	711	2425	925	3155
5020129205001700	896	3056	1165	3973
5020129206000600	366	1249	476	1624
5020129206000830	566	1931	736	2510
5020129206001150	724	2469	942	3213
5020129206001320	860	2933	1118	3813
5020129206001700	1082	3690	1407	4798

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5020129203000600	3,7	4,2	0,02	700 x 440 x 55
5020129203000830	5,4	6,1	0,03	930 x 440 x 55
5020129203001150	6,9	7,9	0,04	1250 x 440 x 55
5020129203001320	8,1	9,4	0,05	1420 x 540 x 55
5020129203001700	10,2	11,8	0,06	1800 x 540 x 55
5020129204000600	4,2	4,9	0,03	700 x 540 x 55
5020129204000830	6,3	7,1	0,03	930 x 540 x 55
5020129204001150	8	9,2	0,04	1250 x 540 x 55
5020129204001320	9,4	10,9	0,05	1420 x 640 x 55
5020129204001700	11,8	13,7	0,07	1800 x 640 x 55
5020129205000600	4,8	5,6	0,03	700 x 640 x 55
5020129205000830	7,1	8,1	0,04	930 x 640 x 55
5020129205001150	9,1	10,4	0,05	1250 x 640 x 55
5020129205001320	10,7	11,6	0,03	1420 x 340 x 60
5020129205001700	13,5	14,5	0,04	1800 x 340 x 60
5020129206000600	5,3	5,8	0,02	700 x 340 x 60
5020129206000830	8	8,6	0,02	930 x 340 x 60
5020129206001150	10,2	11	0,03	1250 x 340 x 60
5020129206001320	12,1	13,1	0,04	1420 x 440 x 55
5020129206001700	15,1	16,4	0,05	1800 x 440 x 55