

ALPHA LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030100104001200	400X1200	8	47	355	56,5	93,5	43	15	30	1,28	C-E-D
5030100104001400	400X1400	10	47	355	56,5	93,5	43	15	30	1,40	C-E-D
5030100104001600	400X1600	12	47	355	56,5	93,5	43	15	30	1,51	C-E-D
5030100104001800	400X1800	14	47	355	56,5	93,5	43	15	30	1,62	C-E-D
5030100105001200	500X1200	10	47	455	56,5	93,5	43	15	30	1,56	C-E-D
5030100105001400	500X1400	12	47	455	56,5	93,5	43	15	30	1,67	C-E-D
5030100105001600	500X1600	14	47	455	56,5	93,5	43	15	30	1,79	C-E-D
5030100105001800	500X1800	16	47	455	56,5	93,5	43	15	30	1,90	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030100104001200	368	1255	479	1634
5030100104001400	392	1337	510	1740
5030100104001600	419	1429	545	1859
5030100104001800	450	1535	585	1995
5030100105001200	519	1770	675	2302
5030100105001400	543	1852	706	2408
5030100105001600	570	1944	741	2527
5030100105001800	601	2050	782	2667

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.12	9.05	0,06	432X1330X89
7.71	9.87	0,06	432X1530X89
8.31	10.70	0,07	432X1730X89
8.91	11.52	0,08	432X1930X89
9,06	11.26	0,07	532X1330X89
9.66	12.12	0,08	532X1530X89
10.26	12.98	0,09	532X1730X89
10.85	13.84	0,10	532X1930X89

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel