

ASITA LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030100404001200	400X1200	9	47	355	56,5	86,5	43	15	30	1,42	C-E-D
5030100404001400	400X1400	11	47	355	56,5	86,5	43	15	30	1,46	C-E-D
5030100404001600	400X1600	13	47	355	56,5	86,5	43	15	30	1,58	C-E-D
5030100404001800	400X1800	15	47	355	56,5	86,5	43	15	30	1,69	C-E-D
5030100405001200	500X1200	10	47	455	56,5	86,5	43	15	30	1,56	C-E-D
5030100405001400	500X1400	12	47	455	56,5	86,5	43	15	30	1,67	C-E-D
5030100405001600	500X1600	14	47	455	56,5	86,5	43	15	30	1,79	C-E-D
5030100405001800	500X1800	16	47	455	56,5	86,5	43	15	30	1,90	C-E-D
5030100406001200	600X1200	11	47	555	56,5	86,5	43	15	30	1,77	C-E-D
5030100406001400	600X1400	13	47	555	56,5	86,5	43	15	30	1,88	C-E-D
5030100406001600	600X1600	15	47	555	56,5	86,5	43	15	30	2,00	C-E-D
5030100406001800	600X1800	17	47	555	56,5	86,5	43	15	30	2,11	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030100404001200	497	1695	647	2207
5030100404001400	456	1555	593	2023
5030100404001600	483	1648	628	2142
5030100404001800	514	1753	669	2282
5030100405001200	529	1804	688	2347
5030100405001400	553	1886	719	2452
5030100405001600	580	1978	754	2572
5030100405001800	611	2084	795	2711
5030100406001200	627	2139	816	2783
5030100406001400	651	2220	847	2889
5030100406001600	678	2312	882	3008
5030100406001800	709	2418	922	3145

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.26	10.19	0,06	432X1330X89
8.30	10.46	0,06	432X1530X89
8.90	11.29	0,07	432X1730X89
9.50	12.11	0,08	432X1930X89
9.03	11.23	0,07	532X1330X89
9.63	12.09	0,08	532X1530X89
10.23	12.95	0,09	532X1730X89
10.82	13.81	0,10	532X1930X89
10.30	12.76	0,08	632X1330X89
10.90	13.66	0,09	632X1530X89
11.50	14.55	0,10	632X1730X89
12.09	15.45	0,11	632X1930X89

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel