

ASITA DOUBLE LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030100504001200	400X1200	9	61	355	56,5	87	26	15	30	1,35	C-E-D
5030100504001400	400X1400	11	61	355	56,5	87	26	15	30	1,46	C-E-D
5030100504001600	400X1600	13	61	355	56,5	87	26	15	30	1,58	C-E-D
5030100504001800	400X1800	15	61	355	56,5	87	26	15	30	1,69	C-E-D
5030100505001200	500X1200	10	61	455	56,5	87	26	15	30	1,56	C-E-D
5030100505001400	500X1400	12	61	455	56,5	87	26	15	30	1,67	C-E-D
5030100505001600	500X1600	14	61	455	56,5	87	26	15	30	1,79	C-E-D
5030100505001800	500X1800	16	61	455	56,5	87	26	15	30	1,90	C-E-D
5030100506001200	600X1200	11	61	555	56,5	87	26	15	30	1,77	C-E-D
5030100506001400	600X1400	13	61	555	56,5	87	26	15	30	1,88	C-E-D
5030100506001600	600X1600	15	61	555	56,5	87	26	15	30	2,00	C-E-D
5030100506001800	600X1800	17	61	555	56,5	87	26	15	30	2,11	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030100504001200	501	1709	652	2224
5030100504001400	524	1787	682	2326
5030100504001600	551	1879	717	2445
5030100504001800	583	1989	758	2585
5030100505001200	618	2108	804	2742
5030100505001400	642	2190	835	2848
5030100505001600	669	2282	870	2967
5030100505001800	700	2387	910	3104
5030100506001200	736	2510	957	3264
5030100506001400	760	2592	988	3370
5030100506001600	787	2684	1024	3492
5030100506001800	818	2790	1064	3629

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.84	10.86	0,06	432X1330X103
9.44	11.68	0,07	432X1530X103
10.04	12.51	0,08	432X1730X103
10.64	13.33	0,09	432X1930X103
10.58	12.87	0,08	532X1330X103
11.18	13.73	0,09	532X1530X103
11.78	14.60	0,10	532X1730X103
12.37	15.46	0,11	532X1930X103
12.26	14.82	0,09	632X1330X103
12.86	15.72	0,10	632X1530X103
13.46	16.62	0,12	632X1730X103
14.05	17.53	0,13	632X1930X103

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel