

AVVO LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030100604001200	400X1200	11	97	355	56,5	105	8	15	30	1,46	C-E-D
5030100604001400	400X1400	13	97	355	56,5	105	8	15	30	1,57	C-E-D
5030100604001600	400X1600	15	97	355	56,5	105	8	15	30	1,68	C-E-D
5030100604001800	400X1800	17	97	355	56,5	105	8	15	30	1,80	C-E-D
5030100605001200	500X1200	12	97	455	56,5	105	8	15	30	1,66	C-E-D
5030100605001400	500X1400	14	97	455	56,5	105	8	15	30	1,78	C-E-D
5030100605001600	500X1600	16	97	455	56,5	105	8	15	30	1,89	C-E-D
5030100605001800	500X1800	18	97	455	56,5	105	8	15	30	2,00	C-E-D
5030100606001200	600X1200	14	97	555	56,5	105	8	15	30	1,93	C-E-D
5030100606001400	600X1400	16	97	555	56,5	105	8	15	30	2,04	C-E-D
5030100606001600	600X1600	18	97	555	56,5	105	8	15	30	2,16	C-E-D
5030100606001800	600X1800	20	97	555	56,5	105	8	15	30	2,27	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030100604001200	511	1743	665	2268
5030100604001400	535	1825	696	2374
5030100604001600	562	1917	731	2493
5030100604001800	593	2023	771	2630
5030100605001200	596	2033	775	2643
5030100605001400	620	2115	806	2749
5030100605001600	647	2207	842	2872
5030100605001800	678	2312	882	3008
5030100606001200	735	2507	956	3260
5030100606001400	758	2585	986	3363
5030100606001600	785	2677	1021	3482
5030100606001800	817	2786	1063	3625

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.18	11.29	0,08	432X1330X139
9.77	12.13	0,10	432X1530X139
10.37	12.96	0,11	432X1730X139
10.97	13.80	0,12	432X1930X139
10.57	12.96	0,10	532X1330X139
11.17	13.84	0,12	532X1530X139
11.77	14.71	0,13	532X1730X139
12.36	15.58	0,15	532X1930X139
12.56	15.22	0,12	632X1330X139
13.16	16.14	0,14	632X1530X139
13.75	17.04	0,16	632X1730X139
14.35	17.96	0,17	632X1930X139

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel